

Douglas County Surveyor's Record of
Government Corners Renewed

T 26 T. S. R 2 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

118

Section corner for Secs. 6, 5, 7 and 8

Found - 1959 GLO brass cap, in place.
Down or broken remains of Madrone, N.51 1/2°E., 15.8 ft. to root hole. (not fd. by Weyerhaeuser Co. records 7/7/7)(Orig. record 13", N.51 1/2°E., 24 lks. 1959) 1883 Rec. N.45°E.)
Evidence of old Madrone scattered by logging at approx. location of orig. 20" Madrone, down and rotted S.50°E., 47 lks.
Down 38" Fir (W. Co. 7/7/67 record identified this BT S.60 1/2°W., 21.6 ft.)
50" Fir (W. Co. 1967 record identified this BT, N.12°W., 38.1 ft.)
Down 16" Fir, face partly healed, BT tag. (1967 record identified this BT, N.25°E., 85.7 ft.)
28" Fir stump, face and plates intact. (1967 record identified this BT, S.71°E., 59.6 ft.)
22" Fir, down healed face and plate intact. (1967 record identified this BT S.40°W., 58.0ft.)
48" Fir, face and plate intact, (1967 record identified this BT N.22°W., 36.6 ft.)

Accessories added this date:

W nails and plates on:

40" Fir stump, N.56°E., 59.2 ft.
54" Fir stump, N.64°E., 65.2 ft.

4/15/77

119

North 1/4 Corner for Sec. 8

Found - 1959 GLO brass cap in mound of stone.
18" Fir, face healed over; BT plate bears S.25°E., 18.6 ft. center measurement.
12" Fir, face healed over; BT plate, bears N.40°W., 6.6 ft. center measurement. See Ren. #9

Accessories added this date:

36" Fir, N.53°E., 32.5 ft. with W nail and plate
28" Fir, S.11°E., 14.0 ft. with W nail and plate.

4/18/77

120

W.C. to 1/4 Corner for Sec. 24 only.

Found - 1" I.P. firmly set 4" above ground with a 1916 US GLO brass cap properly marked.
A 43" D. Fir snag, with no scribing visible on rotted blaze bears N.63°W., 35.6 ft.
A protruding point of bluff with no orig. chisel marks visible remarked "X BO" bears S.59°W., 3.7 ft. (Rec. S.51°W., 4.0 ft.)
New BT's- A 10" Hemlock bears N.13°W., 16.9 ft. scribed "X BT" on a double blaze with brass washer stamped "LS 397" nailed into lower blaze.

A 4"x4" X is at the exact bearing point.

121

W.C. to 1/4 corner for Sec. 19 only of T.26-3.

Found - Orig. 15" Cedar, opened to find scribe marks "1/4 S19" visible bears S.24°E., 11.2 ft.
Set - 2" x 30" I.P. 18" in the ground on solid rock, in a 3 ft. diam. times 2 ft. high mound of stone with a 3" brass cap mkd.
T26S R2W RIW 1981 LS 397

1/4 W.C.
S19

New BT's- A 7" Cedar bears S.22°E., 51.2 ft. scribed "X BT"
A 12" D. Fir bears N.41°E., 13.2 ft. scribed "X BT"

2/81

122

Sec. corner common to Sec's. 29, 30, 31, & 32.

Found - 2 1/2 " Aluminum Cap on a 3/4 " I. Pipe (not of record), firmly set, protruding 6" out of a small mound of Stone, marked: U.S. P.C. Property Cor. T26S R2W 30 29 31 32 PE 4287 1963 Do not disturb.

No trace of orig stone.

BT's- 15" Fir blowdown (orig 10"), with well healed blaze bears N.66°E., 16.5-ft. to stump hole.
14" Fir blowdown (orig. 12"), with well healed blaze bears S.7°E., 11.9-ft. to stump hole.
23" Cedar(orig. 20"), alive with well healed blaze, bears

Continued...OVER...

Glen McChesney
For: Weyerhaeuser
Company
April, 1977
(filed 12/80)
C.S. 58/8

George Grubb
For: U.S. Forest
Service
Feb. 1981
M 86 - 68

Gregory E. Quibell
Deputy Doug. County
Surveyors Office
Debbie Stewart, wit.
Sept. 17, 1981
C.S. 61 / 27