

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 26 S T. S. R 2 W R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21981

...CONT....

122

Gregory E. Quibell

Sept. 17, 1981
C.S. 61/27

(23" Cedar) bears S.38°W., 13.9-ft.
23" Fir (orig. 14") with well healed blaze bears N.7°W.,
19.2-ft. (Rec. N.9°W., 18.5-ft.)
New BT's- 10" Cedar scribed "T26S R2W S29 CS BT" in double blaze, bears
N.75°E., 40.1-ft.
9" Cedar scribed "T26S R2W S32 CS BT" in double blaze, bears
S.3°E., 12.7-ft.
Note - Corner is North 40-ft. of Road Centerline.

9/17/81

Center 1/4 of Sec. 26.

123

T.E. Shrum, Jr.
for: Champion Int.
Sept. 15, 1981
M 89-28

Set - 2 1/2" Aluminum Cap on a 1" x 36" I.P. (1981) C1/4 SEC 26
New BT's- 4" D. Fir bears N.21°30'W., 6.5-ft.
20" R. Cedar bears S.55°W., 32.8-ft.

9/15/81

East 1/4 corner to Sec. 27 only.

124

RE-NEWED SEE CORNER NO. #140
Set - 2 1/2" Aluminum Cap on a 1" x 36" I.P. (1981) 1/4 corner 27 only
New BT's- 6" Hemlock bears N.62°W., 10.4-ft.
10" Hemlock bears N.31°30'W., 20.0-ft.

9/15/81

1/4 Corner common to Secs. 5, & 6.

125

(Reference notes C.S. 59/30 now attached to this renewal.)

Found - 1959 BLM B.C., firmly set in mound of rocks, Ref. notes.
properly marked. Also, see Ren.#106.

Gregory E. Quibell
Deputy Doug. County
Surveyors Office
Teresa Buley, witness
Dec. 9, 1981
C.S. 61/29

BTs - 48" Fir w/W nail per Ref. notes, bears N.61°W., 14.6-ft.
to nail. Tree alive & well, shows good scar.
22" Cedar stump w/scribed "1/4 S5 BT" visible as per Ref. notes,
bears S.41°E., 10.6-ft.
60" Fir w/W nail per Ref. notes, bears N.65°E., 34.2-ft. to
nail. Tree alive & well.

New BTs - 14" Hemlock scribed "1/4 S6 CS BT" in dbl.blaze bears N.5°W., 14.7'.
12" Hemlock scribed "1/4 S5 CS BT" in dbl.blaze bears S.26 1/2°E.,
25.1-ft.

Note - See C.S. 61/29 for sketch & Ref. notes. 12/9/81

126

North 1/4 cor. for Section 27 only.

Set - A 2 1/2" alum. cap set on a 7/8" x 36" I.P. properly marked and
stamped "PLS 1988"

New BTs - 13" cedar bears S.36°E., 12.8 ft. scribed "1/4 S27 BT".
6" hemlock bears S.67°W., 20.2 ft. scribed "1/4 S27 BT".

Closing corner for Secs. 22 and 27 only. *FD, OK FEB. 2004 D. EDWARDS M 143-66* **127**

Set - 2 1/2" alum. cap set on a 7/8" x 36" I.P. properly marked and
stamped "PLS 1988".

New BTs - 6" cedar bears N.79°W., 36.4 ft. scribed "T26S R2W S22 CC BT".
6" fir, bears S.29°W., 22.3 ft. scribed "T26S R2W S27 CC BT".

Found - a 5/8" iron rod that bears S.89°39'44"W., 2.40 ft.
Orig. 44" fir stump, bears N.30°15'W., 11.2 ft. closed face.
Orig., 14" rotten hemlock stump bears S.50°W., 37.2 ft.
Scribed "26S R2W S27 CC BT."

128

1/4 Corner for Secs. 27 and 28.

Set - 2 1/2" alum. cap on a 7/8" x 36" I.P. properly marked and stamped
"PLS 1988" at the exact position of the orig. 1909 stone,
5"x15"x10" found. No markings on stone, which was partially
buried alongside the I.P.

Found - Orig. BT, 21" hemlock bears N.60°W., 9.2 ft. Scribed 1/4 S28 BT.
New BT - 9" hemlock bears N.56°E., 35.3 ft. scribed 1/4 S27 BT.

129

Center 1/4 corner for Sec. 27.

Set - 2 1/2" alum. cap set on a 7/8" x 36" iron pipe properly marked
and stamped "PLS 1988".

New BTs - 20" fir, bears S.48°E., 13.9 ft. scribed C 1/4 S27 BT.
8" hemlock bears S.64°30'W., 23.7 ft. scribed C 1/4 S27 BT.

6-8/83

Ronald G. Geisler L.S. #1988
For: Champion International Corp.
June - August 1983
M 94 - 80