

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 26

T. S.

R 2

R. W. W. M.

MOKE-CHAPMAN CO., EUGENE, ORE. 21881

CONT - - -

137

(Section corner for 1 and 12 only)
Set - We removed "1/4 from brass cap and build up a 2 ft. dia. 1 ft. high mound of stone.
New BTs -14" dia. R. cedar double blazed and scribed "T26S R2W S1 CS BT" bears N.58°W., 26.2 ft.
4" dia. R. cedar double blazed and scribed "X BT" bears S.48 1/2°W., 31.2 ft.
Corner lies at southeast corner of a new clear cut.

138

Closing Corner for Sections 6 and 7 only, T.26-1 (1910 orig., Mensch)
From the 1910 Mensch retracement:
Found - An original 16 x 12 x 12 inch basalt stone (now measuring 7" x 12" x 2" high on portion protruding from ground. Because of severe frost cracking, we do not remove stone to examine further.
From Garrett survey M47-7:
Found - On the east edge of above stone is a 1/2" I.D. iron pipe protruding 3" above ground.
(Bearings & distances measured from 1/2" I.D. iron pipe.
Found - From 1910 retracement, a madrone, 6" dia. now a 9" DBH madrone bears S.25°E., 18.9 ft. distant as per record. No evidence found of scribing in previously opened blaze. No evidence found of northeast chinquapin BT.
New Accessories: We add new closing corner from Garrett survey M47-7. a 3" dia. brass cap on a 2" I.D. iron pipe protruding 8" above ground bears East, 12.04 ft. dist. (as per M47-7). We also tie southeast bearing tree for the above mentioned cap: Originally an 11" fir scribed T26S R1W S7 BT) now a 13" DBH D. fir with a fully healed double blaze bears S.59°E., 42.5 ft. A new bearing tree, a 15" DH D. Fir scribed CC, T26S, R1W S6 CS BT on a double blaze bears N.55°E., 14.6 ft.
Monument is at east edge of old clear cut on a still definite north south cutting line and is south approx 350 ft. from a creek coursing N.75°E.

- - - AND - - -

Closing Corner for Sections 6 and 7 only, T.26-1 (From Ren. #101)
Found - a 3" dia. brass cap mkd T26S R2W S12 S6 S7 1972 RPLS 544 on a 2" I.D. iron pipe firmly set and protruding 8" above ground.
13" Fir now a 15" DH douglas fir with a fully healed double blaze bears N.6°E., 10.1 ft. distant.
An 11" Fir now a 13" DBH D. Fir with a fully healed double blaze bears S.48 1/2°E., 32.8 ft.
A USFS metal witness sign and post bears South, 4.5 ft. previously unrecorded.
New Accessories: We add original 1910 closing corner as set by Mensch: This closing corner is monumented by the original 16x12x12 basalt stone, now a broken 12"x7" stone protruding 2" above ground with no marks visible. (We do not disturb) and by Garrett's 1/2" I.D. iron pipe on east edge of stone protruding approx 3" above ground. This iron pipe bears West, 12.04 ft. from brass cap monument (agrees with record bearing and distance from M47-7)
Monument is on east edge of old clear cut on a still definite north-south cutting line and is south approx. 350 ft. from a creek coursing N.75°E.

4/19/87

139

Section Corner for Secs. 30 and 31; and Secs. 25 & 36 of T.26-3
Found - 1966 County 2 1/2" brass cap on a 1" iron pipe extends 12" above ground. Ren. #34
9" D. fir bears S.37°W., 7.5 ft. Healed face. (1966)
9" D. fir bears N. 5° W., 16.4 ft. Healed face. (1966)
36" D. fir bears N.45°W., 21.8 ft. Chopped face. Brag marks visible. (Original)
8" D. fir now down and uprooted bears N.61°E., 4.5 ft. (1966)
New BT - 5" D. fir bears N.74°E., 23.3 ft. scribed "T26S R2W S30 BT".

6/30/87

Douglas County Surveyors Office
Stephen John Flause
R. W. Smith
April 19, 1987
C.S. 62/40

Ronald Geisler
For: Champion
International
Crew: Lynn Sibley
Dean Turner
June 30, 1987
C.S. 63/60