

Douglas County Surveyor's Record of
Government Corners Renewed

26

T. S.

2

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91881

163

Cor. Secs. 14, 15, 22, & 23

Fd. Cont- A 12" Fir now 16" DBH D.Fir with fully healed single blaze bears N.51½°E. 42.9' (rec N.51½°E. 42.2')
5" Laurel now a rotted broken Madrone stump (good root position) with no discernible scribing bears S.34°W., 15.5' (rec. S.33°W., 16.5')
18" Fir now 28" DBH D.Fir with a fully healed single blaze bears N.70½°W., 49.5' (rec. N.71°W., 48.8')

From the 1957 DCSO renewal 1 renewal BT is fd:

16" Cedar, now a 16" Incense Cedar with a fully healed double blaze bears S.1½°E., 128.4' (rec. S.1°E., 128.4')

A BT of unknown origin:

17" DBH D.Fir with an apparent fully healed single blaze (we do not open) bears S.35°W., 44.2' (rec. on fd. BT tag has erroneous reverse bearing S.35°W., and a dist. of 67 lks; survey attributed to "P.O.P.")

New - The previously described fd. stone is set in the fd. hole with 2 notches on one side facing east & 3 notches on another side facing south. Along the west edge of the above stone is set a 2 3/8" brass cap on a 30" galvanized iron pipe. The stone is set with its top flush with the ground & the brass cap monument protrudes approx 6" above the ground. Cap mkd:

DOUGLAS COUNTY SURVEYOR

T26S R2W

S 15 | S 14

S 22 | S 23

2004

Note - No new accessories
Monument is on gradual southerly facing forested slope.
Compass decl. 16½°E.

Douglas Co.
Surveyors Office
Stephen J. Flause
John A. Pike
1/6/2004
C.S. File 67/13-6

164

1/4 Cor. Secs. 21 & 28

Found - 3/4" iron rod and both BTs described by Tracy in 1967 (renewal #87) from which:
22" fir face evident, Tracy BT, new tag & spike bears; N.44°18'E., 17.6 ft. to spike. (Tracy, N.47°E., 18.7')
31" cedar, OBT, scribing visible, bears S.14°E. 9.9 ft.

New - 14" fir, scribed "S28 ¼ BT", new BT, bears S.85°22'W., 26.1 ft to spike.
16" fir, scribed "S21 ¼ BT", new BT, bears N.26°36'W., 33.7 ft to spike.

Note - BT measurements to orig. & other fd. BTs are listed to the center of the tree unless otherwise noted. BT tags placed on trees marked in this survey, list bearing & distance from the head of a 6" spike, placed in the root collar, to the corner monument.

Tony Hostetter
For: Seneca Jones
Timber Co.
12/2005
M149-17

(S14E28)