

Douglas County Surveyor's Record of
Government Corners Renewed

26 T. S. 3 R. W. W. M.

ROSE CHAPMAN CO., EUGENE, ORE., 91002

10
COR. BET. 19-24. West Boundary T. 26 S. R.3W.
Set Oak post from which the original treest
A Black Oak 10" dia. S.40°E., 44 lks.
A Black Oak 14" dia. S.25°W., 35 lks.
Mark new tree
A Black Oak 30" dia. N.30°W., 12 lks.

J.W. Cole Dep.
Wit.
A. Schloeman
S.C. Bruce
Cecil Black
April 17, 1916.
C.S. No. 12, P. 277

11
COR. BET. SECS. 29 and 30.
I reestablished corner from the old decayed original B.T.s
and note that bearings and distances do not agree, and sit
in corner at an interpolated point. Corner is W. Oak post
5 x 5 x 30" from which
A B. Oak 5" dia. bears S.21 1/4°E., 4.4 ft. C.S. S.B.T.
A. W. Oak 14" dia. bears S.71°W., 35.9 ft. C.S. S.B.T.
B.T. bearing S.21 1/4°E., 4.4 ft. gone. I set a 2 x 30" I.P.
for corner, and marked a 10" fir. N.83°E., 24.7 ft. for
B.T. gone. H.L. Eppstein Co. Sur. 1934

Jan. 20, 1917
Wit.
M.B. Germond
F.S. Blakely
F.B. Lane
W. Smith
No Ref. Pd.

12
COR. 30-29-31-32.
Set corner 5"x 5"x 4' Cedar Post from old B.T. in Section 30
other trees gone, Marked new B.T.
30" Black Oak, Marked S. 30 C.S.B.T., N.62°W., 21.8 ft.
24" Black Oak, Marked S. 29 C.S.B.T., N.44°E., 123 ft.
No trees near in secs. 31 and 32.

H.L. Eppstein
May 1934
Wit.
B.A. Lane
Verne Shrum
C.S. File
18/52

13
SEC. CORNER TO SECTION 7 and 18, T. 26 S. R.3 W. and SECTION
13 and 12 T.26 S.R.4W.
Established Corner from old B.T. which were standing and
scribe marks plain. Set 4" x 4" x 36" Oak Stake. Marked
new trees as follows
Black Oak 20" dia. bears N.28°W., 260 lks.
White Oak 12" dia. bears N.34°E., 38 lks.
Black Oak 8" dia. bears S.17°W., 34 lks.
Black Oak 15" dia. bears S.72°E., 82 lks.

H.L. Eppstein
D.C.S.
Wit. H.L. Smick
N.E. Richardson
Walter Osborne
March 30, 1921

14
CORNER TO SECTION 7 and 12. (T.26-4)
Renewed corner with 4 x 4 x 40" Cedar Stake from the old
B.T.s which I chopped into and found scribe marks. Marked
new trees as follows
W. Oak 30" dia. bears S.82°30'W., 153 lks.
W. Oak 14" dia. bears N.34°30'E., 148 lks.

H.L. Eppstein D.C.S.
Wit.
Bert Lane
N.E. Richardson
April 12, 1921

15
SEC. CORNER 1-6-7-12 T.26S. R 3 and 4 W.
Restablished corner from Two old B.T.S Set 4 x 4 x 40"
Cedar Stake. Marked two new B.T.s and Remarkd two old
B.T., old B.T.s
Red Fir 30" dia. bears N.10°W., 83 lks.
Red Fir 36" dia. bears N.26°E., 83 lks.
New B.T.s
Red Fir 15" dia. bears S.80°E., 60 lks.
Cedar 12" dia. bears S.4°W., 15 lks.

H.L. Eppstein
Dep. Co. Sur.
Apr. 1921
Wit. L.H. Smick
N.E. Richardson
Bert Lane

16
SECTION CORNER COMMON TO SECTIONS 31 and 36 T.25 S.R.3 and 4W.
AND SECTION 1 and 6 T.26 S.R.3 and 4 W.
Established Corner from old B.T.s which I chopped into and
found old Scribe Marks. Set 4 x 4 x 36" Oak Stake for Corner
and Marked B.T.s as follows
White Oak 12" dia. bears N.27°30'E., 77 lks.
Cedar 8" dia. bears N.33°W., 32 lks.
White Oak 13" dia. bears S.70°E., 94 lks.
Cedar 20" dia. bears S.16°W., 131 lks.

H.L. Eppstein
Dep. Co. Sur.
Apr. 1921
Wit. L.H. Smick
N.E. Richardson
Bert Lane

16-A
SECTION CORNER - 1/4 Corner North Side Section 6
Identified location from Original BT's. Drove 1 1/2" Iron Pipe
for corner from which: 16" Fir bears S.5°54'E. 144 ft.
18" Fir bears N.31°33'E. 66 ft.
Dec. 26, 1922

Ben B. Irving,
Deputy
Wit: E. Russell
W.C. Chapman
No Ref. Pd.

SEE CORNER NO. 78

SEE CORNER NO. 106/109

SEE CORNER NO. 107/110

SEE CORNER NO. 64

SEE CORNER NO. 152

SEE CORNER NO. 144

REFER TO
Gov't. Survey, 1958

78
11
12
13
14
15
16
16-A
101