

Douglas County Surveyor's Record of
Government Corners Renewed

26 T. S. 3 R. W. W. M.

June 6, 1921
J. W. Cole Deputy
L. H. Smick Asst.
Witnesses
Seth Mathews
Floyd Watson

March 18, 1922
G. G. Stewart Deputy C. S.
Witnesses
Max Shellabarger
M. L. L. Kimmel

J. W. Cole C.S.
July 12, 1923
Present
C. W. Springer
M. L. L. Kimmel
Joe DeBernardi

C. W. Springer
D. C. S.
July 16, 1923
Present
N. E. Richardson
M. L. L. Kimmel

CORNER TO SEC. 4-5-32-33 ON S. BDY. T.26 S. R. 3 W. 17
Renewed the corner by setting a 4 x 4 x 36 " Oak Post and erecting a mound of rock from which original trees
A Laurel 24" S.29°E., 75 lks. scarred
A W. Oak 18" S.26°W., 158 ft. Scarred
A B. Oak 40" N.15°W., 265.3 ft. bears Scribe Marks
A. B. Oak 15" N.70°E., 156.4ft. dead Scarred

CORNER BET. 32 and 33 18
Renewed from original Bearing trees both alive and standing. Set a Rock Corner and erected mound of rock, from which original trees bear
Pine 60" S.78°E., 149.2 ft.
B. Oak 14" bearing scars N.70°W., 398.2 ft. 148

COR. BET. SEC. 31 and 32 19
Renewed this corner from the decaying remains of original tree. Set at hole where tree stood and ran S.35°W., 22 ft. set a Cedar Post also a Rock 6 x 10 x 20" from which hole where other B.T. stood bears N.89°W., 31 ft. Marked new tree
A. Black Oak 24" dia. S.33°E., 83.3 ft.
Chimney of Forest Blakley house. S.62°40'W.

SEC. COR. 9-10-15-16 20
Renew form stump and one O.B.T. Set 6x6x16" Rock. Remarked O.B.T.
S. Pine 30" S.85°E., 18.0 ft. Gov't. BRASS CAP
Fir 42" South 61.6 ft.
W. Fir 30" N.47°W., 56.0 ft.
No other suitable

SEC. COR. 10-11-14-15. 21
Renew from one O.B.T. standing and 2 rotten. Set 1" G. Iron Pipe with Yew Marker Marked
Fir 36" N.46°W., 16.5 ft.
Fir 30" N.30°E., 21.7 ft.
Fir 24" S.58°E., 42.7 ft.
Yew 10" S.41°W., 19.0 ft.

COR. BET. 10 and 15. 22
Set half way between section corners. All signs of B.T.s gone. Set 2" Pipe. Marked
Cedar 12" S.15°E., 65 ft.
Maple 18" N.31°E., 22 ft.

SEC. COR. BET SECS. 10 and 11. 23
No evidence of old B.T.s so set this cor. from the given to river and line of old blazes to the south. Set a Witness corner North 10 ft. and Iron Pipe 5/8 x 30" from which
A Norway Pine 36" N.37°E., 60.6 ft.
Fir 40" N.74°45'W., 92.8 ft.

SEC. COR. BET. SEC. 2 and 3 24
From one orig. B.T.s set a stone in ground 12 x 12 x 6" form which the Orig. B.T.s bear N.45°W., 50 lks. and a new B.T. bears S.60°30'E., 42.8 ft.

SEC. COR. TO SECS. 2-3-10-11. 25
No evidence left for this corner so established it by double proportionate measurement as per Gov't. Instruction. Drove an Iron Bole 5 x 8 x 30" in ground and erected a pile of rock 2 ft. in dia. and 18" high from which
Alder 10" N.15°E., 36.8 ft.
A Fir 8" N.42°W., 77.2 ft.
B. Oak 9" S.41°45'E., 126.1 ft.
Cedar 9" S.20°30'W., 97.0 ft.

C.S. Vol. 3, page 95, E.B. 51
C.S. Vol. 3, page 114
C.S. Vol. 3, page 164

SEE CORNER NO. 46

SEE CORNER NO. 148

SEE CORNER NO. 108

SEE CORNER NO. 49

SEE CORNER NO. 61

SEE CORNER NO. 59

SEE CORNER NO. 60

ALSO # 6 (1939)