

Douglas County Surveyor's Record of
Government Corners Renewed

26 T. S. 3 R. W. W. M.

1/4 SEC. COR. 1 and 12 **SEE CORNER NO. 76** 26
On Right bank of North Umpqua River. Old Fir Stake in place badly rotted, Found O.B.T. down and rotting badly, bearing scribe marks 1/4 S. B.T. in bark. This O.B.T. is a 12" fir bears N.35°N. 12 lks. from stake. Had no field notes to check so replaced stake with a 6 x 8 x 14" river boulder chisled X on top. Scribed
Cedar 40" S.2°E., 75 lks. scribed 1/4 S. 12 C.S.B.T.
Fir 14" N.71 1/2°E., lks. Scribed 1/4 S. 1 C.S.B.T.
NOTE: May 24, 1937 This 14" Fir is dead so scribed another tree as shown. Arthur Boyer, D.C.S., B.A.Lane, Welden Stone, Maurice Ried.
Fir 20" N.30°E., 27.5 ft. for witness tree to 1/4 Sec. Cor. 1 and 12. **C.S. FILE 30/21-1**

SECTION COR. 16-17-20-21. 27
Found remains of old Corner Stake and old W. trees down and rotten. Set Stake where old stake was and Marked new trees as follows
Fir 16" bears N.68°E., 24 lks.
Fir 24" bears N.44°W., 78 lks.
Fir 12" bears S.32°E., 60 lks.
Fir 20" bears S.76°W., 51 lks. **104**

CORNER OF SECTIONS 8-9-16-17. 28
Corner set by Government Surveyor, Standard pipe for Corner with following Witness trees
W. Oak 12" S.35°30'W., 23 lks.
W. Oak 12" N.72°E., 54 lks. **SEE CORNER NO. 65**
W. Oak 16" S.79°30'E., 120 lks.
W. Oak 16" N.79°30'W., 131 lks.

1/4 CORNER BETWEEN SEC. 16 and 17 29
This corner was gone, and no evidence of old corner. So I established it on appropriate distance between Section Corners by driving 1 x 30" Bolt in the ground and marking following trees.
Fir 12" bears N.75°E., 17.5 ft.
Fir 10" bears N.64°30'W., 12 ft. **SEE CORNER NO. 66**

1/4 SEC. COR. BETWEEN SECTIONS 9 and 10 30
Old White Oak 14" dia. S.85°E., 100 lks. scribe marks are very plain yet. Black Oak 8" dia. N.62°W., 79 lks. Stump is all that remains. Marked the following trees
Fir 8" dia. N.27°E., 11 lks.
Fir 12" dia. N.65°W., 16 lks. **131 235**

S.W. COR. D.L.C. # 40 31
From old B.T. set 18 x 12 x 12" Stone in ground Marked 40 for corner marked
A W. Oak 18" S.31 1/2°E., 332 ft. **51**

S.E. COR. D.L.C. # 40 32
From old Pine tree, no scribe marks visible. Phil Strader, said he had seen marks on same. Set post and marked
A Pine 15" S.50°30'E., 158 ft. **139**

S.E. COR. D.L.C. # 38 33
From old B.T. Stulp Set Rock 18 x 14 x 8" marked 38 for Cor. Marked
W. Oak 18" S.33 3/4°E., 287.9 ft. **52**

S.W. COR. D.L.C. # 41 34
From Pine Stump no scribe marks, but checking out from S.E. Cor. Cl. 40. Set a post flush with ground. Marked
Fir 15" S.14°30'W., 49 ft. **138**

Feb. 7, 1928
Ben. B. Irving Dep. Co. Sur.
W. S. Crear Chain.
Lee McCarn
C.S. FILE 14/23.

June 15, 1928
H.L. Eppstein Co. Surveyor
Witnesses
W. S. Crear
F. L. Perry

May 22, 1929
H. L. Eppstein
Co. Surveyor
G. Richardson
B. A. Lane
H. C. Wood
C.S. VOL. 3 Page 297

June 21, 1930
H. L. Eppstein Co. Sur.
Witnesses
N. F. Richardson
B. A. Lane
Davis
M 2-27