Douglas County Surveyor's Record of Government Corners Renewed

26 T. S. 3 R. W. W. M.

KUKE-CHAPMAN CO., EUGENE, ORE. 81052

Floyd Frear -Surveyor, Jack Bathrick, Durwood Owens, Witnesses — Dep. Co. Sur. May 20, 1937 — Arthur Boyer, Wit. B.A. Lane, Maurice Reid, Weldon Stone — Feb. 21, 1949 — Percy Armstrong — 6/15/49 — C.S. File 40/237

Art Boyer-Surveyor, H. Northcraft, P. C. Armstrong, D. C. Cooper, Witnesses — Dec. 1949 — C.S. File 40/237

Boyer Ben B. Irving D.C. SM. B. Germond — May 22, 1933 WIT. M. L. Kimmel, Fred Schmidt — N.E. Richardson — Feb. 6, 1933 — Weldon Stone — Pickett McMillen C.S. 30/214 C.S. 37/155 C.S. 37/155

35

¼ COR. BET. SECS. 16 and 21
Two old posts lying on ground. From this position bears
A Red Cedar 16" S.70°20'W., 22
A Red Cedar 24" N.65°40'E., 44
SEE ALSO #83

36

COR. BET. SECS. 11 and 12.
Location identified from O.B.T. 36" Fir S.10°W., 10 lks.
Set a Fir Post 4 x 4 x 42" from which a
A Fir 18" dia. bears S.28°E., 45 lks. Mkd. ¼ S. 12 C.S.B.T.
A ~~Fir~~ 15" dia. bears S.44°W., 85 lks. Mkd. ¼ S. 11 C.S.B.T.
Cedar 5/12/88 JK (PER NOTES IN CS 37/155)
RENEWED, SEE CORNER NO. #212

37

W.C. FOR ¼ SEC. COR. 10 and 11.
B.T.s destroyed. Set new trees
30" Fir N.82°13'W., 142.5 ft. W.C. ¼ S. 10 C.S.B.T.
27" Fir. N.85°37'E., 52.8 ft. W.C. ¼ S. 11 C.S.B.T.
RE-RENEWED, SEE CORNER NO. 61

38

¼ COR. BET SEC. 6 T.26 S., R. 2 W. and SEC. 1 T.26S., R.3W.
Set one New Tree
Fir 40" N.24.3 ft. Mkd. ¼ S. C.S. B.T.
RE-RENEWED, SEE CORNER NO. 180

39

COR. BET. SECS. 1 and 2
Set from evidence on ground--E. and W. fence and pile of rocks as confirmed on the ground by Pickett McMillan who saw original stake as set by U.S.G.L.O. for this ¼ Cor and also by F. C. Frear who also saw this original stake as witnessed by McMillan. Set 10 gage shot gun Barrel in ground and scribed
A Fir 15" dia. N.27½°E., 28 ft.
A Fir 18" dia. S.83°E., 14.7 ft.
C.S. File 30/214
RE-RENEWED, SEE CORNER NO. 98

40

SEC. COR. 27-28-33-34
Remark Original B. T., 2 ft. W. Oak bearing N 15° E 208.6 ft.
New Tree 12 in. Maple bearing N 56° W 144.8 ft.
SEE CORNER NO. 55

41

SEC. COR. 28-29-32-33
Set ½" x 1¾" x 36" iron bar and mound of rock. Found O. B. T. #210
with marks gone, which bears S 37° W 235 ft., Remark. 1963 BLM
Also mark 2Ft. Forked W. Oak bears S 44½° W 130 ft. BRASS CAP
10 in. W. Oak bearing S 7° E 129.8 ft. SEE Vol. 32, Pg. 13390
RE-RENEWED, SEE CORNER NO.

42

¼ COR BETWEEN 19-20 RE-RENEWED 47/182 MAY 24, 1957
Found badly rotted old stake in ¼ cor. Drove 1" x 30" steel bar to perpetuate corner.
SEE CORNER NO. 75

43

SEC. COR. 17-18-19-20 FD. OK - 3/75 - G. BAUCHMAN - M 55-64 ; 7/84 D. BENTZ M 97-154
Set 1½" x 54" iron pipe for corner on E & W right of way fence, from which
5/8" iron rod in the highway r/w line bears N 11° 30" E 404.4 ft., mkd. 894+76.6 (No trees in this quadrant)
5/8" iron rod in the highway r/w line bears N 66° 05' W 360 ft. mkd. 890+00 (No trees in this quadrant)
18" W. Oak bears S 5° 40' W 756 ft. mkd. S 19, T 26 S, R 3 W 1581 B. T.
14" Double W. Oak bears S 37° 18' E 755 ft. mkd. S 20, T 26 S, R 3 W, 1581 B T.
See file 40/237

44

¼ COR. 17-20
Found Original Oak B T. S 3° E 15 lks., in good shape.
Drove 2 steel auto springs and ½" iron bolt for corner from which
24" Fir bears N 69° W 44 ft., scribed with knife, 1581 on upper blaze, ¼ S 17 on lower blaze.
File 40/237
SEE CORNER NO. 67

45

SEC. COR. 5-6-7-8
Found original scribed corner stake and B. T. to the NW with scribe marks still distinct. Found also Maple B.T. to NW, decayed.
Set 4" x 4" Cedar post, properly scribed for cor, from which
14" Fir bears S 29° 30' W 20.3 ft. mkd. S 7 1581 B.T.
16" Fir bears N 47° W 16.4 ft. mkd. S 6 1581 B.T.
16" Fir bears S 47° 10' E 46.4 ft. mkd. S 8 1581 B.T.
14" Fir bears N 78° 45' E 43.5 ft. mkd. S 5 1581 B.T.
File 40/237
SEE CORNER NO. 63