

Douglas County Surveyor's Record of
Government Corners Renewed

26 T. S. 3 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

59

$\frac{1}{4}$ corner to secs. 2 and 3.

Found 12 inch stone with chisled + on top, 18 inches under road fill at corner. The Northwest BT checks for bearing & dist. bark scribed $\frac{1}{4}$ S (now 48 inch Fir)-original. Also found 48 inch Fir, 60°E., 42.8 feet standing but bark is rotted and no scribing found. REN.#24

Set an iron pipe with brass cap at corner (and over corner stone) marked $\frac{1}{4}$ S $3\frac{1}{2}$ T26S R3W, County Surveyor's Office, 1957.

Rescribe on bark:

Northwest B.T.-a Fir, N.45°W., 33.0 feet, rescribed $\frac{1}{4}$ S 3 CS BT, on bark.

Blazed and scribed:

12 inch Cedar, S.68°E., 36.8 feet, mkd. $\frac{1}{4}$ S 2 CS. BT.

James W. Byron, Deputy
County Surveyor.
April 2, 1957.
C. S. File 47/17L.

Witness corner to sec. corner to secs. 2, 3, 10 and 11. SEE ALSO REN.#199 60

Sec. corner in creek. Pipe and mond of stone not found. All bearing trees except Northeast BT found and check for bearings & distances. I do not open BTs.-they show good faces. REN.#64 #25

Exact corner location determined by projection of North line of North Umpqua Homesites.

Set an iron pipe with brass cap on section line East of corner mkd. Wit.

Cor. $\frac{3}{10} \frac{2}{11}$ T26S R3W, 43.5 feet West to corner,

from which:

10 inch W. O. bears N.83°E., 26.9 feet scribed Wit. Cor. S 2, T26S, R3W., CS BT.

5 inch W. O. bears N.43°W., 4.3 feet scribed Wit. Cor. CS BT.

6 inch W. O. bears S.73°W., 12.7 feet scribed Wit. Cor. CS BT.

6 inch Ash bears S.67°E., 18.2 feet scribed Wit. Cor. S 11 CS BT.

James W. Byron, Deputy County Surveyor
April 1, 1957.
C. S. File No. 47/168.

Witness corner to $\frac{1}{4}$ corner to secs. 10 and 11. SEE ALSO REN.#201 61

$\frac{5}{8}$ inch iron pipe set by Cole in 1923 not found.

Found 40 inch Fir - old scribing. REN.#23 ALSO SEE #37

Position of Wit. Corner determined by using Southeast corner Lot and Sec. corner to secs. 2, 3, 10 and 11.

Set an iron pipe with brass cap at point for Witness Corner mkd. Wit. Cor.

14.1 feet North of $\frac{1}{4}$ S 10/11, T26S, R3W., County Surveyor's Office, 1957,

from which:

40 inch Fir bears East 62.8 feet, bark scribe Wit. Cor. $\frac{1}{4}$ S 11 CS.BT.

6 inch W. O. bears S.75°W., 73.2 feet scribed Wit. Cor. S 10 CS BT.

James W. Byron, Deputy
County Surveyor
May 27, 1957.
C. S. File No. 47/190.

$\frac{1}{4}$ corner to secs. 24 & 25. 62

Found: Both Orig. BTs. The SE BT now 25 inch dead Fir opened 10 or 20 years ago-old face scribed $\frac{1}{4}$ S BT. The NE BT shows faint scribe marks (bark scribed), now 36 inch Fir, checks distance but I find bearing to be N.10°E., Record N.40°E.

Set brass cap at corner marked $\frac{1}{4}$ S 24/25 T 26 S, R 3 W County Surveyors Office, 1957. SEE ALSO #91

Marked new B.T.s:

10 inch Sugar Pine bears S.78 $\frac{1}{2}$ °E., 31.4 feet scribed $\frac{1}{4}$ S 25 CS BT.

12 inch R. Fir, bears N.82°E., 3.0 feet scribed $\frac{1}{4}$ S 24 CS BT.

Renewed

Section corner to sections 5, 6, 7, and 8. 63

Found:

4 x 4 Sq. Stake & Stumps of all BTS as set by Boyer, 1949. REN.#45

Set 1 inch Iron Pipe with brass cap marked County Surveyors Office, 1955,

Cor. $\frac{6}{7} \frac{5}{8}$ T 26 S. R 3 W.

from which:

Blazed & Scribed 8 inch cedar S.29°E. 81.4 feet S 8 CS BT.

Mt. Scott Lookout Bears N.25 $\frac{1}{2}$ °E.

Blaze & Scribe 8 inch Laurel S.20 $\frac{1}{2}$ °W, 157.8 feet S 7 CS BT.

Blaze & Scribe 18 inch R.Fir N.24°W, 221 .0 S 6 CS BT.

Surveyed for G. C. Finlay
James W. Byron, Deputy
County Surveyor
May 26, 1955
C.S. File No. 46/154