

Douglas County Surveyor's Record of
Government Corners Renewed

26 T. S. 3 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Weyerhaeuser Timber Co.
 By Lester E. Calder
 Glen McChesney-Tom Shrum,
 & Don Wright
 April 1960
 C. S. File No. 51/87
 C.S. 53/115

(continued)

County Survey Record: Brass Cap, Found.
 10" S. Pine S.78¹/₂°E. 31.4 ft. - 10" S. Pine scribed "CS S 25 BT."
 12" R. Fir N.82¹/₂°E. 3.0 ft. - 12" Fir scribed "CS S 24 BT".
 Referenced by G. McChesney (Plates & "W" nails only). Dec. 20°
 36" Fir N.07°E. 16.2 ft. (Orig. BT.)
 12" Fir N.85°E. 2.1 ft. (County BT.)

SEE ALSO COR. NO. 62

1/4 Corner common to Sec. 24, 26S-3W, & Sec. 19, 26S-2W. 92

GLO Survey Record: Post, down, decayed, scribed.

10" Laurel S.25°W. 10 lks. - Found in 1950-51 survey, gone in '59 surv.
 10" Laurel N.69°E. 13 lks. - Okay.

Found corner referenced previously by Curtis Price with plate & "W" nail
 on one tree & plate only on other tree. Destroyed these references &
 re-REFER, as follows: 30" Fir S.55°E. 17.4 ft. SEE #58
 20" Hem Stump S.24°W. 7.2 ft.

Center of Section 24. 93

Found pipe referenced previously by the 1950-51 survey as a temporary
 point for cutting. Destroyed this pipe & refer.

Set 1" pipe for center of section at intersection of East-West line of
 the 1950-51 survey. This point is 61 ft. East of the above mentioned
 temporary point.

Referenced by G. McChesney (Weyerhaeuser Method)

30" Hemlock N.38°E. 16.0 ft.
 30" Hemlock S.32°E. 18.0 ft.

N. E. Richard-
 son
 Milo Godfrey
 Les Kershner
 C.S. File
 39/11

	T26S		
Township Corner	S36	S31	R3W
	S 1	S 6	
	T27S		

County Surveyor's office
 Reset from three Old B. T's., badly deteriorated, Jan. 7, 1947
 Set: 1 1/2" Iron Pipe with Brass Cap 24" in ground mkd. as above.
 36" Fir bears S. 6°E., 543.8 ft.
 10"W. Oak " S.81°W., 195.8 ft.
 30" W.Oak " N.15 1/4°W., 231.5 ft.

1/4 Section Corner to Sections 20 and 21. 95

Reestablish as follows:

Set SandStone, properly marked 4" x 8" x 18" from which:

15" R. Fir bears N.62°34'W. 83 lks. dist.
 13" R. Fir bears N.70°56'E. 109 lks. dist.

Set by M. B. Germond, Deputy, Sept. 1908
 Recorded in Vol. 2, Page 153.

1/4 Section Corner to Sections 34 and 35. 96

Set Post & Marked New BT's:

W. Oak 20" S.11°E. 657 lks.
 Ash 16" N.1°30'W. 550 lks.

Jan. 14, 1896, Hayden
 Recorded in Vol. 2, Page 285.

Also C.S. Vol 2, Page 61

Section Corner to Sections 1, 2, 11, and 12. 97

Found - 3 Orig. BT's: Orig. 20", now 42" Fir (N.48°E. record) we find

should be N.55°E. 38.3 ft., shows old bark scribing.

Orig. 60", now 60" Fir, (N.45°W. record). We find should be
 N.25°W. 99.0 ft., shows old bark scribing.

Orig. 20", now 42" Fir S.88°W. 43.6 ft., shows good scar.

I do not open.

Also find old scribed Stake on Ground at Corner.

Set Brass Cap at Corner Mkd: County Surveyor's
 Office, 1960

S 2	S 1	
S 11	S 12	T26S R3W

New BT's: 8" W. Fir bears N.54°W. 16.0 ft. scribed S2 T26S R3W CS BT
 14" R. Fir bears S.50°W. 19.0 ft. scribed S11 T26S R3W CS BT.
 7" R. Fir bears N.62°E. 25.3 ft. scribed S1 T26S R3W CS BT.
 19" R. Fir bears S.79°E. 16.9 ft. scribed S12 T26S R3W CS BT.

FD. OK 11/18 GARY LANGRISH, DOUG. CO SURVEYOR OFFICE C.S. 59/46

James W. Byron, Deputy
 For Douglas County Rd. Dept.
 Milo Godfrey & C. Putnam
 Oct. 24, 1960
 C. S. File No. 52/58