Douglas County Surveyor's Record of Government Corners Renewed

T. 26 S. T. S. R. 3 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

110

Section Corner to Sections 29 - 30 - 31 - 32.
Found - 36" Bl. Oak N.62°W. 21.8 ft., previously opened, good scribing "30 CS" visible on old face. Ren. No. 12.
29" Bl. Oak N.44°E. 123.0 ft., top broken out, but still alive, prev. opened, both old faces visible but scribing gone.
30" Bl.Oak N.80°W. 19.8 ft, opened many years ago & face rotted away(Orig. BT).
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963 T26S R3W S30|S29 / S31|S32
New BT's: 8" Madrone S.49°E. 47.2 ft. Mkd: T26S R3W S32 CS BT.
8" Madrone S.82°W. 47.0 ft. Mkd: T26S R3W S31 CS BT.
25" Bl.Oak N. 8° W. 45.4 ft. Mkd: T26S R3W S30 CS BT.
16" Bl.Oak N.25°E. 88.5 ft. Mkd: T26S R3W S29 CS BT.
Note - Fence Corner (Fences S & E.) bears S.70°W. 4 feet.

111

Wit. Cor. to Sections 11 - 12 - 13 - 14.
Found - 66" Fir N.15°W. 17.8 ft.(to face), bark scrbng. visible.
Rotten Hemlock Stub N.42°E. 52.8 ft., fragments of unmistakable scribing visible.
45" Fir S.27°E.(not S.50°E.) 11.9 ft., old bark face visible, no scribing found. #216
No trace of S. W. BT.
Corner location falls in logging road to be built, Set Witness Corner 70 ft. West of Cor.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964 T26S R3W WC S11|S12 / S14|S13
70' E. to Cor.
New BT's: 23" Red Cedar N.5°E. 35.4 ft. Mkd: WC T26S R3W S12 CS BT.
14" Hemlock N.69°W. 49.5 ft. Mkd: WCT26S R3W S11 CS BT.
39" Red Cedar S.51°W. 37.0 ft. Mkd: WC T26S R3W S14 CS BT.
38" Red Cedar S.75°E. 15.0 ft. Mkd: WC T26S R3W S13 CS BT.
Sept. 1964

RE-RENEWED, SEE CORNER NO.

112

¼ Section Corner to Sections 11 and 14.
Found -Yewwood Stake set by Eppstein, 1925, See Ren. #5. Stake set still solid, scribed "S11" on N. side & "S14" on S. side. #228
60" Fir N.10°E. 11.9 ft.(to face) Old bark scribing visible, looks like Original.
44" Fir S.35°E. 12.0 ft.(not S70°E. 13.2'), bark scribing very plain "¼ S BT" (This is not same scribing as other tree)
Distance to center of tree.
Set - Brass Cap alongside Yew Post & Mkd: County Surveyor's Office, 1964
T26S R3W ¼ S 11 / S14
Rescribe - 60" D.Fir N.10°E. 11.9 ft.(to face) Mkd: ¼ S11 CS BT.
New BT - Red Cedar S.69°W. 10.6 ft. Mkd: ¼ S14 CS BT.
Sept. 1964

RE-RENEWED, SEE CORNER NO.

Milo E. Godfrey, Deputy County Surveyor
Wm. Stoffel & Mike Stone
December 1963 & January 1964
C. S. File No. 53/34

113

¼ Section Corner common to Sections 2 and 11.
Set - 5/8" Rod, from which a:
24" D.Fir BT bears N.78½°E. 26.5 feet.)
19" D.Fir BT bears S.26°W. 55.4 feet.) See Ren. No. 54. 164
Oct-Nov. 1964

Bruce A. Shaner
For Cota & Sendlebach
M 22 - 61

114

Sec. Cor. to Secs. 13 & 24, T26-3W. and Secs. 18 & 19, T26-2W.
Found - Stone 4 x 12 x 15", firmly set, shows notches on S. & N.
17" Fir N.15°W. 7.3 ft, now stub 5.0 ft. high, rotted & burned, shows scribe.
24", now 24" SSnag Fir, S.84°E. 26.6 ft., record S.80°E. 20.5 ft., shows old axe marks in bark, no scribe found.
24", now 28" Fir, alive, N.53°E. 78.8 ft., record 71.3 ft., open & shows scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965 T26S R3W S13|S18 / S24|S19 R2W
New BT's: 6" D.Fir S.87°W. 13.1 ft. Mkd: T26S R3W S24 CS BT.
6" D.Fir N.74°W. 25.4 ft. Mkd: T26S R4W S13 CS BT.
No tree large enough to S. E. - Orig. N. E. BT. O. K.
Note - See BT's. Weyerhaeuser Nails & Plates in C.S.File 53/115
C.S. 55/19

Vernon "Ray" Tracy
M.Darby & T.Connell
C.S. File No. 54/7
June 1965