

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 26 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Witness Corner to $\frac{1}{4}$ Corner to Sections 18 and 17. #211 OF 140
 Found - County Surv. Brass Cap Mkd. "Wit. Cor. 18 17 21.3 ft. N. to $\frac{1}{4}$ S 1955"
 (Recorded in Ren. #70)
 12" W. Oak S. 59° W. 61.8 ft., shows scribe on partially healed scar.
 New BT: 8" E. Oak N. 79° W. 43.8 ft. Mkd: W.C. $\frac{1}{4}$ S18 CS BT.
 Note - Scott Mtn. Lookout bears N. 16 $\frac{1}{2}$ ° E. Corner lies 4 ft. North
 of edge of paving on old N. Umpqua Hwy.

RE-RENEWED SEE COMPUTER NO.

141

Sec. Corner to Sections 25 - 26 - 35 - 36.
 Found - Orig. 20", now 25" Fir S. 35° W. 13.2 ft. Alive, prev. opened &
 shows "S" scribe.
 Orig. 20", now 36", Fir Stump N. 30° W. 21.1 ft., find fragmentary
 bark scribe.
 $\frac{3}{4}$ " I. Pipe & Aluminum Cap, as recorded in Ren. #102 which bears
 S. 10° W. 4.3 ft. from true corner location. Believe Mr.
 Shrum had wrong notes in the field.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966

T26S R3W	S 26	S 25
	S 35	S 36

 New Bearings & Distances to Shrum's BT's:
 10" Maple S. 70 $\frac{1}{2}$ ° E. 46.3 ft. Mkd: "S36 BT" & aluminum tag "RE 4287".
 8" Yew N. 57° E. 27.7 ft. Mkd: "S25 BT" & alum. Tag RE 4287".
 18" Cedar N. 85° W. 30.0 ft. Mkd: S26 BT" & Alum Tag RE 4287".
 Use Orig. BT. to S.W.

142

Sec. Cor. to Sections 27 - 28 - 33 - 34.
 Found - Orig. 15", now 25", W. Oak N. 15° E. 208.6 ft., shows scar.
 Tree alive, we do not open.
 12", now 13", Maple N. 56° W. 144.8 ft., shows scribe on
 unhealed face, now stump. Recorded in Ren. #40 by Frear.
 Do not find Brass Cap as recorded in Ren. #55.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966

T26S R3W	S 28	S 27
	S 33	S 34

 (Buried 12" below surface of ground)
 New BT's: 11" Maple N. 38° W. 204.2 ft. Mkd: T26S R3W S28 CS BT.
 9" W. Oak N. 12 $\frac{1}{2}$ ° E. 187.3 ft. Mkd: T26S R3W S27 CS BT.
 Note - No Trees available to South. - Brass Cap is buried 12" below
 surface of the ground.

143

S. W. Corner D. L. C. No. 42.
 Found - $\frac{3}{4}$ " I. Rod, as recorded in Ren. #50.
 Orig. 15", now 42", W. Oak S. 55° W. 82.5 ft., opened prev.,
 no scribing found.
 New BT's: 9" I. Cedar N. 30° W. 66.7 ft. Mkd: S.W. Cl. 42 CS BT.
 12" W. Oak S. 65° W. 45.0 ft. Mkd: S. W. Cl. 42 CS BT.

144

Section Corner to Secs. 6 & 7, R3W. & Secs. 1 & 12, R4W.
 Found - Burned Cedar Stump, 12", now 16" Cedar Stump S. 4° W. 9.9 ft.,
 Open & find "26 BT" scribe. Only remaining evidence of corner
 as recorded in Ren. #15.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966
 (12" in ground & build Mound of Stone)

T26S R4W	S 1	S 6
	S 12	S 7

 New BT: 14" D. Fir S. 88° W. 102.8 ft. Mkd: T26S R4W S12 CS BT.
 No other trees available.
 Note - Corner lies in N - S Fence approx. 180 ft. S. of Creek,
 course S.E. curving to East.
 1 $\frac{3}{4}$ " Axle Shaft bears N. 85° W. 1.8 feet.

145

$\frac{1}{4}$ Corner to Sec. 6, T26-3W. & Sec. 31, T25-3W.
 Found - Brass Cap set by GLO, 1943, & Fir Stumps referred to in Ren. #101.
 11" D. Fir S. 11° E. 12.8 ft. Alive, face pitched over. Do not disturb.
 13" D. Fir N. 4° W. 17.4 ft. Dead, burned, partial scribe visible.
 New BT: 8" D. Fir N. 86° W. 51.1 ft. Mkd: $\frac{1}{4}$ S 31 CS BT.
 Note - Corner is 70 ft. North of E - W Fence and 20 ft. East of
 Creek, course South.

Vernon "Ray" Tracy
Mike Stone & Jack Heritage
January and February 1966
C. S. File No. 54/7