

Douglas County Surveyor's Record of
Government Corners Renewed

26

T. S.

3

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21981

Angle Point 6 Sec. 9 191
 Found: 1924 G.L.O. Brass cap, firmly set and properly marked.
 14" Ash, now 20", N.63°W., 8.6 ft. Shows scar.
 New BT's: 14" B. Oak, N.41°W., 21.8 ft. Scribed PR AP6 CS BT.
 Note: This corner lies north 33.0 ft. and west 25.0 ft. from center
 line of road. 12/3/71

Angle Point 7 Sec. 9 192
 Found: 1924 G.L.O. Brass cap, firmly set and properly marked.
 Remains of Yewwood BT, out of ground. Shows old face (rotted).
 Distance of 136.6 ft. north to M.C. Corner hits good.
 New BT: 24" Maple, N.31°W., 9.0 ft. Scribed PR AP7 CS BT.
 Note: This corner lies 45.0 ft. south from center line road. 12/3/71

1/4 Corner to Sections 1 and 12. 193
 Found - Bearing Trees alive & in good condition as
 recorded in Ren. #76 by J.W.B., 1957. X
 No trace of C. S. Brass Cap found due to addition
 of riprap to hold fill of N. Umpqua Hwy. # 213
 Set - Brass Cap at Cor Mkd: County Surveyor's Office T26S R 3W
 1972 S 1
S 12
 Note - Hole could only be dug 1 ft. deep, built
 rock mound 3 ft. across & 2 ft. high around pipe.
 This corner lies 14.0 ft. west of west edge of pavement &
 across road from Rock Creek Guard Station. 3/15/72

S 1/16 Cor. between Sec. 32 and 33. 194
 Found - Cole's cedar post with scribed visible, in E-W fence line.
 36" Pine stump, bears N.68°30'E., 10.5 ft.
 26" Fir stump, bears S.6°30'W., 55.3 ft.
 Set - 2" x 36" Gal. ironpipe in place of cedar post
 New BT's - 20" Cedar scribed "S 1/16 S33 BT", bears N.27°E., 65.7 ft.
 28" Pine, scribed "S 1/16 S32 BT", bears S.74°W., 62.7 ft.
 Note: This corner is the Initial Point of Standley Subd.

1/4 Corner to Sections 13 and 14. 195
 Corner set by proportionate measurement.
 Set - 2-1/2" Iron Pipe with Brass Cap.
 22" Hemlock N.69°W. 23.9 ft. to RR Spike
 38" Hemlock S.13°E. 46.1 ft. to RR Spike
Sept. 1973

Section Corner to Sections 13 - 14 - 23 - 24. 196
 Found - Doug. Co. Surveyor's Pipe with Brass Cap, Ren. #117.
 18" Fir N. 7°W. 31.0 ft. CS BT
 12" Hemlock N.10°E. 10.0 ft. CS BT.
 10" Fir N.24°W. 34.6 ft. CS BT.
 28" Cedar S.40°E. 39.1 ft. CS BT.
 Marked: 28" Cedar S.36°E. 37.5 ft. W.Co. Tag
 32" Fir N.65°E. 40.4 ft. W.Co. Tag
 14" Fir N.84°W. 31.6 ft. W.Co. Tag
 24" Fir S.22°W. 57.5 ft. W.Co. Tag
Sept. 1973

N. 1/16 Corner to Section 23 and 24. 197
 Corner set by proportionate measurement.
 Set - 2-1/2" Iron Pipe with Brass Cap
 16" Maple S.42°W. 41.4 ft. to W! Nail.
 22" Fir N.76°E. 44.4 ft. to RR Spike.
Sept. 1973

John M. Powell
 J. Heritage
 Dec., 1971
 C.S. File 54/7

Jan 1972

Tracy, V.R.
 L.E. Monrean
 3/15/72
 C.S. File
 No. 54/7

Jan 1973

Victor McLind for
 Standley Subdivision
 Plat Vol. 14 Pg.
 29 & 30
 April 19, 1973

Nick Juliano
 For: Weyerhaeuser Co.
 C. S. File No. 55/316