

Douglas County Surveyor's Record of
Government Corners Renewed

T. 26 T. S. R. 3 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Victor McLind for
Vian & Hebard
M 51 - 34
10/73

Center 1/4 Corner, Sec. 34.
Set - 5/8" I. Rod from which:
new Bt's - 8" D. Fir, bears N.55°W., 3.6 ft.
8" Cedar, bears S.36°E., 21.1 ft.
Both trees blazed and scribed "C 1/4 S34 BT".

10/73

198

Northwest Corner for Sec. 11

Set - 5/8" Iron Rod (See also Ren. #60) #207
New BT's - 8" Oak bears N.21°E., 12.0 ft. scribed T168 R3W S2 BT.
10" Ash bears N.58°W., 21.1 ft. scribed T26S R3W S3 BT. *Corr. 9/21/77*
8" Ash bears S.22 1/2°W., 17.1 ft. scribed T26S R3W S10 BT.
7" Ash bears S.34°E., 19.4 ft. scribed T26S R3W S11 BT.
Old Northwest corner Sec. 11 bears west 43.5 ft. from the witness cor.

199

North 1/4 Corner Sec. 11.

Set - 5/8" Iron Rod. (See also Ren. #164)
BT's - 12" D. Fir bears N.8°W., 24.0 ft. scribed 1/4 S2 BT.
24" D. Fir bears S.8°E., 25.7 ft. scribed 1/4 S11 BT.

201

New West 1/4 corner for sec. 11.

Set - 5/8" Iron Rod (See also Ren. #61)
BT's - 7" Oak bears S.75°E., 12.3 ft. scribed WC 1/4 S11 BT. #208
8" Oak bears S.58°W., 18.6 ft. scribed WC 1/4 S10 BT.
New W 1/4 cor. bears North 16.0 ft.

202

New Center 1/4 for Sec. 11.

Set - 2" Iron Pipe (See also Ren. #184)
BT's - 12" Maple bears N.2°W., 20.5 ft. scribed C 1/4 S11 BT.
8" Maple bears N.87°W., 13.4 ft- scribed C 1/4 S11 BT.

203

1/4 Corner for Sec. 13 and Sec. 18 of T26-2.

Found - 1965 Douglas County Surveyor Brass Cap. Ren. #115
6" Cedar stub, N.27°E., 18.9 ft
10" Hemlock snag, S.34°W., 9.4 ft
Set - New R.P. trees:
8" Cedar, S.85°E., 23-5 ft
16" Cedar, S.65°W., 57.3 ft. (Dist. to form nail
at base of tree)

204

Center 1/4, Section 2

Found - 1/2" Alum. pipe Ren. #103
From which:
48" Cedar stump, BT with Weyerhaeuser "W" nail bears S.57°W.,
24.9 ft.
28" W. Fir stump, BT bears N.55°W., 28.7 ft.
New BT's - 12" W. Fir BT, I scribe "C 1/4 S 2 BT" bears S.42 3/4°E., 36.7 ft.
18" W. Fir, BT, I Scribe "C 1/4 S2 BT" bears N.86 3/4°W., 33.2 ft.

205

1/4 Corner for Secs. 2 and 11.

In reference to the Circuit Court of the State of Oregon for Douglas Co.
Decree No. 75-210, The judgement determined that the position for the 1/4 cor.
fell as proportioned by Baughman, RM 2-69, C.S. No. 59/21. Ren. #200

Found - A 5/8" I.R. set by G. Baughman.
A 12" D. Fir, bears N.8°W., 24.0 ft. Tree is double blazed and
scribed "1/4 S2 BT".
A 24" now 26" D. Fir, bears S.8°E., 25.7 ft. Tree is double blazed
and scribed "1/4 S11 BT".
Set - Brass cap at 1/4 cor. as proportioned by Baughman, cap stamped:
"Douglas County Surveyors Office" T 26 S R 3 W
1976 1/4 S 2
S 11

Note: Placed 5/8" I.R. beside cap.

I REMOVE the brass cap which mkd. Eppstein's 1/4 cor. (See Ren's. 4, 54, 113,
and 164) and mark position with a 5/8" I.R. which bears N.28°43' E., 119.86
ft. from cor. as proportioned by Baughman. I destroy scribing on BT's in
reference to this corner.

6/8/76

Glenn S. Baughman for:
Sun Studs
October 1974
RM 2 - 69

Donald Peel
for Weyerhaeuser
Nov. 1974
M 54 - 76

JAN 75

Bruce Shaner
For Asa DeGroot
March 4, 1976
M 56 - 34

L. E. Monrean, Doug. Co. Surveyor
P. Earle; A. Cangie
June 8, 1976
C.S. 59/18 # 59/21

RE-RENEWED, SEE CORNER NO. #207
RE-RENEWED, SEE CORNER NO. #205
RE-RENEWED, SEE CORNER NO. #208
RE-RENEWED, SEE CORNER NO. #209