

Douglas County Surveyor's Record of
Government Corners Renewed

26 T. S. 3 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

206

1/4 Corner for Sec. 3 and Sec. 34 of T25-3
Found - 1943 GLO brass cap properly stamped.
4" now 17" Red Cedar, bears S.17°W., 2.6 ft. Tree has well
healed blaze. I do not open.
54" now 56" Fir stump, bears N.15°W., 15.2 ft. Stump has a
well healed blaze. I do not open.
A 5" Yew, now a 6" staub, bears S.86°E., 14.3 ft. (Rec. S.88°E.,
14.5 ft.) Has been hit by log. Stump is very loose.) Stump
scribed "1/4 S3 BT".
Note: Orig. 6" Hemlock in NE quad. now gone.
6" Yew bearing N.10°E., 25.1 ft. has been pushed over by cat
logging. Ren. #162
A 16" Red Cedar, now 18" bears S.6°E., 31.4 ft. Tree double
blazed and scribed "1/4 S3 CS BT". Ren. #162
New BT - A 15" Red Cedar, bears N.79 1/2°E., 23.8 ft. Tree double blazed.
Scribed "1/4 S34 CS BT".

L. E. Monrean, Doug. Co. Surveyors
P. L. Earle
Sept. 20, 1976
C.S. 59/24

Section corner for 2, 3, 10 and 11 - ^{FD OK PER PIESKE 5-90 1950-2018 A#B} - 9/20/76
Found - A 5/8" I.R. set at sec. cor. as determined by Baughman. Ren. #199
A 1957 County Surveyors Office Witness Corner Brass cap. Ren. #60
From the Baughman corner the 1957 monument bears S.86°E., 68.0 ft.
From the Baughman Corner (5/8" I.R.) Found -
An 8" Oak bears N.23°E., (Rec. N.21°E.) 12.0 ft. scribed "T26S
R3W S2 BT"
An Ash, 9" (Rec. 10") bears N.56°W., (Rec. N.58°W) 21.1 ft. Tree
scribed "T26S R3W S3 BT".
A 8" Ash bears S.24°W., (Rec. S.22 1/2°W.) 18.5 ft. (Rec. 17.1 ft.)
Tree scribed "T26S R3W S10 BT"
A 8" Ash (Rec. 7") bears S.34°E., 19.1 ft. (Rec. 19.4 ft.) scribed
"T26S R3W S11 BT".
From the 1957 monument Ren. #60 Found -
A W. Oak, 10" now 12" bears N.85°E., (Rec. N.83°E.) 26.9 ft. Tree
has well healed blaze. We open and find scribing "W.T. Cor
S2 T26S R3W CS BT".
A W. Oak, 5" now 8" bears N.43°W., 4.3 ft. Tree has well healed blaze
We open & find scribing "W.T. Cor. CS BT".
A W. Oak 6" now 10" bears S.73°W., 12.7 ft. Tree has well healed
blaze, We open & find scribing "Wit. Cor CS BT"
An Ash 6" now 10" (double tree) bears S.67°E., 17.2 ft. to center
of base 18.2 ft. to center of scribed trunk. Tree has well healed
blaze. We opened and find a rotted face with fragmentary scribing.
No other BT's found.
Renewal - We replace the 5/8" I.R. set by Baughman with an I. Pipe 2" x 30"
long 24" in the ground with brass cap attached mkd:
"Douglas County Surveyor" T26S R3W S3 S2 S10 S11 1977
We place 5/8" I.R. along North edge of cap.
We replace 1957 County Surveyor brass cap monument with a 5/8" I. Rod.
We remove the scribing from the trees which reference this monument. Ren. #60
This Renewal (#207) was done in accordance with Circuit Court Decree #75-210
See C.S. File 59/21

207

3/21/77

208

W.C. 1/4 Cor. Secs. 10 and 11.
See Renewals #'s 23, 37, 61 and 201.
Found - A 5/8" I. Rod set as witness corner to 1/4 Corner Ren. #201.
Also found 1957 County Surveyor brass cap Marked in Ren. #61.
Brass cap bears N.80°E., 84.0 ft. of witness corner to 1/4 Cor.
as determined by Baughman
Found - From the Baughman witness corner:
An 9" Oak Rec. 7" bears S.75°E., 12.3 ft. scribed "WC 1/4 S11 BT"
This tree is also the 1957 SW BT.
An 8" Oak bears S.63°W., (Rec. S.58°W.) 18.6 ft. Tree scribed
"WC 1/4 S10 BT".
From the 1957 County Surveyor Brass Cap found-
A fir 40" now 48" bears East 62.8 ft. Tree bark scribed "W.T. Cor.
1/4 S11 CS BT".
A W. Oak 6" now 9" bears S.75°W., 73.2 ft. Tree has well healed blaze
We open and find good scribing "W.T. Cor. 1/4 S10 CS BT".
No other BT's found.

RE-NEWED CORNER NO. #240

Larry E. Monrean, Douglas County Surveyors Office
Karen Cheney
Pete Earle
March 21, 1977
C.S. 59/31