

Douglas County Surveyor's Record of  
Government Corners Renewed

T 26 T. S. R 3 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

Gary L. Langlitz, Douglas County Surveyors Office  
Stephen J. Flause  
Larry E. Monrean, Doug. Co. Surveyors Office  
K. Cheney - Pete Earle  
March 21, 1977  
C.S. 59/31

R. B. Kimberlind  
P. L. Earle, Doug. Co. Surveyors Office  
June 2, 1977  
C.S. 59/34

*FD. OK 12/13/82  
J. Powell, Doug.  
Co. Surveyors  
Office. 05/22/11  
Tree To Be Removed  
By Construction*

CONT. FROM PREV. PAGE -

208

Renewal - We replace Iron Rod at Baughman Witness corner with a 2" x 30" I. Pipe 27" in the ground with brass cap mkd. "County Surveyors Office" W. C. T26S R3W North to 1/4 S10 S11 16.0 ft. 1977.

Set 5/8" I. Rod along north side of cap.

I replace 1957 County Surveyor Brass cap with a 5/8" Iron rod.

We remove the scribing found on the two trees which reference this monument.

Renewal #61

This renewal was done in accordance with Circuit Court Decree #75-210. (See C.S. File 59/21.

3/21/77

209

Center 1/4 Corner for Sec. 11.

See previous renewals #'s 184, 202 and RM 2-69 and C.S. 59/21.

Found - 5/8" I. Rod at C 1/4 as established by B. B. Irving. Ren. #184  
Source of Iron Rod unknown.

Also fd. -A 2" I. Pipe firmly set at the C 1/4 as established by G. Baughman (See Ren. #202 and RM 2-69)

BT's for B.B. Irving's C 1/4 found as follows:

A 20" D. Fir, now a 20" snag with bark scribing "C 1/4 S11 CS BT" visible bears East 19.4 ft. (Rec. per Ren. #184, East 18.5 ft.) Irvings distance fits the scribed face.

A 24" now 36" D. Fir alive and in good condition with bark scribing "1/4 11" visible bears N.26 1/2°W., 23.1 ft. (Rec. per Ren. #184 N.30°W., 21.5 ft.) Irving's measurement fits the scribed face.

BT's per Ren. #202 as follows:

12" Maple, scribed "C 1/4 S11 BT" on a double blaze bears N.3°E., 20.5 ft. (Rec. Per Ren. #202, N.2°W., 20.5 ft.) and an 8" Maple scribed "C 1/4 S11 BT" on a single blaze bears S.88°W., 13.4 ft. (Rec. per Ren. #202, N.87°W., 13.4 ft.)

Renewal-In the position of Baughman's 2" I. Pipe, we set a 1" x 30" I. Pipe, 24" in the ground with brass cap attached mkd. "Douglas Co. Surveyor" T26S R3W C1/4 + S11 1977; and place the found 2" I. Pipe along the North side of the brass cap.

We attach a plastic cap inscribed "Doug. Co. Surveyor" to B.B. Irvings C 1/4 which now bears S.53°E., 35.0 ft. from the brass cap. We deface both B.B. Irving BT's except for the scribing "BT" found on his East BT. The above described procedures were followed in order to properly reflect the Circuit Court Decree #75-210 (See C.S. 59/21)

Note: Under fence running northerly approx. 120 ft. to left bank, North Umpqua River, fence running southerly approx 25 ft. to a corner then running westerly toward the left bank of the N. Umpqua River, also located approx. 300 ft. west of a house.

3/21/77

210

Sec. Cor. for Secs. 29, 28, 32 and 33.

Found - 2 1/2" I. P. with 3 1/4" Brass cap below ground level. BC mkd. Bureau of Land Management Cadastral Survey T26S R2W S29 S28 S32 S33 1963. (Wrong range stamp noted)

A 39" White Oak bears S.38 1/2°W., (Rec. S.37°W) 235.0 ft. with open rotted out blaze.

An orig. 10" now 19" White Oak bears S.6°E., 124.1 ft. (Rec. S.7°E. 129.8 ft., 1949) with well healed blaze.

An orig. 2 ft. now 30" White Oak bears S.47 1/2°W., 127.8 ft. (Rec. S.44 1/2°W., 130 ft., 1949) with well healed blaze. Tree is four trunked, measured three ft. above the ground.

An orig. 10" now 15" Black Oak bears N. 18 1/2°E., 231.1 ft. (Rec. White Oak, N.17 1/4°E., 230.3 ft.) with well healed blaze

An Orig. 30" now 40" Forked B. Oak bears N.64°W., 216.0 ft. (Rec. White Oak, N.65 1/4°W., 215.8 ft.) with well healed blaze. Tree measured below fork.

No monument set. Slashed out incorrect 2 on brass cap, stamped 3 above.

Note: Found 1/2" x 1 3/4" Iron bar in 24" deep hole ± 4 ft. north of brass cap. Watson C. Talcott stated that he, an interested nearby resident, had found said iron bar in that location and had dug it out trying to find brass cap. Drove iron bar at North edge of brass cap, flush with top. Set steel fence post with witness sign attached directly above brass cap.

See Ren. #41

6/2/77