

Douglas County Surveyor's Record of
Government Corners Renewed

T 26 T. S. R 3 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21991

211

Witness corner for 1/4 corner for Secs. 17 and 18.
Found - 1" x 36" I.P. bent with brass cap marked "County Surveyors"
T.26S. R.3W. Wit. Cor. 18/17 21.3 ft. N. to 1/4 S. 1955 Office
Was found at approx. corner location, laying on ground. Ren. #140
8" now 10" Black Oak, N.79°W., 43.8 ft. with well healed
blaze. Other BT probably destroyed by road widening.
Set - 1" x 36" Iron pipe with brass cap 4" above ground marked:
"Douglas County Surveyor" 1977
T 26 S R 3 W
Wit. Cor.
S 18 | S 17
21.3 ft. N. to 1/4 Cor.
New BT - 6" White Oak bears N.9°W., 6.4 ft. Double blazed and scribed
"WC 1/4 S18 CS BT".
Note: Witness corner lies 4 ft. North of N. edge of Old N. Umpqua
Highway pavement.

9/28/77

RE-RENEWED, SEE CORNER NO. #238

212

1/4 Corner for Secs. 11 and 12.
Found - A 1 1/2" Alum. alloy pipe 12" above ground.
A 36" now 26" Fir snag badly rotted bears S.15°W., 7.6 ft.
(O.B.T. Rec. S.10°W., 6.6 ft.)
A 15" now 20" Cedar bears S.59°W., (Rec. S.44°W., to a 15" Fir
per Ren. #36) 56.1 ft. Found partly healed blaze and
scribing "S11 CS".
A 12" now 30" S. Pine bears N.59°W., 53.5 ft. with a well healed
blaze.
A 5" now 8" Yew bears S.16°E., 29.7 ft. with a well healed
blaze. (Pine and Yew marked by Hale in 1946). (RECORD SOURCE
UNKNOWN (PROBABLY
WEYER OR HEUER))
DID NOT RENEW

9/28/77

1/4 Corner for Secs. 1 and 12.
Found - A 1" x 30" I.P. with brass cap laying 4 ft. west of corner location
marked: "County Surveyor's" T 26 S Ren. #193
Office 1957 1/4 S 1
R 3 W
A 12" now 14" R. Fir bears S.38 1/2°E., 123.1 ft. with well
healed double blaze.
A 36" Cedar bears N.46°E., 80.5 ft. with double blaze scribing
"1/4 S1 CS BT" in upper blaze.

Set - A 1" x 30" Iron pipe with brass cap set at edge of pavement level
marked: "Douglas County Surveyors" T 26 S
1977 1/4 S 1
S 12
R 3 W

No new accessories. Corner is at west edge of pavement across the road
from Rock Creek Guard Station. We set a steel fence post with survey
marker sign 1.0 ft. west of brass cap.

10/18/77

1/4 Corner for Sec. 12 and Sec. 7 of T26-2
Found - 1959 Cadastral brass cap properly marked, set in a 1.0 ft. high
3.0 ft. mound of stone, 13" above ground.
a 20" Fir (down) bears S.63°W., 35.6 ft. with a well healed blaze.
(no record of marking tree.)
a 15" Cedar, dead, bears N.81 1/2°E., 46.5 ft. with visible
scribing "1/4 S7 BT" in partially healed single blaze.
a 12" now 14" Cedar bears N.62°W., 19.8 ft. with visible scribe
marks in almost healed blaze.
New BT - A 50" D. Fir bears N.45°E., 32.3 ft. single blazed and marked
"1/4 S7 CS BT".

Corner is 150 ft. south of south bank, North Umpqua River.

12/30/77

RE-RENEWED, SEE CORNER NO. #234

214

R. B. Kimberling
M. W. Cline
Doug. Co. Surveyors
Office
Sept. 28, 1977
C.S. 59/40

R. B. Kimberling
M. W. Cline
Doug. Co. Surveyors
Office
Sept. 28, 1977
C.S. 59/40

R. B. Kimberling
M. W. Cline
Doug. Co. Surveyors
Office
Oct. 18, 1977
C.S. 59/40

R. B. Kimberling
F. C. Silagy
Doug. Co. Surveyors
Office
Dec. 30, 1977
C.S. 59/42