

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 26 S T. S. R 3 W R.W.W.M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

218

Witness Corner to the Center East 1/16 Sec. 12.

Corner surveyed in. See M 65 - 73.

Set - The true corner point is presently occupied by a tree, we therefore establish a witness corner which bears S.87°11'15"E., 5.00ft. from the true corner location. WE SET a 1" x 30" I.P. 26" in the ground with brass cap attached marked: Douglas County Surveyor

T 26 S R 3 W

W.C.

N.87°11' 15" W 5 ft to

C E 1/16 C
1978

BT's- A 10" Red Cedar, scribed "WCCE 1/16 S12 CS BT" on a double blaze, bears N.18 1/2°E., 29.8 ft.

A 16" Hemlock scribed "WCCE 1/16 S12 CS BT" on a double blaze bears N.78 1/2°W., 3.9 ft.

3/9/78

219

North east 1/16 Corner for Sec. 12.

Set - Corner location determined by survey. (M 65 - 73)

At the corner point WE SET a 1" x 30" I.P. 25" in the ground with brass cap attached marked: Douglas Co. Surveyor 1978

T 26 S

NE | 1/16

S 12

R 3 W

BT's- An 8" D. Fir scribed "NE 1/6 S12 CS BT" on a double blaze, bears S.10°E., 12.3 ft.

A 18" S. Pine, scribed "NE 1/16 S 12 CS BT: on a double blaze, bears S. 59°W., 37.0 ft.

3/14/78

220

North 1/16, Sec. 12 and sec. 7 of T26-2.

Set - Corner location determined by survey. (M 65 - 73). At the corner point WE SET a 1" x 30" I.P. 28" in the ground, with brass cap attached marked: Douglas Co. Surveyor 1978

T 26 S

N 1/16

S 12 | S 7

R 3 W R 2 W

BT's- A 12" R. Cedar, scribed "N 1/16 S12 CS BT" on a double blaze, bears N. 51°W., 28.5 ft.

A 16" D. Fir scribed "N 1/16 S12 CS BT" on a double blaze bears S.34°W., 26.8 ft.

Corner located approx. 50 ft. south of Road 26-2-7.1

3/14/78

221

West 1/16 for Secs. 1 and 12.

Set - 1" x 30" Galv. I.P. with brass cap 3 inches above ground at W 1/16 corner as proportioned in survey (M 65 - 73)

Cap is stamped "Douglas County Surveyor" T 26 S R 3 W

1978

W 1/16 S 1

S 12

BT's- A Yew 14" bears S.17°W., 15.1 ft. Tree double blazed and scribed "W 1/16 S12 CS BT"

A 35" D. Fir bears N.53°W., 99.8 ft. Tree double blazed and scribed "W 1/16 S1 CS BT"

Corner lies approx. S.40°E., 40 ft. of intersect of four-wheel drive road intersection running East, West, and North.

3/2/78

222

West Center 1/16 for Sec. 12.

Set - Corner location determined by survey. (M 65 - 73) At the corner point SE SET a 1" x 30" I.P. 27" in the ground with brass cap attached marked: Douglas Co. Surveyor

T 26 S

1978

C W 1/16 C

S 12

R 3 W

BT's- A 16" Red Cedar, scribed "CW 1/16 S12 CS BT" on a double blaze bears N.1°W., 37.3 ft.

A 24" D. Fir scribed "CW 1/16 S12 CS BT" on a double blaze bears S.83°E., 101.9 ft.

note - Corner located along E-W cutting line, approx. 200' West of small ck.

Gary L. Langlitz, Douglas County Surveyors Office
Larry E. Monrean
Stephen J. Flause
Frank C. Silagy
March, 1978
C.S. 60/7 M 65 - 73