

Douglas County Surveyor's Record of  
Government Corners Renewed

T 26

T. S. R 3

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

228

1/4 Corner for Sections 11 and 14.

Found - 1964 County brass cap, properly marked on a 1" I.P. Ren. #112  
Eppstein's 1925 Yewood post marked S11 on north side and S14  
on south side still solid and firmly set just north of cap.  
44" Fir stump with bark scribing 1/4 S BT, S35°E., 12.0 ft. to  
center of tree. Ren. #112  
Orig. 48" now 60" Fir stump cut flush with ground on side facing  
corner. bears N.10°E., 11.9 ft. to face. No scribing visible.

New Accessories:

Set PK nail with flagging in the top of orig. 48" now 60" fir stump  
N.21°E., 11.5 ft.  
Set PK nail with flagging in top of 12" cedar stump 1.0 ft. tall  
on uphill side, N.57°W., 68.4 ft.  
Set PK nail with flagging in top of 10" Fir stump 4.0 ft. tall,  
S.56°W., 27.0 ft.

DCSO BT tags put on all trees.

3/26/81

Witness corner for Special meander corner Sec. 9.

Found - 1924 GLO brass cap monument out of ground near bearing tree  
described below. cap is stamped "SMC S9" 1924 and is attached  
to a 1" x 36" iron pipe.

No original bearing trees found.


A White Oak, 11" now 14" with well healed double blaze bears  
S.65°E., 22.2 ft. (This is the only bearing tree found) Ren. #128

We set a temporary marker at corner position (in log extending out over the  
water) and find:

A 16" Ash bearing south 18.8 ft. (rec. south 15.8 ft.) with BLM  
boundary tag attached. We are not able to locate any evidence of  
blaze, scribing or axe work. Along with noted difference of  
record dist. we determine that this is not a bearing tree.

As the true corner position is in the water, WE SET a witness corner  
S.0°56'W., 40.0 ft. from Special Meander Corner on north south center sec.  
line, by survey, using true M S M C corner position and AP #7 (found brass  
cap) for references. (See 1924 BLM survey and 1972 resurvey)

Set - A 1" x 36" iron pipe with attached brass cap stamped "Douglas  
County Surveyor" W.C.



T26S R3W 1981

New BT's- 21" DBH D. Fir marked "X CS BT" bears N.76°E., 21.4 ft.  
8" DBH I. Cedar marked "X CS BT" bears S.24°W., 44.1 ft.  
20" DBH D. Fir marked "X CS BT" bears S.75°W., 28.5 ft.  
22" DBH D. Fir marked "X CS BT" bears N.27°W., 9.3 ft.

4/1/81

Center 1/4 Corner for Sec. 29

Set - 5/8" x 30" Iron rod.

BT's- 40" D. Fir bears S.21°E., 66.0 ft. scribed "C 1/4 S29 BT"  
14" Oak bears N.79°E., 30.0 ft. marked "C 1/4 S29 BT".

2/81

1/4 Corner for Sections 20 and 29

Set - 5/8" x 30" Iron rod

BT's- 18" Oak bears N.48°E., 266.10 ft. marked "1/4 S20 BT"  
14" Oak bears S.19°E., 158.80 ft. marked "1/4 S29 BT"

2/81

Gregory Quibell  
Deputy, Doug. Co.  
Surveyors Office  
Witness: D. Stewart  
March 26, 1981  
C.S. 61/19

L. E. Monrean, Deputy  
Douglas County Surveyors  
Office  
T. R Plouff  
April 1, 1981  
C.S. 61/19

(sketch attached  
to field notes)

Ronald Quimby  
BHW, Engineering  
For: Watson Talcott  
Feb. 1981  
RM 3 - 45

O V E R

230

231