

Douglas County Surveyor's Record of  
Government Corners Renewed

T 26

T. S.

R 3

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

232

Witness corner for the SW corner of DLC #46

Found - 1 1/2" I.P. with 1966 County Brass cap attached properly marked. Cap protrudes approx. 9" above ground and is in the east fence of "Wimberly Family Cemetery". Ren. #167

26" now 31" fir with well healed blaze bears N.1°W., 18.0 ft.

(Rec. N.17°E., was apparently taken with compass near the fence. By doing the same I agree with rec. bearing.) My bearing (N1°W.) was taken by offsetting 10.0 ft. east from the brass cap and the center of the 31" fir.

Approx. 20" rotted fir stump which is possibly the 19" D. fir per Ren. #167, bears S.10°E., 81.5 ft. which again matches record with my compass near fence. No scribing or face visible.

No original evidence was found.

New Accessories:

9" Fir scribed "X CS BT" in double blaze bears N.29°W., 66.3 ft.

10" Fir scribed "X CS BT" in double blaze bears N.10°E., 74.9 ft.

12" Fir scribed "X CS BT" in double blaze bears N.54°E., 84.8 ft.

4 1/2" round knob on top of tombstone marked "Mrs. A.J. Greenway died May 9, 1907" bears S.52°W., 36.9 ft.

Bearings shown for new bearing objects were taken at the object end rather than near the fence at the brass cap end of their respective lines.

Sketch in file.

3/30/82

Section Corner for Secs. 23, 24, 25, & 26.

Found - 1972 B.L.M. B.C. (properly marked).

BTs - 50" fir bears N.31°E., 8.6-ft., w/healed face.

17" hemlock bears S.47°E., 14.5-ft., w/healed face.

16" hemlock bears S.11°W., 31.1-ft., w/scribing partially visible.

6" hemlock stump, 2-ft. tall bears N.40°W., 16.0-ft., scribed:

"T26S R3W S23 BT".

All four of these BTs were set & recorded in 1972.

New BT - 13" hemlock bears N.13°W., 18.9-ft., scribed: T26S R3W S23 BT.

1/84

Geisler, Ronald G.  
L. Sibley,  
D. Turner  
Champion Internat.  
Corporation  
Jan. 31, 1984  
C.S. 58/146

233

1/4 Corner for Section 1 and 12

Found - 1977 Douglas Co. brass disk on a I.P. flush with ground, Cap properly marked. Ren. #213

12" now a 21" D. fir with a well healed double blaze bears S.38 1/2°E., 123.1 ft. Ren. #76

36" now a 42" cedar with a partially healed double blaze scribing visible in upper blaze "S BT" bears N.46°E., 80.5 ft. Ren. #76

Steel fence post with sign bears S.67 1/2°W., 1.1 ft. (Rec. 1 ft.)

New BT - 6" maple, bark scribed "1/4 S1 CS BT" which faces S.45°E., bears N.6°W., 23.5 ft.

Corner is at west edge of pavement (Hwy #138) across Hwy from Rock Creek Guard Station.

11/26/84

Randall W. Smith  
Stephen J. Flause  
Douglas County Surveyor  
Office Deputies  
November 26, 1984  
C.S. 62/21

234

1/4 Corner for Sections 9 and 10.

Found - 1972 US GLO disk set flush in a rock bluff properly mkd.

14" now 22" 2 1/2 ft. high rotted W. Oak stump. No scribing found, bears S.84 1/4°E., 66.0 ft. (orig. BT)

(No other orig. BTs found.)

14" now 23" D. fir, with an opened partially re-healed blaze. No scribing visible, bears N.73°W., 12.5 ft. Agrees with 1972 resurvey. (Rec. N.63°W per ren. #131 and 1924 resurvey) (Rec. N.65°W., 10.6 ft. per Ren. #30) BT per 1924 resurvey.

A DCSO disk on an I.P. stamped "County Surveyors Office T26S R3W W.C. 1/4 S9 S10 35 ft. S. to cor. 1966" bears North 33.95 ft. (Rec. North, 35.0 ft. per Ren. #131 and 1972 resurvey)

New Accessories:

A 4" square metal post with a black satellite dish attached bears N.82 1/2°E., 20.0 ft.

10" D. fir with a double well healed blaze that faces Northeast bears N.9 1/2°W., 27.7 ft. (BT per Ren. #131 scribed to wit. cor.)

19" D. fir with a double well healed blaze that faces westerly bears N.36 1/2°E., 37.6 ft. (BT per Ren. #131 scribed to wit cor.)

Larry E. Monrean  
Deputy, Doug. Co.  
Surveyors Office  
Randall Smith  
Stephen Flause  
Dec. 26, 1984  
C.S. 62/21

235