

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 26

T. S.

R 3

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91881

C o n t. -----

(1/4 Cor. Secs. 9 and 10)

Note - Corner lies on steep rock bluff on the north bank of the North Umpqua River in back yard of house at 22127 N. Umpqua Hwy. New BTs are BTs to Wit. Cor. per Ren. #131. These are used instead of scribing new trees to protect scenic value of yard.

12/26/84

235

Witness Corner for 1/4 Corner for Secs. 9 and 10

Found - A 1966 DCSO disk on an I.P. protruding 10" above ground. Evidence of a mound of stone present around I.P. marked as in Ren. #131. 8" now 10" D. fir with a well healed double blaze bears S.30 1/2°W., 7.7 ft. (Rec. S.34°W., 8.4 ft. Dist. is to center of trunk) #131. A U.S. General Land Office disk stamped "T26S R3W 1/4 S9 S10 1972" bears South 33.95 ft. (Rec South 35.0 ft. per Ren. #131 and 1972 resurvey).

New Accessory:

SE foundation corner of main house bears N.35°E., 6.1 ft.

Note - Witness corner lies under wood deck of house at 22127 N. Umpqua Hwy. on top of bluff on north bank of the N. Umpqua River.

12/26/84

236

Witness corner for 1/4 Corner for Secs.18 and 19

Found - Actual quarter corner monument (origin unknown) falls in middle of a road with thick asphaltic surfacing; this monument is not searched for.

A 1961 DCSO brass cap on a 1 1/4" I.P. marked as in Ren. #100 is firmly set and protrudes approx. 1 foot from ground.

No evidence of original bearing trees found.

26" dbl. W. oak, now a 28" DBH double trunked white oak with a well healed double blaze bears N.26°E., 23.0 ft. Ren. #100

Set - No monument set but evidence of long acceptance of location of gun barrel marking the 1/4 corner position can be found in C.S. 3/16; C.S. 36/31; C.S. 32/10 and M 16 - 76.

New Accessories:

A 2 1/2' x 2 1/2' concrete storm culvert access box, its surface flush with ground is marked with an "X" at the northwest corner bears S.78°E., 78.5 ft.

An unmarked (due to ornamental nature) 32" DBH Atlas Cedar (C. Atlantica) bears S.56°W., 115.0 ft.

Galvanized steel end post of cyclone fence bears south, 8.6 ft.

Note - Monument lies approx. 10 ft. north of Alexander Lane just northeast of rear entrance to Glide Upper Elementary School.

12/27/84

237

Witness corner for 1/4 Corner for Secs. 17 and 18.

Found - 1977 DCSO disk on an I.P. protruding 3" above ground mkd as in #211 8" now an 11" Dia. B. oak with a well healed single blaze bears N.79°W., 43.8 ft. per Ren. #140.

6" now an 8" dia. W. oak with a partially healed double blaze scribing visible "1/4 S18 CS" bears N.9°W., 6.4 ft. per Ren. #211

New BT - 10" dia. W. oak double blazed and scribed "WC 1/4 S17 CS BT" bears N.50°E., 20.4 ft.

Note - Wit. Cor. lies 22 ft. North of Glide Loop Rd. center line.(County Road #4B5) No scribable trees south of corner. Scott Mtn. Look Out not observed due to cloud cover. See Ren. #140.

12/2/84

238

1/4 Corner for Sections 29 and 32.

Found - A disk on an I.P. protrudes 15" above a 1 ft. dia. mound of stone marked per Ren. #185.

5" now 6" dia. Ash with a partially healed double blaze, scribing visible "1/4 S29 BT" bears N.7°W., 7.0 ft.

12" now 14" W. oak with a partially healed double blaze illegible scribing visible, bears S.70°E., 178.9 ft.

New BTs- 6" Ash double blazed & scribed "1/4 S23 CSBT" bears S.7 1/2°E., 29.5

4" Ash double blazed & scribed "X BT" bears N.65°W., 17.2 ft.

Note - Corner lies near the east edge of a swampy ash grove in an E-W fence line.

12/27/84

239

Larry E. Monrean, Deputy, Douglas County Surveyors Office
Randall Smith and Stephen J. Flause, Party Chief and Notekeeper
December, 1984
C.S. 62/21