

Douglas County Surveyor's Record of  
Government Corners Renewed

26 T. S. 4 R. W. W. M.

H. L. Eppstein Co. Sur.  
Nov. 6, 1926  
Wit. J. H. Wolford  
W. S. Crear  
Guy King

H. L. Eppstein  
Mar. 7, 1921  
Wit. L. H. Smick  
N. E. Richardson  
Bob Blakeley

H. L. Eppstein Dep. Co. Sur.  
March 4-5, 1921  
Wit. L. H. Smick  
N. E. Richardson  
Arthur Blakeley

F. C. Frear  
E. Summers Dec. 27, 19  
H. L. Eppstein  
B. Lane  
H. L. Eppstein  
Wit.

No Ref. Found  
F. B. 54, Page 50  
F. B. 54, Page 51  
No Ref. Found

- 1 N.E. COR. D.L.C. # 45.  
Re-set from one Old B.T. marks plain remarked same viz a 40" B. Oak bears S.80°E., 2.97 ch. Set a 4 x 36" Madrone Stake for Corner.
- 2 N.W. CORNER D.L.C. # 45  
Reset from one old B.T. and field notes. Remarked new B.T.s Set Stone from which new B.T.s  
Black Oak 20" dia. bears N.3°30'W., 48.5 links  
White Oak 30" dia. bears N.69°05'E., 85 lks. **63**
- 3 SECTION CORNER TO SECTION 22, 23, 26, 27  
Set Corner from old B.T. (5 inch Oak) in section 26, said Oak was dead but could see old scribe marks. I renewed Corner by setting 4 x 4 x 40" Oak Stake. Marked New B.T. as follows  
Red Fir 14" dia. bears S.70°30'W., 18 lks.  
Red Fir 10" dia. bears N.66°30'W., 35 lks.  
Red Fir 12" dia. bears N.32°E., 27 lks.  
Red Fir 15" dia. bears S.55°E., 55 lks. **91**
- 4 CORNER BETWEEN SECTIONS 22 and 23  
I renewed Corner from one old B.T. which I chopped into and found scribe marks other old B.T. gone. I reset corner and remarked old B.T. which is not White Oak 40" in dia. bears S.18°E., 315 lks. Marked New B.T. White Oak 14" dia. bears N.18°W., 120 lks.
- 5 S.E. COR. D.L.C. # 40.  
Reset from one old B.T. scribe marks were plain. Set 4 x 4 x 14" Oak Stake. Marked New trees as follows  
Fir 18" dia. bears S.45°30'W., 21 lks.  
B. Oak 15" dia. bears N.60°30'E., 55 lks. **100**
- 6 SECTION CORNER TO SECTION 14, 15, 22 and 23.  
Reset Corner from two old B.T.s which were dead but scribe was plain. Marked new B.T. as follows  
Ash 8" dia. bears N.62°30'W., 846.0 lks.  
W. Oak 8" dia. bears S.56°30'E., 434 lks. 418.6 lks. SEE  
W. Oak 10" dia. bears N.83°E., 493 lks. F.B. 54, P. 51  
No tree S.W. near. J.B. APR. 55
- 7 CORNER OF RAPER CL. 49 ON SEC. LINE BET. SECS. 28 and 33. ON SOUTH AND WEST BDY. OB CL. 49.  
Set a Sandstone 10 x 10 x 18" marked on N.E. side Cl. 49 C.S. X on top from which stump of Original B.T. bearing scribe marks bears S.5°E., 122 ft. marked new trees as follows Cl. 49 C.S.B.T.  
W. Oak 12" S.52°W., 52.6 ft.  
W. Oak 36" S.81°E., 104 ft.  
Tree N.W. has been grubbed out old fence lines converge at this point a new N. and S. fence built upon a line established by M.B. Germond bears East 35 ft. **45**
- 8 INTERIOR "L" COR. OF D.L.C. 43  
Set Stake 4 x 4 x 36" on section line 511.5 feet East of Section Corner 13-14-23-25--Marked 14" Red Fir N.48°30'E., 48 feet. **24** **104**
- 9 CORNER BETWEEN 13 and 24.  
Set Spring from two old B.T. Marked New B.T.s  
White Oak 10" S.34°W., 81 ft.  
White Oak 12" N.42°E., 145.6 ft. **54 & 89**