

Douglas County Surveyor's Record of
Government Corners Renewed

26 T. S. 4 R. W. W. M.

See letter from U.S. Bureau of Land Management

April 19, 1955 - C.S. 46/122

CORNER TO SECTIONS 27-28-33-34.

Found rock set by M. B. Germond from which original Ash B.T. bears S.15°E., ~~19.8~~ ft. Stump of original B.T. bearing scribe marks bears N.70°W., ~~20.5~~ ft. Marked new trees
White Oak 18" S.21°15'W., 58.0 ft.
White Oak 12" N.54°00'W., 34.8 ft.

changes made from V 8 E 10

10

This cor in wrong position - see Removal Notes C.S. 46/122

SEE CORNER NO. 50

183 195

1/4 COR. BET. 27 and 34

Found old B.T.s standing dead, had been previously cut open and scribe marks still show. I could not make both distances and bearings check so intersected bearings. Erected mound of rock with rock in center marked 1/4 S. C.S. Old trees then bear
N.20°E., 44 ft.
N.75°W., 39 ft.
Point of Ledge rock N.62°E., 97.2 ft.

JAN. '71 - Searched for, not found, Badly Burned, Pasture Area J.M.P.

11

J. W. Cole Co. Surveyor
Feb. 1923
Witness
N. E. Richardson

1/4 COR. BET. SECS. 34 and 35

Renewed corner from which original B.T. bearing rotted out scars scribe marks faintly visible bears S.1°E., 153.1 ft. Hole where a tree has stood N.83°W., 183 ft. Set a binder shaft 1" x 46" and mound of rock. Marked new trees
White Oak 7" dia. bears S.34°W., 163.3 ft.
White Oak 16" dia. bears S.34°E., 72.6 ft.

101

12

SEE CORNER NO. 101

SET COR. SEC. COMMON TO SECS. 29-30-31-32.

I set corner from one old tree with scribe marks on it. One other tree standing no scribe marks. Set 4x4x36" Oak Stake and marked new trees as follows
White Oak 12" dia. bears S.54°E., 66 ft.
White Oak 10" dia. bears S.31°W., 38 ft.
White Oak 24" dia. bears N.45°W., 297 ft.
.No tree in Sec. 29 near

13

SEE CORNER NO. 46

H. L. Epstein Co. Sur.
Witnesses
W. L. Dolan
E. D. Boise

SEC. COR. TO 28-29-32-33

Set Stone 8 x 12 x 15" from 2 old B.T. still standing in good condition. Marked tree from tree gone as follows
A Cedar 12" dia. bears S.85°E., 123 ft.
A Fir 12" dia. bears N.58°E., 262.6 ft.

14

SEE CORNER NO. 47

S.W. COR. D.L.C. # 43

Set pipe from B.T. Black Oak S.85°W., 13 lks. New B.T. Fir. 24" S.237 lks. *SEARCHED FOR, NOT FOUND, JAN. '71 J.M.P.*

15

COR. 23-24-25-26.

Set Iron Pipe. Old B.T. S.41°W., 4.73 ft. *SEARCHED FOR, NOT FOUND JAN. '71 J.M.P.*
18" Pine N.8°W., 1.82 chs)
15" Pine S.59°30'E., 82) lks Set by Cain *F.B. 33 26.2*
MARK -18" Pine N.22°E., 2.25 B.T. S. 24 C.S. *SEARCHED FOR, NOT FOUND JAN. '71 J.M.P.*

16

1/4 COR. BETWEEN 23 and 24

Set by proportional measurement. A Fir Stake 3"x 3"x 3' 1/4 S. from which
A Fir 12" N.26°W. 26 lks. 1/4 S. 23 C.S.
Laurel 15" N.80°E., 20 lks. 1/4 S. 24 C.S.

17

SEE CORNER NO. 106

1/4 CORNER BET. 23 and 26

Set Iron Pipe, Auto Spring for corner from which
Fir 30" dia. bears N.79°E., 1.10 ch. Old B.T.
Fir 8" dia. bears S.25°W., .77 ch. 1/4 S. 26 B.T. C.S.
Fir 48" N.30°W., 27.5 ft. Marked 1/4 S. 23 C.S. B.T.
This last Fir was scribed by A. Boyer, Dep. Co. Sur. on Dec. 15, 1936. The Witnesses were Bert Lane and C. F. Moore
FEB. 2, 1971 - SEARCHED FOR, NOT FOUND - C.S. 56/1 J.M.P.

18

Nov. 18-28, 1925
W. S. Great Chain
Witnesses
O. G. King, A. L. Casebeer, Casebeer

C.S. File 2/44
C.S. File 3/20
C.S. Vol. 3, Page 223 to 225 inc.