

Douglas County Surveyor's Record of
Government Corners Renewed

26 T. S. 4 R. W. W. M.

~~COR. 19-24-25-30. E. OR W. SIDE OF TWP. ? 30~~
 Marked ~~new~~ Witness Trees as follows
 B. Oak 28" N.62°30'W., 121 lks.
 B. Oak 36" S.47°00'W., 223 lks.
 B. Oak 6" S.64°30'E., 96 lks.

~~1/2 COR. BET. 1 and 12 THIS CORNER IS IN T27-4 31~~
 Yew post. New Witness trees as follows
 Laurel 5" S.23°01'W., 227 lks. SEARCHED FOR 2/2/71 JMP.
 W. Oak 36" N.61°37'E., 393 lks. NOT FOUND SEE FB 21 PG 9

~~1/4 COR. BETL 16 and 21 32~~
 Set W. Oak Post 4" x 4" x 3'. Marked the following trees
 B. Oak 7" S.26°44'E., 57 lks.
 B. Oak 12" N.24°51'E., 125 lks. T27-4 W

~~1/4 COR. S. BDY. SEC. 31 - Vol. 2, Pg. 278 33~~
 Set post from which SEE CORNER NO. 51
 An Ash 7" dia. marked C.S. $\frac{1}{4}$ S. E.T. bears S.30°E., 140 1/2 links
 An Oak 12" dia. in Fence row, Marked C.S. $\frac{1}{4}$ S. B.T. bears S.82°10'W., 336 lks.

~~CENTER SEC. 31 - Vol. 2, Pg. 278 34~~
 Set a marked C.S. from which
 A White Oak 10" dia., marked C.S.B.T. bears S.36°W., 15 lks.
 A Maple 7" dia. marked C.S.B.T. bears N.42°W., 28 1/2 lks.

~~1/4 CORNER ON SOUTH TOWNSHIP LINE BETWEEN SECS 34 and 35 #119 35~~
 Set a Star Auto Axle for Corner from the old B.T. namely a 15" White Oak N.10°E., 95 links. Other B.T. gone.
 Marked Black Walnut 8" dia. bears S.60°15'E., 239 ft. marked C.S. $\frac{1}{4}$ S. B.T. O.K. 1/27/71 es. 56/1

~~SEC. COR. BETWEEN 31-36-1-6 or S. E. Cor. Sec. 36. 36~~
 Reset from 3 old B.T.'s. Badly deteriorated, Jan. 7, 1947
 Set 1 1/2" I. P. with Brass Cap 2 1/2" in ground marked
 36" Fir, Bearing S. 6°E., 543.8 ft. SEE CORNER NO. 84
 10" White Oak, bears S. 81°W., 195.8 ft.
 30" White Oak, bears N. 15 1/4°W., 231.5 ft. T. 273 County Surveyors 045.00

~~1/4 COR. BETWEEN SECS. 16-17 37~~
 Set a 1"x36" I. P. with a brass cap 2 1/2 ins. in the ground mkd. County Surveyors Office $\frac{1}{4}$ S $\frac{15}{16}$ " from which
 Black Oak 14" diam. bears S 41° E 292.4 ft. mkd.
 $\frac{1}{4}$ s 16 C S B T.
 W. Oak 7" diam. bears S 30° W 291.8 ft. mkd.
 $\frac{1}{4}$ S 17 C S B T.

Location identified from tie to NE Cor. D.R.S. Dailey DLC#46 Sec. Cor. 8-9-16-17 and tie to bank of the North Umpqua River.
 This method was used because the agreement with the official field notes was believed to be a more accurate method than setting by proportional distances as the SE Cor. Sec. 16, S 1/4 Cor. Sec. 16, S 1/4 Cor. Sec. 17, SW Cor. Sec. 17, and 1/4 Cor. 19-20 were all known to be missing.
 The remnants of a BT stump (probably set be W. S. Britt over 60 years ago but not recorded) faced properly for this location. This old BT bears N29° 17' W 464.25 ft.
 June 20, 1947

~~NE COR. DLC #46, 38~~
 Set a 1"x36" I. P. with a brass cap 2 1/2 ins. in the ground. mkd. County Surveyors Office NE DLC #46 T 26 S, R 4 W. from which:
 A W. Oak 8" diam. bears S 86° 45' E 14.3 ft.
 A W. Oak 8" diam. bears S 18° 30' E 22.6 ft.
 Location was identified from an O. B. T. formerly 7" W. Oak, now 20". which bears S 35° W 42 lks. June 19, 1947
 6/8/72 BRASS CAP FOUND AT EDGE OF PATIO BY HOME OWNER - NO TREES LEFT (CAP UNDISTURBED - JUST UNCOVERED)

Set by Germond

H. L. Eppstein Co., Sur.
 J. H. Wolford Wit.
 L. L. Singleton Wit.
 Feb. 13, 1934

N. E. Richardson-Surv.
 Witnesses
 Milo Godfrey
 Les Kershner

N. E. Richardson-Surv.
 Milo Godfrey
 Les Kershner
 Witnesses

C.S. File 18/45

C.S. File 39/11
 Jan 7 18, 1947

C.S. 39/89
 M 13-43

Also See #27