

County Surveyor's Record, Douglas County, Oregon

T 26 S, R 4 W, WM.

CHAINS

39

COR. SECS. 8-9-16-17

Renewed from 3 O. B. T.

Set 1"x36" G. I. P. 24" in the ground. with a Brass cap mkd. County Surveyors Office Secs. 8-9-16-17 T26S, R4W from which 4 new B. Ts. are set.

- W. Oak 10" diam. bears N 20° 15' W 64.5 ft.
- W. Oak 8" N 74° 15' E 64.7 ft.
- W. Oak 14" diam. bears S 70° E
- W. Oak 15" diam. bears S 25° 30' W 114.8 ft.

June 2, 1947

105

1/4 COR. BETWEEN SECS. 15 & 16

Set a 1"x36" G. I. P. with a Brass Cap mkd. S 16-S 15 County Surveyors Office, 24" in the ground, from which

- A W. Oak 7" diam. bears N 68° W 11.8 ft.
- W. Oak 8" diam. bears S 44° E 44.1 ft.

June 9, 1947

OK 5/18/6, BY BENTZ
M102-2A#B

40

Surv. N. E. Richardson
Wit. M. E. Godfrey
L. S. Kershner

SEC. COR. 20, 21, 28, 29.

Set from one old B.T. with Scribe Mks. N 38° E 38 lks. Scribe destroyed.

Set a 1" x 36" Iron Pipe with a Brass cap mkd. 20, 21, 29, 28, T 26 S, R 4 W, County Surveyors Office.

- Pipe set 24 inches in the ground, from which:
- W. Oak 12" diam., bears N 12 3/4° W 11.3 ft. dist.
 - W. Oak, 14" diam., bears N 74 1/4° E 41.3 ft. dist.
 - W. Oak 12" diam., bears S 31 1/2° E 32.8 ft. dist.
 - W. Oak 12" diam., bears S 50° W 16.5 ft. dist.

July 11, 1947

41

SEE STATE HWY
SERIES (1938) FOR
PRIOR COR. INFO.
(C.S. 8-6)
(E J-8)

1/4 SEC. COR. BETWEEN SECS. 21 & 28.

Set a 1" x 36" Iron Pipe 24" in the ground with a Brass cap mkd. 1/4 Cor. 21, 28, T 26 S, R 4 W, County Surveyors Office from which:

- An Old B.T. bears S 76° W 195 lks. dist.
- An Old B.T. bears N 66° W 203 lks. dist.
- A W. Oak 15" diam. bears S 28° W, 29.5 ft. dist.
- A W. Oak 16" diam., bears N 35° W 23.4 ft. dist.

July 15, 1947

42

Fd. 1/84 by
De Groot
M 96-17

SEC. COR. 15-16-21-22

Found iron pipe for corner. Set new B. T's.

- 10" Laurel bears N 66° W 33.9 ft.
- 20" Fir bears N 61° E, 42.8 ft.
- 26" Fir bears S 71° W 13.0 ft.
- 30" Fir bears S 41° E 32.2 ft.

43

1/4 section corner to secs. 26 and 35.

Found - 18" W. O., S. 88° W., 14.5 feet as renewed 1925. We cut out scribed CS. Also found mound of rock and earth at corner.

Set 1" Iron Pipe with Brass Cap mkd. 1/4 S 26/35, T 26 S, R 4 W., County Surveyors Office 1955.

Chiseled 4" --- on 4 ft. x 6 ft. x 4 ft. high rock chisled W. P. on West face, N. 10° E., 47.5 feet.

Blazed and Scribed 30" B. O., N. 47 3/4° E., 20.5 feet, 1/4 S CS BT.

JAN '71 - FOUND O.K. TAGGED TREES

44

S. W. corner of the R. A. Raper Donation Land Claim No. 49.

Found - 10" x 10" x 18" sandstone and both B. T.s as scribed 1923 show old blazes. I do not cut out. Both check for bearings and distances. SEE REN # 7

Set 1" x 30" Iron Pipe with brass cap mkd. S. W. cor. D.L.C. 49, T 26 S, R 4 W, County Surveyors Office 1955. Reset sandstone alongside brass cap.

Blazed and scribed 6" W. O., N. 86 1/2° E., 6.0 ft., S W CL 49 CS BT.

45

RENEWED CORNER NO. 117

Surveyor- N. E. Richardson
Witness- Milo E. Godfrey
Les Kershner

C.S. File 39/89
M 13-43

M 13-45
C.S. 39/90

Surv. N. E. Richardson
Wit. M. E. Godfrey
L. S. Kershner

James W. Byron, Deputy County Surveyor
R. Irving J. Fee
April 8, 1955 C. S. File 46/122.
Smith) - Witness
Godfrey)

August 1949