

Douglas County Surveyor's Record of
Government Corners Renewed

26 T. S. 4 R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 97195

57

1/4 Section Corner to Sections 7 & 18.

Found - Both Orig. BT's, now standing, old faces rotted, check for bearing & distance.

Both BT's., recorded by Eppstein, 1929(record 10" W. Oak S.68°E. 22.4 ft. - 10" W. Oak N.10°E. 32.3 ft.) I find to be 12" W. Oak N. 2°W. 30.6 ft. - 12" W. Oak S.60 1/2°E. 23.8 ft. The N. 2°W. BT. has open face, good scribing visible. REN.# 24

Set Brass Cap at Corner Mkd: 1/4 S 7 T26S R4W County Surveyor's
S18 Office, 1958

No New BT's. scribed.

James W. Byron, Deputy
Milo Godfrey
S. A. Bilow
December 9, 1958
C. S. File No. 49/125

58

Renew Meander Corner to Sec. 19, T26S R4W, & Sec. 24, T26S R5W.

Found - Orig. 8", now 18" W. Oak S.63°E. 157.0 ft. I open near base & find good scribing "BT".

Corner falls on River Bar. I set Brass Cap 165.0 ft. South of M.C. I find no evidence of BT's. at this Point for 1/4 Corner 24/19. I do find 1" I. Pipe bears S.29°W. 17.4 ft. This pipe may have been set for 1/4 Corner.

North - South Fence is 81.0 ft. West from Wit. Cor.
Set Brass Cap for Wit. Cor. Mkd: Wit. Cor. 165 ft. North to
MC T26S County Surveyor's Office, 1958

R5W 24/19 R4W

New BT's: 7" W. Oak N.64°E. 16.4 ft. scribed WC MC S19 CS BT.
7" W. Oak S.35°W. 53.3 ft. scribed WC MC S24 CS BT.

James W. Byron, Deputy
Milo Godfrey
S. A. Bilow
For Office Records.
Dec. 1958
C. S. File 49/128 - M 13 - 57

59

1/4 Section Corner to Sec. 18, T26S R4W, & Sec. 13 T26S R5W.

Found - Orig. 12", now 42" B. Oak N. 7° 48'W. 211.2.ft. I open & find good scribing "1/2 S".

Set Brass Cap at Corner Mkd: 1/4 S13/S18 T26S County Surveyor's
R5W R4W Office, 1958.

New BT's: 12" W.Oak bears S.81°40'W.(True) 91.5 ft. scribed 1/4 S13 CS BT.
9" W.Oak bears N.23°E(True) 104.5 ft. scribed 1/4 S18 CS BT.

60

Section Corner to Sec. 18 & 19, T26S R4W, & Sec. 13 & 24, T26S R5W.

Set by single proportion between 1/4 Corner 13/18 & M.C. on South Bank of River.

Set Brass Cap at Corner Mkd: S13/S18 T26S County Surveyor's
R5W S24/S19 R4W Office, 1958 from which:
10" W. Oak bears S.42°53'W. 296.0 ft. scribed S24 T26S R5W CS BT.
13" B. Oak bears N.11°52'E. 373.3 ft. scribed S18 T26S R4W CS BT.

RE-RENEWED SEE CORNER NO. #123

61

1/4 Section Corner to Sec. 24, T26S R4W. & Sec. 19, T26S R3W.

Found - 1 1/2" Iron Bar at Corner & 16", now 18" Fir Stump., I open & find good scribing "BT", record S.43 1/2°W. 13.2 ft., I find should be S. 53° W. 13.2 ft. REN.# 25

Also find, now 32" Oak Snag checks record distance & bearing as recorded by Cole, 1916.

Set Brass Cap alongside Iron Bar & Marked Cap: County Surveyor's
Office, 1959 1/4 S24/S19 T26S
R4W R3W

New BT's: 9" R.Fir bears S.63°E. 74.0 ft. scribed 1/4 S14 CS BT.
4" R.Fir bears S.50°W. 83.0 ft. scribed 1/4 S24 CS BT.

RE-RENEWED SEE CORNER NO. #16

62

Section Corner to Secs. 19 & 30, R3W, & Secs. 24 & 25, R4W.

Found - BT's. as recorded by Cole, 1916: 30", now 30" down Oak, (REN.# 7 T.26-3)
N.61°W. 88.4 ft., I open & find good scribing "BT".

All other BT's. down. I do not find Drill Steel at Corner.

Note - Section Corner at

Set Brass Cap at Section Corner Mkd: County Surveyor's Office, 1959

R4W S24 | S19 T.26S.
S25 | S30 R3W

New BT's: 16" Laurel bears N. 4°W. 223.0 ft. scribed S24 T26S R4W CS BT.
3" Laurel bears N.42°E. 37.0 ft. scribed CS BT.
12" R.Fir bears S.68°E. 125.8 ft. scribed S30 T26S R3W CS BT.

94

James W. Byron, Deputy County Surveyor
Milo Godfrey
S. A. Bilow
March 19, 1959
C. S. File No. 49/48