

Douglas County Surveyor's Record of  
Government Corners Renewed

26 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97198

James W. Byron, Deputy  
For Allenby & Nye, Whistler's Park Estates  
Milo Godfrey  
S.A. Bilow  
March 10, 1959  
C.S. File No. 49/115

63  
Renew N. W. Corner D.L.C. No. 45.  
Found - All BT's. have been removed by County Road Construction Crew.  
I retrace Tie as shown by Evans, See C.S. File No. 41/398 &  
I find 6"x 7"x 12" Stone at record dist. & bearing. I believe  
this is Stone as recorded by Frear, 1919. Top of Stone 1"  
under surface. REN #2  
Set Brass Cap alongside Stone Mkd: County Surveyor's Office, 1959  
NW Cor. DLC 45 T26S R4W  
Note - Corner on Top Cut Bank 4' from Top of Cut Slope.  
New BT's: 13" W.Oak bears N.70°W. 51.8 ft. scribed CL NW 45 CS BT.  
6" W.Oak bears South 37.0 ft. scribed NW CL 45 CS BT.

64  
 $\frac{1}{4}$  Section Corner to Sections 17 & 18.  
Found - Orig. 8", now 20" W. Oak S.20°E. 92.4 ft., I open & find  
good scribing " $\frac{1}{4}$ "S".  
Now 36" W. Oak S. 4°W. 551.0 ft., record 12" W.Oak S.5°W. 590.7 ft.,  
I open, center rotted, no scribing found.  
I use Original S. E. BT. and Set Brass Cap at Corner Mkd: County  
Surveyor's Office, 1959  $\frac{1}{4}$  S18/S17 T26S R4W.  
New BT's: 20" B.Oak bears N.21°E. 129.0 ft. scribed  $\frac{1}{4}$  S17 CS BT.  
20" W.Oak bears S.20°E. 92.4 ft. scribed  $\frac{1}{4}$  S17 CS BT.  
Note: See C.S. File for Tie to  $\frac{1}{4}$  Corner, Sketch in file.

James W. Byron, Deputy  
S. A. Bilow  
For T. W. Jones  
May 11, 1959  
C. S. File No. 49/155  
Map File M 15 - 15

65  
 $\frac{1}{4}$  Section Corner to Sec. 3, T26S R4W., & Sec. 34, T25S. R4W.  
Found: Orig. BT. Cedar, now 48", shows good bark scribing " $\frac{1}{4}$  S BT"  
S.61°W. 20.0 ft.  
Orig. BT. R. Fir, now 36", N.33°W. 25.0 ft., shows good  
bark scribing " $\frac{1}{4}$ "S".  
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1959  
 $\frac{1}{4}$   $\frac{S34}{S3}$  T25S R4W  
T26S  
New BT's: 18" Laurel bears N.51°E. 3.5 ft. scribed  $\frac{1}{4}$  S34 CS BT.  
8" W.Fir bears S.13°W. 21.9 ft. scribed  $\frac{1}{4}$  S3 CS BT.

66  
 $\frac{1}{4}$  Section Corner to Sections 3 & 10.  
Found: - Orig. 14", now 34" B. O. N.51°E. 99.0 ft., I open & find  
good scribing " $\frac{1}{4}$ "S".  
No trace of Original S. E. B.T.  
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1959  
 $\frac{1}{4}$   $\frac{S3}{S10}$  T26S R4W  
New BT's: 15" B. Oak bears S. 7°W. 69.9 ft. scribed  $\frac{1}{4}$  S10 CS BT.  
14" B. Oak bears N.23°E. 57.0 ft. scribed  $\frac{1}{4}$  S3 CS BT.

James W. Byron, Deputy  
Milo Godfrey  
Clete Putnam  
Allenby Job for Pete Serafin  
April and May, 1960  
C. S. 52/24 M 11 - 66

67  
Meander Corner to Sections 18 and 19.  
Found - Orig. 7", W. Oak, now 18", shows good reverse scribing,  
S.18°W. 11.8 ft. No trace of Orig. N. E. BT.  
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960  
M C  $\frac{S18}{S19}$  T26S R4W  
New BT's: 13" Cedar bears N.82°E. 43.3 ft. scribed MC S18 CS BT.  
10" W.Oak bears S.32 $\frac{1}{2}$ °W. 78.4 ft. scribed MCS19 CS BT.

68  
N. E. Corner Lot 6, Sec. 18.  
Set at Hub Mkd: N. E. Corner Lot 6.  
Set Brass Cap Mkd: N. E. Corner Lot 6, T26S R4W County Surveyor's  
Office, 1960  
BT's: 11" W.Oak bears S.28 $\frac{1}{2}$ °W. 12.5 ft. scribed NE Lot 6 CS BT.  
17" W.Oak bears S.67 $\frac{1}{2}$ °E. 21.8 ft. scribed NE Lot 6 CS BT.

69  
S. E. Corner Gov't Lot 6.  
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960  
BT's: 14" W.Oak N.80°W. 11.2' S.E. Cor. Gov. Lot 6, Sec. 18, T26S R4W.  
9" W.Oak bears N.11 $\frac{1}{2}$ °E. 42.5 ft. scribed SE 6 CS BT.

FD OK  
7/84  
L. DALAN  
M 97-13