

Douglas County Surveyor's Record of
Government Corners Renewed

T. 26 S. T. S. R. 4 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Section Corner to Sections 15 - 16 - 21 - 22.
Found - 1" I. Pipe at Corner & 10", now 12" Laurel N.66°W. 33.9 ft.,
shows scribing. *Ren. #43*
S.W., S.E., and N. E. BT's now stumps.
New BT's: 7" Laurel bears S.70°W. 30.4 ft. scribed S21 T26S R4W CS BT.
8" R. Fir bears N.52°E. 74.9 ft. scribed S15 T26S R4W CS BT.

83

James Byron &
Crew
3/7/63
C.S. File
No. 49/125

Township Corner

R4W		T26S		R3W	
S 36	S 31	S 31	S 36	S 31	S 36
S 1	S 6	S 6	S 1	S 31	S 36
T27S		T27S		T27S	

84

Found - I. Pipe with Brass Cap set by Richardson in 1947. (See Cor. #36) #27
35" W. Oak N.15 1/4°W. 231.5 ft. shows good scar. Tree alive.
10" W. Oak S.81°W. 195.8 ft. now dead snag, all scribing visible.
Stump of 36" Fir S.6°E. 543.8 ft., bark scribing visible.
New BT's: 12" D. Fir S.28°E. 444.6 ft. mkd: T27S R3W S6 CS BT.
26" W. Oak S.76°W. 175.7 ft. mkd: T27S R4W S1 CS BT.
This tree was marked as BT. in 1917 survey, scar
previously opened and old face rotted away, new scribing
above old face.
Note - Corner is approximately 6" North of E. & W. fence line and
200 ft. East of Buckhorn Road.

Wilo E. Godfrey & Crew
October 22, 1963
C. S. File
No. 53/33

Township Corner
(N.W. Cor.
T27S R4W)

R5W		T 26 S		R4W	
S 36	S 31	S 31	S 36	S 31	S 36
S 1	S 6	S 6	S 1	S 31	S 36
T 27 S		T 27 S		T 27 S	

85

Found - Corner Tree, D. Fir, now 24", in fence corner, fences E, N. & N.W.
Steel Axle, 1 1/8" diam., N.55°E. 3 ft. from corner tree.
30" Fir Stump N.87 1/2°W. 22.1 ft. opened & fd. good scribing "36".
28" Fir Stump S.62°W. 21.8 ft., shows good scar.
26" Fir Stump S.30°E. 31.0 ft., shows good scar.
No trace of Northeast Bearing Tree.
New BT's: 11" D. Fir N.83°E. 28.8 ft. Mkd: T26S R4W S31 CS BT.
9" D. Fir N.16°W. 41.3 ft. Mkd: T26S R5W S36 CS BT.
4" Madrone S.36°E. 51.4 ft. Mkd: S 6 CS BT.
No trees available S. W. of Corner

Godfrey & Crew
Jan. 3, 1964
C. S. File No.
53/33

1/4 Corner to Sec. 35, T26-4W. & Sec. 2, T27-4W.
Found - 18" Bl. Oak N.25°E. 44.9 ft. This tree opened many years ago.,
Good scribing "BT" visible on badly decayed old face.
Tree still alive but top is broken out.
No trace of S. W. Bearing Tree.
Set - Brass Cap at Cor. Mkd: County Surveyor's 1/4 S35 T26S R4W
Office, 1964 S 2 T27S
New BT's: 21" Bl. Oak N.19°W. 43.5 ft. Mkd: 1/4 S35 CS BT.
27" D. Fir S.25°W. 177.1 ft. Mkd: 1/4 S 2 CS BT.
Note - 3-Way Fence Corner, (fences N, S, & E.) bears East 2.0 feet.

86

Wilo E. Godfrey, Deputy
Wm. Stoffel and Mike Stone
January 1964
C. S. File No. 53/33

Sec. Corner to Secs. 31 & 32, T26-4W. & Secs. 5 & 6, T27-4W.
Found - 21" White Oak N.70°E. 217.8 ft., opened & fd. reverse scribing "BT"
on badly rotted pieces of overgrowth of old face.
No trace of any other BT's.
Set - Brass Cap at Cor. Mkd: County Surveyor's T26S R4W S31 | S32
Office, 1964 T27S S 6 | S 5
New BT's: 6" D. Fir S.67°E. 15.3 ft. Mkd: T27S R4W S5 CS BT.
12" I. Cedar S.17°E. 88.8 ft. Mkd: T27S R4W S5 CS BT.
No suitable trees available in any other quadrant.
Note - Corner lies in E. edge of power line road, directly under power
wires. Gate Post E. end steel gate in E. & W. Fence Line,
(scribed "B.O.") bears N.22°E. 16.0 feet.

87

FO. OK 8/87
D. Bentz
11/01-26