

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 26 S. T. S. R. 4 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97881

Milo E.  
Godfrey  
& Crew  
March 4,  
1964  
C.S. File  
No. 49/125

Sec. Cor. to Sec. 6 & 7, T26-4W. & Sec. 1 & 12, T26-5W. #125 88  
Found - 36" B. Oak S.63°E. 372.9 ft., chopped open & fd. good scribing, "B".  
No trace of other Bearing Trees.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T26S R5W 

S 1	S 6
S 12	S 7

 R4W  
Office, 1964  
New BT's: 18" W. Oak S. 50°E. 322.8 ft. Mkd: T26S R4W S7 CS BT.  
20" D. Fir N. 81½°E. 320.0 ft. Mkd: T26S R4W S6 CS BT.  
No trees near west of line.  
Note - Corner lies 4 ft. south of E. & W. Fence Line.  
Corner is just East of top of bald, grassy ridge.

Godfrey &  
Crew  
May 11,  
1964  
C.S. No.  
49/125

Wit. Cor. to ¼ Corner to Sections 13 and 24. FND OK D. BEUTZ 2/91 M III - 59 89  
Found - Brass Cap & BT's. set in 1958, see Ren. #54.  
Corner position will be in pond to be built later.  
Move Brass Cap from Corner position, set Wit. Cor. 110 ft. East of Corner.  
Set - Brass Cap Mkd: County Surveyor's T26S R4W ¼ 

S13	WC 110E
S24	

  
Office, 1958  
New BT's: 18" White Oak N. 5°E. 34.7 ft. Mkd: WC ¼ S13 CS BT.  
21" Bl. Oak S. 58°W. 76.9 ft. Mkd: WC ¼ S24 CS BT.

Milo E. Godfrey  
& Crew  
Aug. 1964  
C. S. File  
No. 53/47

¼ Corner to Sec. 2, T26-4W. & Sec. 35, T25-4W. 90  
Found - G.L.O. Brass Cap set in 1957.  
10" Fir N. 60°E. 10.6 ft., now dead snag, scribing plainly visible.  
12" Fir S. 49°W. 9.5 ft., uprooted & down, scribing visible.  
New BT's: 15" D. Fir S. 16°E. 21.8 ft. Mkd: ¼ S 2 CS BT.  
12" D. Fir N. 70°W. 42.2 ft. Mkd: ¼ S35 CS BT.  
Note - Corner is on point of small spur sloping south; approx. 25 ft.  
South of wire fence running E. & W.; & approx. 75 ft. East of  
gate where fence line crosses new logging road.

John M. Powell  
F. Jones & J. Brady  
Dec. 13, 1965  
C. S. File No. 49/125

Section Corner to Sections 22 - 23 - 26 - 27. 91  
Found - ¾" Iron Rod at Corner, See Ren. #3.  
12" R. Fir Stump N. 32° E. 17.8 ft., opened stump, fd. scribe "B".  
14" R. Fir Stump S. 70½° W. 11.9 ft.  
10" R. Fir Stump N. 66½° W. 23.1 ft.  
15" R. Fir Stump S. 55° E. 36.3 ft.  
Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's Office, 1965  
T26S R4W 

S 22	S 23
S 27	S 26

  
New BT's: 31" Laurel N. 88° W. 85.3 ft. scribed T26S R4W S22 CS BT.  
30" Fir S. 84° E. 196.0 ft. scribed T26S R4W S26 CS BT.  
Note - Set Iron Rod in Fence, due North 4.1 ft.

Vernon "Ray" Tracy  
Mike Stone & J. Layne  
Feb. 1, 1966  
C. S. File No. 54/7

Sec. Cor. to Secs. 1 & 12, T26-4W. & Secs. 6 & 7, T26-3W. 92  
Found - Burned Cedar Stump only remaining evidence of Cor., See Ren. #74A.  
12", now 16", Cedar S. 4° W. 9.9 ft., open & find  
"26BT" scribe & reverse.  
All other BT's. gone.  
Set - Brass Cap at Cor. MKD: County Surveyor's Office, 1966  
T26S R4W 

S 1	S 6
S 12	S 7

 R3W  
12" in ground & build  
mound of stone.  
New BT: 14" D. Fir S. 88° W. 102.8 ft. Mkd: T26S R4W S12 CS BT.  
No other trees available.  
Note - Corner lies in N - S fence approximately 180 ft. S. of  
Creek, course S.E., curving to East.  
1¼" Axle Shaft bears N. 85° W. 1.8 feet.