

Douglas County Surveyor's Record of
Government Corners Renewed

T. 26 S. T.S. R. 4 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

93

1/4 Corner to Sec. 12, T26-4W. & Sec. 7, T26-3W.
Found - Very old, squared Post showing partial scribe "12 & 1/4".
Unrecorded 1" I. P. at approximate corner location.
No trace of Orig. BT's.
Eppstein's BT's, See Ren. #74, T26-4W., are now stumps:
30" W. Oak Stump S. 82 1/2° W. 101 ft., badly burned, no scribing.
14" W. Oak N. 34 1/2° E. 97.7 ft., sawed stump & log show
traces of old faces, badly rotted, no scribing.
Set- Set- Brass Cap at Cor. Mkd: County Surveyor's Office, 1966
T 26 S R4W 1/4 S 12/S 7 R3W
New BT's: 8" D. Fir N. 42 1/2° E. 170.0 ft. Mkd: 1/4 S 7 CS BT.
14" W. Oak N. 56° W. 145.8 ft. Mkd: 1/4 S 12 CS BT.
Note - This corner lies in N. - S. Fence.

"Ray"
Tracy &
Crew
C.S.
File
No.
54/7

Feb. 4, 1966

94

Sec. Cor. to Secs. 24 & 25, T26-4W. & Secs. 19 & 30, T26-3W.
Found - Co. Brass Cap, 1959, as recorded in Ren. #62, T26-4W.
16" Laurel N. 4° W. 223.0 ft. Alive & almost healed blaze.
3" Laurel N. 42° E. 37.0 ft., blaze healed, alive.
12" R. Fir S. 68° E. 125.8 ft. Alive, scribe visible on partially
healed blaze.
New BT: 5" D. Fir S. 8° W. 21.4 ft. Mkd: S25 CS BT.
Note - Corner lies at fence corner, fences N. & E.
No trace of Orig. BT called for in renewal as area has been
cleared and burned.

March 1, 1966

95

Sec. Cor. to Secs. 13 & 24, T26-4W. and
Secs. 18 & 19, T26-3W.
Found - 1" Iron Pipe, 3 ft. high, Set in Mound of Stone.
No trace of BT's., but do find stools of Myrtle at
approximate locations of Original BT's.
In searching through field books & map made by R. W. Fenn,
C. E., in 1903, we find reference to mound of stone & I. Pipe
at the location of this corner. Map in possession of W. H.
L. Osborne & field books are to be turned over to Co. Surveyor.
Since this corner has been used for 60 - 70 years, we set:
Set - Brass Cap alongside existing Pipe in Mound of Stone & Mkd:
County Surveyor's Office, 1966
T26S R4W S 13 | S 18
S 24 | S 19 R3W
New BT's: 13" Myrtle (in clump of two) N. 82° E. 45.5 ft. Mkd:
T26S R3W S18 CS BT.
8" Myrtle S. 60° E. 34.9 ft. Mkd: T26S R3W S19 CS BT.
7" Myrtle S. 70° W. 29.0 ft. Mkd: T26S R4W S24 CS BT.
(tree in clump of seven)
7" Myrtle N. 73° W. 12.0 ft. Mkd: T26S R4W S13 CS BT.

March 8, 1966

MICROFILM TO HERE 10/67

96

1/4 Corner to Sec. 24, T26-4W. & Sec. 19, T26-3W.
Found - County Surveyor Brass Cap, 1959, & BT's. as
recorded in Ren. #61, T26-4W.
9" R. Fir S. 63° E. 74.0 ft., alive, healed blaze.
4" R. Fir S. 50° W. 83.0 ft., alive, healed blaze.
Set - 6 ft. steel fence post alongside brass cap.

12/4/67

97

Points on Range Line T. 26 S., R. 4 W. and R. 3 W.
Set - 5/8" Iron Rod on high bank of N. Umpqua River 705 ft. South of
section corner to Secs. 13 & 24, R4W. & Secs. 18 & 19, R3W.
Set - 5/8" Iron Rod on R/W Line Old Co. Rd. No. 4, 50.87 ft. South
from corner on high bank mentioned above.
Set - 5/8" Iron Rod 525.59 ft. South of point off line mentioned
above, from which Power Pole bears N.25°W. 3.0 ft.
(Power Pole No. 14-11)
Note - See Map in Map File No. 35-8 for points on line

December, 1967

James W.
Byron, Co. Surv.
For.-Ore. St.
Game Comm.
M 35 - 8

Sept. 68

Vernon "Ray" Tracy
Mike Stone & Jack Heritage
March 1966
C. S. File No. 54/7

RE-RENEWED SEE CORNER NO #114