

Douglas County Surveyor's Record of
Government Corners Renewed

T 26

R 4

T. S.

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

114

Section corner for Secs. 13 and 24;

and Secs. 18 and 19 of T.26-3

Found - A 1966 County brass cap on a 1" x 36" I.P. properly stamped.

A 1" I.Pipe 3 ft. above ground in a mound of stone.

Pipe and stone referenced by R. W. Fenn, C.E. See Ren. #95 .

Pipe is south of cap 0.1 ft.

An orig. 15" Myrtle, now a very rotted stump bears S.43°W.,
8.6 ft.

An orig. 6" Myrtle bears N.73°W., 17.8 ft. This tree is gone but
a clump of new growth myrtle is at the position.

No other orig. trees.

A 13" Myrtle now 14" with healed over double blaze bears
S.88°E., 45.5 ft. (Rec. N.82°E.,) Tree is in a clump of three.

An 8" Myrtle now an 11" with a partially healed blaze bears
S.50°E., 34.9 ft. (Rec. S.60°E.) No visible scribe.

A 7" Myrtle with partially healed double blaze with visible
scribe "T26S R4W S4 C" in a clump of nine trees (Rec. seven)
bears S.74°W., 29.0 ft. (Rec S.70°W.)

A 7" Myrtle with partially healed double blaze no visible scribe
bears N.73°W., 12 ft.

Above 4 trees are from Ren. #95

Left cap and pipe in place. Tagged BT's.

Karen Reed
Doug. Co. Surveyor's
Office
Terrie Plouff
E. Reuben Scott
July 29, 1980
C.S. 61/11

115

1/4 Corner for Sec. 31 and Sec. 6 of T.27-4

Found - A 3/4" x 30" iron rod buried 12" below the surface of the ground.

Found remnants of wooden post in hole with iron rod. Ren. #33 & 51

No orig. Pine found.

A 12" Oak, now 24" with healed over previously chopped out double
blaze bears S.80 1/2°W., 22.8 ft. (Rec. S.82°10'W.) Ren. #33

A 7" Ash, now 29" with well healed blaze bears S.30°E., 92.7 ft.

A 15" W. Oak, now 25" with well healed double blaze bears S.36°E.,
48.0 ft.

A 12" W. Oak, now 16" with well healed double blaze bears N.30°W.
103.6 ft. (Rec. N.30°E.,) Ren. #51

Set - We reference out the iron rod and set a 1 1/2" x 36" iron pipe
with brass cap stamped: "Douglas County Surveyor" T.26S. 1/4
S31 S6 T27S R4W 1980" in its position then SET the iron rod
along the west side of the cap. Put three rocks around the
cap. Cap protrudes 0.2 ft. above ground.

No new accessories.

Cap lies north 29.1 ft. of an E-W fence and 4.1 ft. west of westerly corral fence.

8/7/80

116

1/4 Corner for Sec. 31; and Sec. 36 of T.26-5

Found - A 5/8" I. Rod protruding 2" from ground and a flagged stake
marked "W 1/4 Sec. 31", from Ren. #113

A thorough search for the orig. BTs reveals no evidence of these
or the pitch post monument from Ren. #73 ,

A fenceline running randomly south and northeast lies 43 ft. due
east of the 5/8" W. 1/4 corner monument. R. Wade's map M83-72
records the distance to the fence as 55 ft. This is apparently
an error of measurement possibly caused by not measuring on a
true bearing and by the random coursing of the fenceline. No
evidence of the monument having been located at 55 ft. is found.

Set - The 5/8" x 30" iron rod found is referenced out, removed and replaced
with a D.C.S.O. 2 1/2" brass cap on a 1" x 30" I.P.. The 5/8"
I.R. is set on the east edge of the brass cap. Both monuments are
firmly set and protrude 2" from the ground. Brass cap is marked
"Douglas County Surveyor" T26S 1/4 S36 R5W S31 R4W 1980.

New BT's- A 16" DBH B. Oak bears N.46 1/2°E., 40.9 ft. scribed "1/4 S31 CS BT"
on a double blaze.

A 23" DBH approx 50 ft. tall D. Fir snag bears S.05°E., 90.3 ft.
bark scribed BT near base.

A 21" DBH B. Oak bears N.18°W., 41.8 ft. scribed 1/4 S36 CS BT on
a double blaze.

No other suitable bearing objects available.

All accessories are marked with D.C.S.O. BT tags.

8/25/80

Karen Reed, Deput
Douglas County
Surveyor Office
Terrie Plouff
Aug. 7, 1980
C.S. 61/11

Stephen Flaus
Deputy, Doug.
Co. Surveyor's
Office.
Bill Stewart
Aug. 25, 1980
C.S. 61/11