

Douglas County Surveyor's Record of
Government Corners Renewed

T 26 T.S. R 4 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

117

Southwest corner for DLC #49
 Found - DCSO brass cap on a 1" x 30" I.P. firmly set, leaning slightly west and protruding 15" above ground. Cap is marked "County Surveyors Office" T29S R4W SW Cor DLC 49 1955. Ren. #45
 A 10" x 10" x 18" sandstone set on the northeast edge of the brass cap monument, marked "CL 49 CS" on its northeast face and marked "X" on its top face. Ren. #7
 Search for orig. bearing trees is fruitless; apparently old road work in area destroyed evidence of these trees.
 A 12" W. Oak now 25", bears S.51°W., 52.6 ft. (Rec. S.52°W., 52.6 ft.) This tree has a well healed blaze, we partially open to find scribing "L 49". Ren. #7
 A 36" W. Oak, now 46", bears S.81°E., 104.0 ft. (Rec. S.81°E., 104 ft.). Tree has well healed blaze, we partially open to find scribing "CS". Ren. #7
 A 6" now 9" W. Oak, bears N.82°E., 6.3 ft. (Rec. N.82°E., 6 ft.) we partially open the well healed double blaze to find scribing "BT". Ren. #45
 Set - Because all found bearing tree locations agree closely to record the location of the brass cap and sandstone monument is accepted as good. Because brass cap has wrong township marking we RESTAMP it to read "T26S" and add the marking "RESTAMP 1980".
 New BT - A 13" D. Fir bears N.34°W., 42.5 ft. and scribed "SW CL 49 CS BT" on a double blaze.
 All trees are tagged with DCSO BT tags. A north-south fenceline is approx. 2.2 ft. east of the brass cap.

Stephen J. Flause
 Deputy - Doug.
 Co. Surveyors
 Office.
 Bill Stewart
 Aug. 7, 1980
 C.S. 61/11

8/7/80

118

Section Corner for Secs. 13, 14, 23 and 24.
 Found - 3/4" x 33" I.R. Ren. #49
 Original monument not found.
 No original bearing trees found.
 Found from Ren. #23, A White Oak, 5" now 10" bears N.43°E., 202.8 ft. (Rec. 203.8 ft.) We open a portion of blaze and find old scribing and axe marks.
 From Ren. #49 A 14" now 24" B. Oak bears S.78°W., 69.7 ft. (Rec. 70.7 ft.) Tree has old fence wire grown into tree.
 A W. Oak, 7" now 13" bears N.17 1/2°W., 187.0 ft. (Rec. 186.0 ft.) Tree has well healed double blaze. Ren. #49
 Set - At position of section corner as marked by found iron rod WE SET A 1" x 36" I. pipe with attached brass cap stamped "Douglas County Surveyor" T26S S14 S13 S23 S24 R4W 1981. This monument set with cap 6" above ground with iron rod along North side.
 New BT - A W. Oak 14" scribed "T26S R4W S13 CS BT" on a double blaze bears N2 1/2°E., 155.4 ft.
 This monument set in E-W fence 51 ft. east of fence corner. Fences running N-S-E-W.

FD OCT '90
 G. BAUGHMAN
 1991-0063
 FD. 12-91
 D.E. GEORGE
 M114-1B

L. E. Monrean
 Deputy, Doug. Co.
 Surveyors Office
 S.J. Flause; Karen
 S. Mosley
 March 18, 1981
 C.S. 61/19

3/18/81

119

1/4 Corner on the South Tnsp. line, common to Sec. 34 & Sec. 3 of T.27-4.
 Found - 2-1/2" I.P. w/ 3" B.C. marked: "T26S R4W 1/4 S34 S3 T27S R4W 1975 U.S. Dept. of Interior B.L.M." from which:
 BTs - 38" Oak orig. BT, with healed face bears N.10°E., 63.4-ft.
 14" Walnut BT, with healed face bears S.61°E., 238.6-ft. (Rec. 239.6-ft.). Ren. # 35
 Note - 1" iron axle is set alongside B.C. 8/17/81

B.A. Shaner
 OR L.S. #430
 For: J.A. Barnes
 Aug. 17, 1981
 C.S. 58/229

120

NorthWest Corner of D.L.C. #50.
 Found - No monument found.
 BTs - 18" Black Oak, orig. BT, with definite face in at 85 to 90 years & an older face in at 125 to 130 years, badly rotted, probable orig. face, but no scribes visible on either face, bears S.45°E., 15.8-ft.
 36" Maple, orig. BT, with old face, bears N.30°W., 47.0-ft. (Rec. BT was a 7" Black Oak, N.30°W., 49.5-ft.).
 Creek, 10.0-ft. wide, course NW, is 27.0-ft. East of this Corner (Rec. is 38.3-ft.).
 New BTs - 10" W. Oak BT, I scribed "T26S R4W NWC DLC 50 BT" bears

B.A. Shaner
 OR L.S. #430
 For: J.A. Barnes
 July 27, 1981
 C.S. 58/229