

Douglas County Surveyor's Record of
Government Corners Renewed

26

T.S.

5

R. W. W. M.

F. C. Frear D.C.S.
Tom Hait) Wit.
J. C. Kaegi)
Marck 22, 1919

J. W. Cole Deputy County Surveyor
May and June 1921

G. G. Stewart D.C.S.
Sept. 24, 1922
Tom Dixon, Claude Crocker
Witnesses J. H. Short

Ben B. Irving
Dep. Co. Sur.
Mar. 18, 1929
N.R. Richardson
E. HoHinger
Al Smith)
Witnesses 22/40

Flemer

Vol 3 Page 57

C.S. Vol 3 Page 93

C.S. File 1/56

C.S. File 22/40

COR. OF D.L.C.s 43-44-45
I reset from old B.O. B.T. stumps which Tom Hart and G.W. Short claim is the original B.T. they having seen the mark on same. Later M. B. Germond, County Surveyor claims also to have seen the original letters on the stump 8 or 9 years ago. I set a 1 x 48" I. Rod for the Corner from which the 24" Black Oak Stump bears N.63°E., 3.53 chains. I remarked
A Laurel 16" bears N.86½°E., 4.04 chains marked C.S.B.T.

N.W. COR. CL. 48
I renewed this corner from the original B.T. which bears scribe marks, but is dead. Set at the tree N.5°E., 64 lks. and set an Oak Post also an Iron Bolt 1" x 14" from which I marked new trees
A Black Oak 24" dia. bears S.54°W., 45 ft.
A Black Oak 12" dia. bears S.17°30'E., 72.7 ft.

S.W. COR. D.L.C. # 48
A Rock 6 x 8 x 12" from which a White Oak 30" dia. bears N.66°30'E., 58.1 ft. This Rock had been placed for the Corner by some previous surveyor but no record made.

COR. BETWEEN 17 and 18.
Set Oak Post also an Iron R. R. Spike from which the original B.T. bears N.10°E., 23.8ft. bearing scribe marks. Marked new trees as follows
A Black Oak 18" dia. S.40°30'W., 35 ft.
A Black Oak 14" dia. N.73°00'W., 24.2 ft.

COR. TO SECTIONS 7, 8, 17, and 18
Set an Oak Stake from which the remains of original B.T.s check with field notes Marked new trees as follows.
A Fir 18" dia. bears S.29°W., 39.2 ft.
A Fir dia. bears N.33°4'E., 36.7 ft.
A Fir 24" dia. bears S.56°10'E., 36.7 ft.
A Fir dia. bears N. 59°W., 45.5 ft.

S.W. CORNER D.L.C. # 41
I reset from old B.T.s standing but rotten. Set 3/4" Galvanized Iron Pipe. Marked the following trees
Black Oak 20" dia. bears S.41½°E., 5.2 ft.
Black Oak 8" dia. bears N.41½°E., 48.4 ft.

S.E. CORNER D.L.C. # 41
I reestablished by running South and East lines of D.L.C. 41. B.T.s gone. Set Iron Pipe and marked trees as follows SEE 1953 AFFIDAVIT - C.S. 41/144
White Oak 8" dia. bears N.64°W., 66 ft.
Black Oak 12" dia. bears N.67°E., 62.3 ft.
Var. 17°E.

N.E. CORNER D.L.C. # 41 (SEE DEC #39)
I reset from old B.T.s. Set Iron Pipe and marked the following trees
Black Oak 24" dia. bears N.51°E., 52.2 ft.
Black Oak 24" dia. bears S.70°W., 107.6 ft. (old B.T.)

SECTION CORNER BETWEEN SECS. 7 and 12 (T.26-6)
Position identified from one O.B.T. scribe marks nearly rotted off. Drove 2" x 36" Iron Pipe and marked the following trees
Fir 14" dia. bears S.42°W., 84 lks. Scribed 1/8 S. 12
C.S.B.T. 65
Fir 10" dia. bears N.31½°E., 36 lks Scribed 1/8 S. 7
C.S.B.T.

SW. CORNER OF CALVIN C. REED D.L.C. #47
Marked the following trees
Oak 24" N.1°W., 37 ft.

1

2

3

4

5

6

7

8

9

10

(over)