

Douglas County Surveyor's Record of
Government Corners Renewed

26 T. S. 5 R. W. W. M.

(Cont.) - -

(#10)

Oak 10" N.19°W., 21.1 ft.
Oak 6" S.54°W., 111.4 ft.

✓ S.E. COR. D.I.C. 47, ^{4" Maple Stake}
Marked the following trees
Ash 12" N.36°E., 14.1 ft.
Maple 14" S.70°E., 11.8 ft. **SEE CORNER NO. #76 11**

✓ S.E. COR. JOHN AKIN D.I.C. 51
Black Oak 14" S.88½°W., 40.8 ft.
White Oak 18" N.41½°W., 30.0 FT - A.E.G.
^{12" B. Oak 535°45' E 31.4'} **SEE CORNER NO. #77 12**

✓ ¼ SEC. COR. BET. SECS. 29 and 32
Fir 12" dia. bears S.65°E., 22.2 ft.
Fir 12" dia. bears N.66½°E., 25.9 ft.
Laurel 8" dia. bears N.47°W., 6.8 ft. **SEE CORNER NO. #81 13**

✓ ¼ S. COR. BET. SECS. 20 and 29
Set a 4" Oak Post and marked the following trees
Laurel 8" N.60½°W., 19.2 ft.
A Fir 20" N.83°E., 18.3 ft. **SEE CORNER NO. #73 & 79 14**

✓ ¼ SEC. COR. BETWEEN SECS. 28 and 33
Reset this corner from a rock found for corner and also
from a White Oak S.76°W., 54 links. Drove a ½" Iron Pin
for corner beside this rock and scribed a new tree
White Oak 12" dia. (Y shaped tree) bears N.23°E.,
62.6 ft. scribed the figures and letters "¼ S. B.T." with a knife. **15**

✓ ½ SEC. COR. BETWEEN SECS. 20 and 21.
Reset from original B.T.s, set a 1½ x 30" Iron Bar out in
a large open hill side, Var. 19°E. from B.T.s original
distances check out fairly close. Both B.T.s in place,
put tags on them. **131 16**

✓ COR. TO SECS. 17, 16, 20, and 21.
Set a 6 x 8 x 12" Sandstone marked with a X on top, 3
B.T.'s standing one completely gone, one dead and broken
off. Two in fair shape. **129 17**

✓ ¼ COR. BETWEEN SEC. 25 and 30
Set a 6 x 9 x 12" Sandstone, from original B.T., 10" in
ground. B.T. is a white oak in good condition. Used ⁷²⁶ U243.
field notes which are (a 30" (now about 36") white oak
bears S.64°15'E., 741.2 ft. The other B.T. gone. Marked
Stone with a ¼ S. on top set a Iron Rod alongside stone. **18**

✓ ¼ COR. BETWEEN SECS. 26 and 35 RESET. **19**
Sighted from trees set by Hicks in 1912, found rock with
cross on it. Drove ¾"x36" Gal. I. Pipe from which Hicks
O.B.T.'s. were as follows:
12" W.O., N 54° E 17.0 ft.
12" W.O., S 31° E 37.9 ft. **111**

✓ COR. TO SECS. 9 - 10 - 15 - 16 **20**
Found orig. B.T.s in N.E. and S.W. quadrants. From these set 1" x 48"
axle 42" in ground to mark sec. cor. 9 - 10 - 15 - 16.
From this found stump and stump hole corresponding to remaining B.T.s
Marked trees as follows:
8 in. W. Oak N 46° W 39.5 ft.
24 in. W. Oak S 63½° W 14.8 ft.
12 in. W. Oak S 48° E 89.0 ft. **SEE CORNER NO. #87**

paper part page 15 page 21 page 28 C.S. File 31/7 No Ref. Found

Pleser
F.B. 36

A. Boyer D.C.S.
Att. Geo. Brown
Darley Ware
Gordon Ware
Mar. 1, 1943

12/1/44
12/5/44
12/22/44

J. M. Morgan
H. B. Church
witnesses
Jim Osborn

F.C. Frear
March 25,
1947

No Refs
Found

H.E. Crowder - Party Chief
for County Engineer's office
April, 1951
C.S. 44/47