

Douglas County Surveyor's Record of  
Government Corners Renewed

26 T. S. 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

Section corner to secs. 21, 22, 27 and 28.

28

Found 4 old B. T.s:

- 14 inch Y. Oak, N.22°E., 39 lks. - standing but dead.
- 12 inch Y. Oak, S.71°E., 57 lks. - down
- 7 inch Y. Oak, N.26°W., 80 lks. - found standing.
- 14 inch W. Oak, S.55°W., 6 lks. - standing, but badly rotted.

Set 2 inch x 36 inch iron pipe for corner and mark new trees:

- 24 inch W. Oak, N.49°E., 36.0 feet, scribe S 22 T 26 S R 5 W, 622 B. T.
- 7 inch W. Oak, S.84°30'E., 39.6 feet, scribe S 27, T26S, R5W, 622 BT.
- 7 inch W. Oak, S.76°30'W., 2.5 feet, scribe S 28, T26S, R5W, 622 BT.
- 8 inch W. Oak, N.33°45'W., 32.0 feet scribe S 21, T26S, R5W, 622 BT.

Edwin S. Woodford  
Witness: M. E. Godfrey  
Set on job for Worth Davis  
August, 1952.  
C. S. File No. 42/114.

$\frac{1}{4}$  sec. corner to secs. 22 and 27.

29

Found mound of rock and B. T.s as follows:

- 8 inch W. Oak, S.18 $\frac{3}{4}$ °E., 234 lks. - original B. T.
- 14 inch W. Oak, N.48°W., 387 lks. - original B. T.
- 8 inch W. Oak, S.80 $\frac{1}{2}$ °W., 11.0 feet scribed R. P. X.
- 18 inch W. Oak, N.31 $\frac{1}{4}$ °E., 24.5 feet scribed R. P. X.
- 8 inch W. Oak, S.5 $\frac{1}{4}$ °E., 24.5 feet scribed R. P. X.

Set a 1 inch x 30 inch iron pipe in rock mound.

Section corner to secs. 1, 2, 11 and 12.

30

Found 3 O.B.T.s:

- 20 inch W. Oak, S.87 $\frac{1}{2}$ °E., 613 lks.
- 30 inch W. Oak, N.72 $\frac{1}{2}$ °E., 608 lks.
- 20 inch Ash, S.7 $\frac{1}{2}$ °W., 199 lks.

Face on Ash tree rotten and no scribe marks visible. The 2 Oaks to the East are still in good condition. Scribe marks found when chopped out.

Set an iron pipe with brass cap for corner marked "County Surveyor's Office, 1957, T26S, R5W,  $\frac{2}{11}$  Sec. corner".

Mark new trees:

- 6 inch Ash, N.80°W., 19.8 feet marked T26S, R5W, S 2 CS. BT.
- 6 inch W. Oak, S.28°W., 114.0 feet mkd. T26S, R5W, S 11 CS BT.
- 7 inch W. Oak, S.39°E., 107.9 feet mkd. T26S, R5W, S 12 CS BT.
- 8 inch W. Oak, N.84 $\frac{1}{2}$ °E., 139.5 ft. mkd. T26S, R5W, S 1, CS BT.

County Surveyor's Office  
April 15, 1957  
C. S. File No. 47/174.

$\frac{1}{4}$  corner to secs. 11 and 12.

31

Found both old BTs. The tree to the Northeast is alive but badly rotted in the center but found scribe marks plain in rotted area. Set corner at intersection of distances. Read bearings to both trees from this point. The bearing to the Northeast tree fits good. The bearing to the tree to the South is S.2 $\frac{1}{2}$ °E., instead of S2 $\frac{1}{2}$ °W., as called for in Government notes.

Set an iron pipe with brass cap mkd.

County Surveyor's  
T26S R5W  
 $\frac{1}{4}$  11 | 12  
1957  
Office.

Marked two new trees:

- 8 inch B. Oak, N.45 $\frac{1}{2}$ °W., 67.8 feet, mkd.  $\frac{1}{4}$  S 11 CS BT.
- 24 inch B. Oak, N.49°E., 109.7 feet, mkd.  $\frac{1}{4}$  S 12 CS BT.

$\frac{1}{4}$  corner to secs. 13 and 14.

32

We found both original BTs alive and in good condition. The Northwest tree is a B. O., 3' 6" diam. The Northeast tree is a B. O., 5 feet dia. Trees check for bearing and distance. Scribing visible and in good condition.

Set 1 inch iron pipe with brass cap mkd. County Surveyor's Office,  $\frac{1}{4}$  S 14/13 1954, T26S, R5W. Scribed: 8" W.O. N42°14'W, 95.2',  $\frac{1}{4}$  S 14 CS BT.  
20" B.O. S.85°30'E, 243.1',  $\frac{1}{4}$  S 13 CS BT.

James W. Byron,  
Dep. Co. Surveyor  
Sept. 1, 1954.  
C. S. File No.  
46/74.