

Douglas County Surveyor's Record of
Government Corners Renewed

26 T. S. 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

James W. Byron, Deputy
Milo Godfrey
S. A. Bilow
December 1958
C. S. File No. 49/128

(continued)

New BT's: Rescribe Orig., now 30" B.Oak N.48°E. 61.7 ft. scribed
1/4 S 8 CS BT. 52 1/2 FT. 9.0
8" B. Oak bears S.11°E. 1/4 scribed 1/4 S17 CS BT.

1/4 Section Corner to Sections 14 & 15. 56
Found - Orig. 36", now 48" Pine, Partly rotted Snag, N.35°E. 28.4 ft.,
I find section of old face showing good axe marks & Scribing "S".
No trace of Orig. S.W. BT.

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1958
1/4 S15/S14 T26S R5W

New BT's; 16" R.Fir bears S.61°W. 18.7 ft. scribed S15 1/4 CS BT.
18" R.Fir bears S.32 1/2°E. 25.6 ft. scribed 1/4 S14 CS BT.

Meander Corner to Sections 23 & 26, Left Bank. 57

Found - 1/2" Iron Pipe set in Concrete at Corner & Both Orig. BT's.
as recorded:

Orig. 12", now 30" W. Oak N.16 1/2°W. 38.2 ft., previously
opened, shows good scribing "BT".

Orig. , now 24" B. Oak S. 9°E. 26.4 ft., shows good scar.
I do not open.

New BT: 12" W. Oak bears N. 18°E. 30.3 ft. Scribed MC S23 CS BT.

James W. Byron, Deputy
Milo Godfrey
Clete Putman
June 21, 1960
C.S. File No. 49/124

Section Corner to Secs. 1 & 2, T26S R5W, & Secs. 35 and 36, T25SR5W. 58
Found - Orig. 24", now 44" Fir S.42 1/2°E. 4.6 ft. I open & find
good scribing.

Also find Laurel Trees, now mostly rotted that check for
Orig. NW. & NE BT's.

No trace of Orig. S. W. BT. found.

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960

S35	S36	T25S
S 2	S 1	T26S

R5W

New BT's: 18" R.Fir bears N.53°E. 12.4 ft. scribed S36 T25SR5W CS BT.
11" Maple bears N.37°W. 10.1 ft. scribed T25S R5W S35 CS BT.
10" R.Fir bears S.22°W. 59.0 ft. scribed T26S R5W S2 CS BT.

James W. Byron
For Ed Russell
April 1955
C.S. No. 47/12

Renew Section Corner

R6W	S36	S31	R5W	T25S
	S 1	S 6		T26S

OK PER M103-30
BY BEUTZ
NOV-56 M106-4

Found: 1 1/2" I. pipe at fence int. Use 1 1/2" I. Pipe for Section Corner.
All Original Bearing Trees gone.

Blazed & Scribed: 10" R.Fir N.17°E. 146.0 ft. S31 T26S R5W CS BT.
16" R.Fir (Steel of) 600.0 ft. S.84°E. S6 T26S R5W CS BT
No other Trees near.

James W. Byron, Deputy
Milo Godfrey
Clete Putnam
July 1960
C. S. File No. 49/125

1/4 Corner Sec. 25, T26-5W & Sec. 30 T26-4W. 60
Found - Stone at Corner as recorded.

10", now 14" B.Oak East 37.7 ft. We open old scared
section & find good reverse scribing "X R P".

Also find base of Oak Stump N.40°E. 48.6 ft.
No trace of S. W. BT.

Set Brass Cap alongside Corner Stone & Mark: County Surveyor's Office, 1960
1/4 S25/S30 T26S
R5W R4W

New BT's: 10" B.Oak bears N.62°E. 23.0 ft. scribed 1/4 S30 CS BT.
22" Pine bears N.10°W. 50.4 ft. scribed 1/4 S25 CS BT.

Sec. Corner Sec. 24 & 25, T26-5W & Secs. 19 & 30, T26-4W. 61
Found - 2" x 18" I. P. at Corner as recorded by

No Trace of Orig. BT. Found Corner is in N. S. Fence Line which
seems to line with Range line and as projected through 1/4
Corner S13/S18 Also corner location.

Check call to foot of Hill, O. K.
Fence Line Thus:

