

Douglas County Surveyor's Record of  
Government Corners Renewed

26 T. S. 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

74  
 $\frac{1}{4}$  Section Corner to Sections 30 & 31  
 Found - White Oak (down & dead) S.  $83^{\circ}$  W. 85.8 feet. Cut open & found good reverse scribing "BT".  
 White Oak (now 24" in diameter) N.  $33\frac{1}{2}^{\circ}$  E. 171.6 feet. -Opened & found good scribing "S"-tree alive and in good condition.  
 Set - Brass cap at corner mkd: County Surveyor's Office -  $\frac{1}{4}$  S 30  
 1963. S 31  
 New BT's: 8" white oak N.  $67^{\circ}$  W 23.0 feet scribed  $\frac{1}{4}$  S 30 CS BT.  
 15" black Oak S.  $75^{\circ}$  W. 26.2 feet scribed  $\frac{1}{4}$  S 31 CS BT.  
 Note: Corner lies in West edge of power line clearing.

75  
 $\frac{1}{4}$  Section Corner to Sections 30 & 29  
 Found - Old Laurel tree (16" in diameter) S.  $54^{\circ}$  E. 30.4 feet. Scribing "BT" visible on old face. Tree alive but old face & entire center of tree dead and rotting.  
 Old Laurel tree (now 29" in diameter) S.  $24^{\circ}$  W. 22.4 feet. Chopped open and found good reverse scribing "4" on over growth of old face. Tree nearly dead.  
 Set: Brass cap at corner mkd: County Surveyors Office, 1963 -  $\frac{1}{4}$  S S  
 30 / 29  
 New BT's: 19" Douglas Fir S.  $87^{\circ}$  W. 30.5 feet, scribed  $\frac{1}{4}$  S 30 CS BT.  
 26" Douglas Fir S.  $58^{\circ}$  E. 40.2 feet, scribed  $\frac{1}{4}$  S 29 CS BT.  
 Note: Corner lies 7.5 feet West of old N. & S. fence line.

76  
 S. E. Corner D. L. C. No. 47  
 Found: Maple tree (now 18" in diameter) S.  $70^{\circ}$  E. 11.8 feet-cut open and found scribing "X" (Fleser's BT) See Renewal No. 11.  
 Ash tree (now 22" in diameter) N.  $36^{\circ}$  E. 14.1 feet. Shows good scar. Did not open. (Fleser's BT)  
 Set: Brass cap at corner mkd: County Surveyors - S.E. DLC No. 47. Office, 1963  
 Blaze & Rescribe: 22" ash, N.  $36^{\circ}$  E. 14.1 feet. (to old face) scribed S.E. D. L. C. No. 47 CS BT.  
 New BT: 13" Maple S.  $26^{\circ}$  E. 24.9 feet, scribed SE D.L.C. No. 47 CS BT.  
 Note: Corner lies in old fence corner. Fences approximately N. & W.

77  
 S. E. Corner J. Akin D. L. C. No. 51  
 Found: 18" white oak N.  $41\frac{1}{2}^{\circ}$  W. 30.0 feet-opened and found good scribing "RPX" - (Fleser's BT) See Renewal No. 12.  
 Black oak (now 18" in diameter) S.  $88\frac{3}{4}^{\circ}$  W. 40.8 feet-shows scar where it was previously opened. Did not re-open. (Fleser's BT)  
 Set: ~~Brass cap at corner mkd: County Surveyor's S.E. D.L.C. No. 51. Office, 1963.~~ REMOVED - REPLACED WITH  $\frac{3}{4}$ " I. ROD office, 1963. REMOVED MARCH 1964 - C.S. FILE NO. 5351 SEE REN # 118 R.P.  
 New BT's: 14" incense cedar S.  $33^{\circ}$  W. 41.1 feet, scribed SE D.L.C. 51 CS BT.  
 16" madrone N.  $36^{\circ}$  W. 25.4 feet, scribed SE D.L.C. 51 CS BT.  
 Note: No trace found of either original BT. R.P.

78  
 S. W. Corner of D. L. C. No. 47  
 Found: 18" Black oak N.  $19^{\circ}$  W. 21.1 feet, scribing visible "RP"-scar was not completely healed over. See renewal No. 10  
 Oak (dead & down) S.  $54^{\circ}$  W. 11.4 feet (not 11.4 ft)-opened and found good scribing "T".  
 No trace found of Oak N.  $1^{\circ}$  W. 37 feet.  
 Also found 10" white oak N.  $43^{\circ}$  E. 11.8 feet, showing good scars. Cut open and found good scribing "BT"-this tree was not recorded in renewal.  
 Set: ~~Brass cap at corner mkd: County Surveyors - S.W. D.L.C. No. 47. Office, 1963~~ BRASS CAP REMOVED - REPLACED WITH  $\frac{3}{4}$ " I. ROD. SEE REN # 120 - C.B. FILE # 53/51  
 New BT's: 10" white oak N.  $43^{\circ}$  E. 11.8 feet, scribed SW D.L.C. 47 CS BT (rescribed)  
 10" white oak S.  $25^{\circ}$  E. 16.6 feet, scribed SW D.L.C. 47 CS BT  
 Note: Corner lies in fence corner-fences South & East.

Milo E. Godfrey, Dep. Co. Surv.  
 Wm. Stoffel, & Mike Stone  
 December, 1963. & November  
 C.S. File: 49/125