

Douglas County Surveyor's Record of
Government Corners Renewed

T. 26 S. T. S. R. 5 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

89

Most Southerly S. W. Corner D. L. C. No. 40.
Found - 33" White Oak S.45°W. 168.3 ft. Cut open & found good scribing "B".
Stump Hole N.25°W. 136.0 feet.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T26S R5W S SW DLC 40
Blaze & Rescribe 33" White Oak S.45°W. 168.3 ft. Mkd: SW DLC 40 CS BT.
New BT: 14" White Oak N.7½°E. 180.6 ft. Mkd: S W DLC 40 CS BT.

90

¼ Corner to Sections 23 and 26.
Found - 21" White Oak N.76½°E. 699.6 ft., cut open & fd. #155 good scribing "½S".
Slight depression in ground (possible old stump hole) S.71½°W 228.4 ft.
Set - Brass Cap At Cor. Mkd: County Surveyor's Office, 1964 T26S R5W ¼ S23 S26
New Bt's: 14" Triple White Oak (measured below forks) N.68°W. 123.4 ft.
Mkd: ¼ S23 CS BT.
18" White Oak S.87½°W. 182.9 ft. Mkd: ¼ S26 CS BT.
Note - The Iron Rod at South Corner of Lots 7 & 8, "Echo Bend" bears S.82½°W. 140.2 ft.
The Iron Rod at the South Corner of Lots 6 & 7, "Echo Bend" bears S.7½°W. 46.8 ft.

91

¼ Corner to Sections 12 and 13.
Found - 22" Oak N.75°W. 15.8 ft. (standing but dead) Cut open & find good scribing "S".
Oak S.33°W. 62.7 ft., dead & down. Did not open.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964 T26S R5W ¼ S12 S13
New BT's: 15" D.Fir S.24°E. 14.3 ft. Mkd: ¼ S13 CS BT.
18" D.Fir N.13°W. 23.7 ft. Mkd: ¼ S12 CS BT.

92

¼ Corner to Sections 17 and 18.
Found - Square Spike buried under loose fill. (See Ren. # 4)
Did not find Oak Stake.
Black Oak N.10°E. 23.8 ft., previously opened, center rotted away.
Black Oak N.73°W. 24.2 ft. Has face rotted, no scribing.
Black Oak S.40½°W. 35.0 ft. center completely burned out.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964 T26S R5W ¼ S 18/S 17 Set spike alongside.
New BT's: 11" W.Oak S.52°E. 47.5 ft. Mkd: ¼ S17 CS BT.
18" Bl. Oak S.67°W. 54.6 ft. Mkd: ¼ S18 CS BT.
Corner is 1.5 feet West of North and South Fence Line.

93

Section Corner common to Sections 7 - 8 - 17 - 18.
Found - Scribed Oak Stake with square Iron Bar alongside. (See Ren. # 5)
21" D.Fir S.29°W. 39.2 ft., shows 2 very plain axe scars.
Fir Stump S.56°E. 36.7 ft.; shows good scar.
Fir Stump N.59°W. 45.5 ft., shows good scars.
Fir Stump N.53°E. 30.4 ft. (not N.33°E. 36.7 ft.) Opened & find good scribing.
Set - Alongside Oak Stake Brass Cap Mkd: County Surveyors Office, 1964 T26S R5W S 7 | S 8 S18 | S17
New BT's: 7" D.Fir N.23°W. 21.6 ft. Mkd: T26S R5W S 7 CS BT.
13" D.Fir S.72½°E. 52.9 ft. Mkd: T26S R5W S17 CS BT.
4" D. Fir N.56½°E. 52.4 ft. Mkd:: S8 CS BT.
Note - A fence corner, fences S. & W., bears N. E. 7 feet.

94

Section Corner common to Sections 17 - 18 - 19 - 20.
Found - 48" Bl. Oak N.58½°E. 1013.1 ft., shows very good scar.
Tree alive and in good condition.
Down & badly rotted Oak S.81½°W. 421.7 ft., both upper & lower scars opened many years ago, center completely rotted away.
Oak N.88½°W. 613.8 ft., down many years, trunk almost completely buried in swamp, impossible to tell exact spot where it stood.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964 T26S R5W S 18 | S 17 S 19 | S 20
New BT's: (See over)

Milo E. Godfrey, Deputy County Surveyor
Wm. Stoffel and Mike Stone
Jan. and February 1964
C. S. File No. 49/125