

Douglas County Surveyor's Record of  
Government Corners Renewed.

T. 26 S. T. S. R. 5 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

100

S. E. Corner D. L. C. No. 46.  
Found - 24" Bl. Oak S.75°E. 55.7 ft. (no dist. given in Orig. Field Notes)  
Cut open & found good reverse scribing "BT".  
Corner set in N. & S. fence line running south from S.W. Corner  
DLC No. 48.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
T26S R5W S.E. Cor. D.L.C. 46  
New BT's: 13" W.Oak N.80°W. 26.7 ft. Mkd: S.E. DLC 46 CS BT.  
9" Bl.Oak N.23°E. 16.2 ft. Mkd: SE DLC 46 CS BT.  
Note - Fence Corner, fences North & East Bears South 14.0 feet.

RE-RENEWED, SEE CORNER NO. #157

101

Reference Point to S.W. Cor. DLC 43  
S.E. Cor. DLC 45 (See Ren. No. 41)  
N.E. Cor. DLC 44 (Ref. Point S.88°51'E. 319.53 feet)  
Found - 1½" Pipe set in East R/W Line of Railroad for Ref. Point to DLC Corner  
As pipe is difficult to find, tied in two poles:  
From 1½" Pipe as found, 3rd Telegraph Pole south of RR crossing,  
E. side of tracks, bears S.43°W. 14.2 ft.  
Power Pole, Copco B 10265, bears S.65°E. 14.8 ft.

Fd. 4/88  
D. BENTZ  
M106-4

102

S. E. Corner D.L.C. No. 49.  
Found - 28" W.Oak N.25°E. 95.0 ft., opened & found good scribing "R".  
White Oak (approx. same size) that fits closely, off 3° in bearing  
and 2 ft. in dist., for other Orig. BT., no scar visible,  
may or may not be other Orig. BT.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
T26S R5W S.E. DLC 49  
New BT's: 18" W.Oak N.67°E. 34.0 ft. Mkd: SE DLC 49 CS BT.  
15" W.Oak S.56°E. 33.3 ft. Mkd: SE DLC 49 CS BT.  
Note - Corner lies approx. 2 ft. west of small creek.

Milo E. Godfrey, Deputy Co. Surveyor  
Wm. Stoffel - Mike Stone - Mike Darby  
March 1964  
C. S. File No. 49/125

103

N. E. Corner D. L. C. No. 49.  
Found - Black Oak S.35°E. 118.8 ft., cut open & found good reverse  
scribing "W". Entire north side of tree has been dead many years.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
T26S R5W N.E. DLC No. 49  
New BT's: 21" W.Oak N.11°W. 24.8 ft. Mkd: NE DLC 49  
11" W.Oak S.42½°E. 47.7 ft. Mkd: NE DLC 49 CS BT.  
Note - Corner is in small creek draining swamp.

104

¼ Corner common to Sections 2 and 1.  
Found - Oak S.44½°W. 157.1 ft., down many years, opened & found good scribng. ¼S  
Ash S.44°E. 186.1 ft., still alive but roots have been washed out by  
creek, lying down across deep gorge in creek. did not open.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
T26S R5W ¼ S 2/S 1  
New BT's: 12" W.Oak S.81°E. 13.3 ft. Mkd: ¼ S1 CS BT.  
17" Bl.Oak S.52°W. 55.8 ft. Mkd: ¼ S2 CS BT.

105

¼ Corner common to Sections 7 and 8.  
Found - 40" Bl.Oak N.40°W. 162.4 ft., cut open scar & found reverse  
scribing "4", most of orig. face rotted away.  
No trace of N. E. tree.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
T26S R5W ¼ S 7/S 8  
New BT's: 16" Bl. Oak N.42°W. 43.4 ft. Mkd: ¼ S7 CS BT.  
22" Bl.Oak N.70°E. 34.5 ft. Mkd: ¼ S8 CS BT.

106

¼ Corner common to Sections 8 and 9.  
Found - 30" W.Oak S.27°W. 63.4 ft., opened & fd. good reverse scribing "¼S".  
No trace of N. E. Bearing Tree.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
T26S R5W ¼ S 8/S 9  
New BT's: 10" Bl.Oak S.43°W. 36.4 ft. Mkd: ¼ S8 CS BT.  
12" Bl.Oak S.84°E. 27.2 ft. Mkd: ¼ S9 CS BT.  
Note - Corner lies at south edge of top of E. & W. Ridge.