

Douglas County Surveyor's Record of
Government Corners Renewed

T. 26 S. T. S. R. 5 W. R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

118-A

S. E. Corner D. L. C. No. 51.
Calculated position from Survey - No old BT's. found.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T26S R5W S.E. DLC 51
New BT's: 12" W.Oak N.61½°E. 8.7 ft. Mkd: S E DLC 51 CS BT.
15" D.Fir S.84°W. 58.7 ft. Mkd: S.E. DDC 51 CS BT.

See Also Ren # 12477

119

N. E. Corner D. L. C. No. 50.
Calculated position. No old BT's. found.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T26S R5W N.E. DLC 50
New BT's: 10" W.Oak N.25°E. 25.9 ft. Mkd: NE DLC 50 CS BT.
7" W.Oak S.88°E. 11.5 ft. Mkd: N.E. DLC 50 CS BT.

120

Mst. Southerly S.W. Cor. DLC No. 47.
Set Corner in calculated position from survey. No Orig. BT's. found.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963
T26S R5W S. W. DLC 47
New BT's: 9" D.Fir N.75°E. 39.2 ft. Mkd: S.W. DLC 47 CS BT.
7" Madrone N.41°W. 36.6 ft. Mkd: S.W. DLC 47 CS BT.

See Also Ren # 10478

121

¼ Corner to Sections 31 and 32.
Set by proportionate measurement.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T26S R5W ¼ S31/S32.
New BT's: 16" I. Cedar N.31½°W. 45.3 ft. Mkd: ¼ S31 CS BT.
5" White Oak S.17°E. 66.7 ft. Mkd: ¼ S32 CS BT.
An old burned-out Laurel Stump fits bearing & distance for
Original S. W. Bearing Tree.

122

¼ Corner to Sections 29 and 28.
Corner set from survey between section corners and facing of
Ofig. BT.
Found - Black Oak, now 38", S.17½°W. (instead of S.17½°E.) 188.1 ft.
Opened scar & found good scribing "S". Other BT. not found.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T.26S R5W ¼ S29/S28
New BT's: 15" Bl.Oak S.20°W. 13.0 ft. Mkd: ¼ S29 CS BT.
12" Bl.Oak N.34½°E. 19.6 ft. Mkd: ¼ S28 CS BT.
Note - Bearings to new trees read with compass set on 19½° East Var.

123

S.W. Corner D L L. C. No. 41.
Found - ¾" Iron Pipe at Corner. - See Ren. No. 6.
20" Bl.Oak S.41½°E. 5.2 ft., now dead & down.
Now 12" Bl. Oak N.41½°E. 48.3 ft., shows good scar. Didn't open.
New BT: 20" Black Oak S.61°E. 39.7 ft. Mkd: S W DLC 41 CS BT.

124

¼ Corner to Sections 27 and 26.
Found - 37" W.Oak S.86½°E. 126.7 ft., shows good scar. Did not open.
Down, dead, & partially burned Bl. Oak N.35½°W. 82.5 ft.
Opened & found reverse scribing "BT" on overgrowth of old face.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T26S R5W ¼ S27/S26.
Rescribe-37" W.Oak S.82°E. (our bearing) 126.7 ft. Mkd: ¼ S26 CS BT.
New BT's: 31" Bl.Oak S.13°W. 210.0 ft. Mkd: ¼ S27 CS BT.
Note - Our bearings read with compass set on variation of 19½°E.

125

¼ Corner to Sections 32 and 33.
Found - Dead & Rotten Laurel Snag N.38°E. 66.0 ft. Overgrowth
of lower scar with good reverse scribing "BT".
Dead Laurel Snag S.21½°W. (not S.31½°W) 33.0 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T26S R5W ¼ S32/S33.

(continued next page.)

Milo E. Godfrey, Deputy
Wm. Stoffel - M. Stone - M. Darby
March 1964
C. S. File No. 53/51
RM 1 - 42

Milo E. Godfrey, Deputy
Stoffel - Stone - Darby
March 1964
C.S. File No. 53/51 Map File RM 1 - 42

Milo E. Godfrey, Deputy
Wm. Stoffel - M. Stone - M. Darby
April 1964
C. S. File No. 49/125