

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 26 S. T. S. R. 5 W. R. W. W. M.

KOBE-CHAPMAN CO., EUGENE, ORE. 21881

131

$\frac{1}{4}$  Section Corner to Sections 20 and 21.  
Found - 25" White Oak S.  $1\frac{1}{2}^{\circ}$  E. 368.9 ft., shows good scars.  
28" White Oak N.  $18^{\circ}$  W. 429.0 ft., opened in 1944.  
Did not find Iron Bar set by Morgan, 1944. See Ren. #16.  
(find yellow tags on both BT's.)  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
T26S R5W  $\frac{1}{4}$  S20/S21  
New BT's: 15" W. Oak S.  $41^{\circ}$  E. 160.2 ft. Mkd:  $\frac{1}{4}$  S21 CS BT.  
14" W. Oak S.  $32^{\circ}$  W. 137.5 ft. Mkd:  $\frac{1}{4}$  S20 CS BT.  
Note - Corner lies in open pasture land approx. 325 ft. east  
of N. and S. Fence Line.

~~Int. "L" Corner DLC. 48 AND - S.B. T25-6W  
Mst. Southerly S.E. Corner D.L.C. #47.  
Found -  $\frac{3}{4}$ " Iron Pipe, 4" below present ground surface, Ren. #33.  
9" White Oak S.  $24^{\circ}$  E. 16.6 ft., very plain scar.  
Corner at old fence corner, traces of old fences W. & N.  
New BT: 18" D. Fir S.  $71^{\circ}$  E. 36.4 ft. Mkd: Int. "L" DLC 48 CS BT.~~

132

$\frac{1}{4}$  Corner to Sec. 31, T26-5W. & Sec. 36, T26-6W.  
Found - 34" Bl. Oak S.  $61^{\circ}$  W. 99.7 ft., opened & found good scribing "B".  
Burned out Oak Stump N.  $65^{\circ}$  E. 20.5 ft.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
T26S R6W  $\frac{1}{4}$  R6W S36/S31 R5W.  
New BT's: 11" W. Oak S.  $48\frac{1}{2}^{\circ}$  E. 29.4 ft. Mkd:  $\frac{1}{4}$  S31 CS BT.  
10" W. Oak N.  $15^{\circ}$  W. 25.9 ft. Mkd:  $\frac{1}{4}$  S36 CS BT.  
Note - Corner is approx. 150 ft. E. & 100 ft. S. of E. end of  
Currier Avenue in "Fairacres".

Milo E. Godfrey, Deputy County Surveyor  
Wm. Stoffel - M. Stone - M. Darby  
April & Map 1964  
C. S. File No. 49/125

~~Center of Section 7.  
Set -  $\frac{3}{4}$ " Iron Rod  
Bearing Tree: 12" Fir bears N.  $85^{\circ}30'$  W.  
scribed C & S 7 BT.~~

~~Wagon. Twp. & Range  
S.B. T. 25 S. R. 6 W.~~

~~Don E. Carrett  
April 20, 1966  
Map File M 21 - 44~~

132A

Wit. Corner to  $\frac{1}{4}$  Corner to Sections 21 and 22.  
Found -  $\frac{3}{4}$ " Pine with flat head. (See Ren. #27)  
Bearing Trees in evidence.

133

Meander Corner, right bank Umpqua River Sections 21 and 22.  
Set - 1" Pipe 7' long, 3' South Top Bank  
10" Ash N.  $35^{\circ}$  E. 6.0 ft. BT.  
12" Ash S.  $67^{\circ}$  W. 18.1 ft. BT.

Wm. A. Elmstad  
June SAPE & Doug. Short  
Sept., 1966  
M 32 - 30

MICROFILM TO HERE 10/87

134

Section Corner to Secs. 2 & 3, T27-5W & Secs. 34 & 35, T26-5W.  
Set - Brass Cap Stamped Sec. Cor. 2 & 3, T27SR5W & Sec. 34 & 35, T26S R5W.  
Seri 1"x 30" Iron Rod bears N.  $27^{\circ}$  W. 76.17 ft.  
N.  $52^{\circ}$  E. 77.90 ft.  
S.  $27^{\circ}$  W. 68.77 ft.  
S.  $53^{\circ}$  W. 76.82 ft.

Baughman,  
Glenn  
4 Star Dev.  
M 35 - 54

March 18, 1968

SEPT. 68

135

NOT  
USED