

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 26 S. T. S. R. 5 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

John M. Powell  
Frank Jones  
C.S. File 49/125

MARCH 71

Section Corner to Sections 20 - 21 - 28 - 29. 136  
Found - County Surveyor's Brass Cap, properly marked in 1963, See Ren. #82.  
Orig. 34", now 37" B.Oak, S.38 $\frac{1}{2}$ °E. 43.6 ft.  
Reblzd. & Rescrbd.: T26S R5W S28 CS BT.  
Orig. 39", now 43" B.Oak, S.82°W. 19.1 ft.  
Reblzd. & Rescrbd.: T26S R5W S29 CS BT.  
15", now 17" D.Fir, S.46°E. 20.0 ft., good scars, pitched over  
scribing, This tree to be cut.  
22" D.Fir, now 22", N.16°W. 10.4 ft., good scars, pitched over  
scribing. This tree to be cut.  
15" D.Fir, now 14" N.76 $\frac{1}{2}$ °E. 36.7 ft., shows good scar. O.K. & Tagged.  
New BT: 6" W.Oak N.56°W. 20.0 ft., mkd: T26S R5W S20 CS BT.

7/23/69

This corner set from resurvey of township line for T25-6 & T25-5. 137  
 $\frac{1}{4}$  Cor. for Sec. 3 T26-5 and Sec. 34 T25-5.

Set - Brass Cap at corner mkd: County Surveyors T 25 S  
(Steel fence post alongside) Office  $\frac{1}{4}$  S34 R  
1972 S 3 5W  
T 26 S

Bearing Objects: T Iron 1" x 36", N.39°E., 20.0 ft.  
T Iron 1" x 36", South, 20.0 ft.

No BT's available.

1/19/72

This corner set from resurvey of township line for T26-5 and T25-5. 138  
Section corner for Secs. 33 & 34 T25-5 and Secs. 4 & 3 T26-5.

Set - Brass cap at corner mkd: County Surveyors T 25 S R 5 W  
(Steel fence post alongside) Office S33|S34  
1972 S 4|S 3  
T 26 S R 5 W

New BT's: 13" B. Oak, N.56°W., 42.2 ft. scribed T25S R5W S33 CS BT.  
14" D. Fir, N.67°E., 60.5 ft. scribed T25S R5W S34 CS BT.  
11" W. Oak, S82°E., 49.5 ft. scribed T26S R5W S3 CS BT.  
15" Maple, S.8°W., 46.0 ft. scribed T26S R5W S4 CS BT.

East-west fence bears south 45.0 ft.

1/19/72

This corner set from resurvey of township line for T25-5 & T26-5. 139  
 $\frac{1}{4}$  Corner for Sec. 4 T26-5 and Sec. 33 T25-5.

Set - Brass cap at  $\frac{1}{4}$  cor. mkd: County Surveyors T 25 S R 5 W  
Office  $\frac{1}{4}$  S 33  
1972 S 4  
T 26 S

New BT's: 15" D. Fir, S.70°E., 18.3 ft. scribed  $\frac{1}{4}$  S4 CS BT.  
15" Maple, N.11°W., 19.6 ft. scribed  $\frac{1}{4}$  S33 CS BT.

1/21/72

This corner set from resurvey of township line for T26-5 and T25-5. 140  
Section corner for Secs. 32 & 33 T25-5 and Secs. 5 & 4 T26-5.

Set - Brass cap at Sec. cor. mkd: County Surveyors T 25 S R 5 W  
Office S 32|S 33  
1972 S 5|S 4

New BT's: 10" W. Oak, N.31 $\frac{1}{2}$ °W., 37.0 ft. scribed T25S R5W S32 CS BT.  
12" W. Oak, N.3°E., 37.3 ft. scribed T25S R5W S33 CS BT.  
12" W. Oak, S25°E., 15.2 ft. scribed T26S R5W S4 CS BT.  
10" W. Oak, S28°W., 40.6 ft. scribed T26S R5W S5 CS BT.

Fence cor. bears S.40°E., 21.6 ft.

1/21/72

This corner set from resurvey of township line for T26-5 and T25-5. 141  
 $\frac{1}{4}$  Corner for Sec. 32 T25-5 and Sec. 5 T26-5.

Set - Brass Cap at  $\frac{1}{4}$  Cor. mkd: County Surveyors T 25 S R 5 W  
(Steel fence post alongside) Office S 32  
1972 S 5  
T 26 S

New BT's: 12" W. Oak, N.54°E., 179.6 ft. scribed  $\frac{1}{4}$  S32 CS BT.  
22" Triple Ash, S.10°W., 229.8 ft. scribed  $\frac{1}{4}$  S5 CS BT.

East-west fence bears South 18.0 ft.

1/21/72

Francis L. Ingram, Deputy County Surveyor  
John M. Powell  
January, 1972  
C. S. File 56/10 M 44 - 48