

Douglas County Surveyor's Record of
Government Corners Renewed

T 26 T. S. R 5 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

Douglas County Surveyors Office
Randall Smith
Stephen J. Flause
Deputies
C.S. 62/31
Feb. 4-5, 1986

151

Section Corner for Sections 13 and 24; and Secs. 18 & 19 of T.26-4.
Found - A 1958 DCSO brass cap/I.P. protruding 12" above ground. Ren. #51
(Orig. stone not found.)
10" now 16" W. Oak with a fully healed double blaze bears
S.42°53'W., 296.0 ft. (agrees with record)
13" now 22" B. Oak with a fully healed double blaze bears
N.11°52'E., 373.3 ft. (agrees with record.)
New BTs - 13" W. Oak double blazed and scribed "T26S R4W S19 CSBT" bears
S.72½°E., 317.3 ft.
22" Pear (not scribed) (stands alone in open field) bears
N.17°W., 263.4 ft.
Corner lies in open field approx. 150 ft. North of North Bank Road.
2/5/86

152

Section corner for Sections 9, 10, 15 and 16.
Found - A 1964 DCSO Brass cap/I.P. protruding 12" above ground. Ren. #87
(Axle per Ren. #20 not found.)
18" now 24" dia. 3½ ft. high stump with a rotted out center old
axes' marks and a blaze (no scribe found) bears S.81°E., 32.2 ft
(Rec. N.88°E., 31.0 ft. dist. possible face measurements) Orig.
(No other orig. BTs found)
12" now 16" dia. W. Oak with a fully healed double blaze bears
S.48°E., 89.0 ft. (agrees with rec.) Ren. #20
4" now 6" dia. W. Oak with a fully healed double blaze bears
North, 32.3 ft. (agrees with rec.) Ren. #87
New BTs - 14" dia. W. Oak (was thought to be NW BT per Ren. #20, we opened
no scribing was found.) single blazed and scribed "T26S R5W S9
CS BT" bears N.43 3/4°W., 39.9 ft.
4" dia. W. Oak double blazed and scribed "X BT" bears S.21°E.,
46.5 ft.
Corner lies in a field approx. 90 ft. SE of North Bank Rd. centerline and
3½ ft. west of a fence.
2/4/86

Douglas County
Surveyors Office
S. Flause and
R. Smith, Deputies
Feb. 20, 1986
C.S. 62/31

1/4 Corner for Sections 14 and 23. Ren. #39 153
Found - A 2 3/8" brass cap, 1954 DCSO, on a 1¼" O.D. I.P. firmly set
and protruding approx. 6" above ground. A low, loose mound
of stone approx. 2 ft. in diam. surrounds base of B.C. monument.
(Note, Local attraction requires setting declination 1 3/4° further east.)
One orig. BT found, a W.oak 20" diam., now a 26" DBH white oak,
(called a 28" tree in Ren. #39) has an opened partially rehealed
single blaze with the scribing "1/4 S" visible and bears S.79°W.,
389.4 ft. (as per record)
A 15" W. Oak now a 20" DBH white oak with a healed double blaze
(one blaze previously opened, no scribing visible, bears
S.84°W., 382.7 ft. (Rec. S.84°12'W., 383.5 ft.) Ren. #39
A 7" B.O. now a 12" DBH white oak with a fully healed double
blaze bears N.30°W., 179.2 ft. dist. (Rec. N.30°W., 180.2 ft.
possible dist. to center of trunk at blaze height.)
New BT - A 7" DBH white oak scribed 1/4 S14 CS BT on a double blaze
bears N.47½°W., 134.0 ft. dist.

154

Douglas County
Surveyors Office
Randall Smith
Stephen J. Flause
Feb. 28, 1986
C.S. 62/31

1/4 Corner for Sections 26 and 35
Found - 1/2" inside dia. I.P. protruding 4" above ground. (Rec. per Ren. #
19, 3/4") Pipe leans 2½" north of plumb.
Corner stone (per Subd. Vol. 4 Pg. 5) measures 8" x 6" x 14".
(Rec. 8"x8"x14") buried 4" beneath ground, marked "+ IP" on top.
(Plumb position of I.P. is 4½" south of "+" on corner stone.)
8" now 15" dia. W. oak with a single fully healed blaze bears
N.54°E., 17.0 ft. (Vol. 4 Pg. 5 - agrees with record)
10" now 9" dia. 4 ft. high double trunked W. oak stump with
scribe visible in single partial healed blaze "1/4" bears
S.31°E., 37.9 ft. (Agrees with record, Vol. 4 Pg. 5)
9" now 11" dia. W. oak with a single fully healed blaze bears
S.11°E., 33.5 ft. Ren. #111