

Douglas County Surveyor's Record of
Government Corners Renewed

26 T.S. 6 R.W.W.M.

19

N.W. CORNER CLAIM # 42

I renewed this corner by measurement from Corner 13.30 chains South. I set 4 x 4 x 40" Post also an Iron Pipe 1 1/2 x 30" dia. from which

A Black Oak 20" dia. bears N. 48° E., 33.8 ft.
A Black Oak 14" dia. bears S. 40° E., 62.0 ft.

61

S.W. CORNER CLAIM # 42 - N.W. INTERIOR L CORNER

I renewed this corner from what I believed to be a stump of the original B.T. which is a stump of a Black Oak 28" dia. Ran S. 26° E., 57.2 ft. from stump and set hub from which a Black Oak 18" dia. bearing scars bears S. 19° E. 129 lks. instead of 29 lks. as per. field notes. A White Oak 20" dia. bearing two scars. Top one rotted out. Bottom scar bears scribe marks B.T. when I chopped it open. Tree bears N. 59° 30' E., 36.8 ft. Marked new trees as follows

A Black Oak 30" dia. bears N. 54° 20' E., 120 ft.
A Black Oak 20" dia. S. 32° 30' E., 90.5 ft.

#57

SEC. COR. SECS. 7 and 8

Set 1 x 18" Iron Pipe from which a 36" B. Oak bears S. 70° E., 40.5 ft.

A Red Fir 24" dia. bears S. 3° E., 34.2 ft.

44

COR. 27 and 34

Set post for corner from old B.T. on Oak. Marked new B.T.s as follows

White Oak 8" S. 46° 30' W., 13.9 ft.
White Oak 6" N. 4° W., 12.7 ft.

Reset in 1949. Refer to later page

42

COR. BET. 14 and 15

Set post for corner from old B.T.s. Marked a new B.T.

White Oak 16" N. 31° 30' E., 99.7 ft.

Old tree still good.

70

BET. 3 and 4

Set Corner from old B.T., Oak down, but scribe marks plain. Set a 4 x 4 x 36" Oak Stake. Marked new witness trees as follows

White Oak 8" dia. bears N. 54° W., 59 ft.
White Oak 6" dia. bears N. 22° E., 66 ft.

SEE CORNER NO. 38

SEC. CORNER ON TOWNSHIP LINE FOR 33-34-4-3. (T25S.R6W & T26S.R6W)

Set corner from old Oak B.T. in fair condition. Scribe marks plain. Set 3 x 3 x 36" post and marked following new Bearing Trees

Black Oak 24" dia. S. 64 1/2° W., 7 1/2 ft.
Fir 20" dia. N. 19° E., 22.4 ft.
Fir 14" dia. S. 12° E., 9.0 ft.
Fir 20" dia. N. 56 1/2° W., 25 ft.

96

SEC. COR. BETWEEN 27, 26, 34 and 35.

Set 2" x 5' Iron Pipe from 24" White Oak N. 43 1/2° W., 180.8 ft. old B.T. scribe marks plain, also stump of Ash in evidence. Marked new B.T.s as follows

12" White Oak S. 46° E., 70.7 ft. marked S. 36 C.S. 103.
10" White Oak N. 60 1/2° E., 261.3 ft. mkd. S. 36 C.S. B.T.
8" White Oak N. 4° 36' W., 436.6 ft. mkd. T. 268. R. 6W.
S. 27 C.S. B.T.

103

S.W. CORNER OF JAMES MCKINNEY CL. 47

Set 2" x 4" Bolt sq. head from Charles Roberts old B.T. marked in 1905 (see record) tree marked Black Oak. Marked C.S. Cl. 4 (zone) B.T. for S.W. Cor. Cl. 47. I marked new B.T. as follows

Red Fir 8" dia. bears N. 88° 30' E., 42.2 ft. marked
C.S. Cl. 47 B.T.

102

J. W. Cole Deputy
May 1921

M 1-69

G.A. McHenry
D.C.S.
Wit.

H.L. Eppstein
Co. Sur.
Wit. W.S. Crear
Wit. Bert Lane
Roy. Agee
Sept. 20, 1928
C.S. File 7/148 Crocker, Dec. 1921

H.L. Eppstein
Surveyor
Witnesses
T. F. Powers
B. A. Lane
Sept. 9, 1930

July 17, 1937
H.L. Eppstein
Wit. Bert Lane
N.E. Richardson
John Marks
John Thennes
C. B. Calkins
C.S. File 15/16

H.L. Eppstein
Co. Surveyor
Wit.
Chester Fisher
John Thennes
C.S. File 15/16

N.B. 5/1/17

F.B. 5/1/17

N.B. 5/1/17

July 10, 1927

C.S. File 6/14

C.S. File 14/61

C.S. File 15/16

C.S. File 15/16

C.S. File 15/16