

Douglas County Surveyor's Record of  
Government Corners Renewed

26 T. S. 6 R. W. W. M.

1/4 COR BETWEEN 27-34.

Corner reset from O. B. T., set an iron pin 5/8" x 24" *REN #22*

- 8" W. Oak N 7° 36' W 12.7 ft. (Set by Eppstein 1927)
- 10" W. Oak S 41° 41' W 13.9 ft. (Set by Eppstein 1927)
- 24" W. Oak, N 33° E 40.55 ft. (Set on Original Survey 1870)

42

J. R. Daugherty  
2/10/49  
C.S. 40/216

S. W. COR. D. L. C. 53

1 1/4" x 36" Shaft with 6" Flange on top set at corner fence post.

- 8" W. Oak N 45° 05' W 137.7 ft. *SEARCHED FOR - NOT FOUND - July 1964 M.E.G. C.S. 52/87*
- 12" W. Oak S 40° 30' W 80.3 ft.

43

N. E. Richardson D.C.S.  
Milo Godfrey - Wlt.  
Les Kershner  
May 13, 1946

1/4 COR BETWEEN SECS. 7 and 8

Found stumps of original bearing trees. *REN #21*

Corner in middle of County Road No. 6

- Scribed 8" Maple N 30 1/2° W 22.6 ft.
- 10" W. Oak S 32 1/4° E 30.0 ft.

Set witness point, 1" iron pipe, S 46 1/4° E 13.5 ft.

44

H. Crowder  
Transitman  
Co. Engineer's Office  
May 23, 1951  
C.S. 44/47

MEANDER CORNER ON SECTION LINE BETWEEN SECTIONS 4 and 5: 45

3" Iron Pipe in County Road Cut Bank

Marked 30" Oak N 45 degrees East, 52.5 Ft. MC S 5

24" Oaks N. 30 degrees West, 119.1 Ft. MC S 6 C 5 B.T.

45

B. B. Irving  
Dec. 1951

Southeast corner of Willoughby Churchill D. L. C. No. 37.

Set a Sandstone 4x6x32"

B. Oak, S. 57° E., 72.9 ft.

46

B. B. Irving  
Co. Surveyor  
1 - 15 - 145

N.E. Cor. Cl 40 Set post marked New Trees.

Old Witness Tree gone

White Oak 10" N 69 1/2° W 42 lks.

Black Oak 20" S 38 1/4° W 22 lks.

*REN #4*

Nov. 20, 1884 Thiel

47

N. E. Cor. Cl. 65 Set Post Witness trees.

A White Oak 18" N 88° W lks.

A Black Oak 30" N 53 1/2° W 23 lks.

*SEARCHED FOR - NOT FOUND  
AUG. 1964 O.S. 53/87*

May 16, 1885 Thiel

48

Int. L Cor. D.L.C. 47 Post Marked B. T.

A White Oak 8" S. 20° W., 88 lks.

White Oak 5" N. 89° W 40 lks.

139  
Roberts

Get. 8, 1905

Set

49

Ext. L. Cor. D. L. C. Marked B. T.

Forked B. Oak N 59° E 58 lks.

140

50

1/4 sec. corner of secs. 25/36.

Found split rock with cross on top. Trees have been cut. Scribing on both trees visible and they check for bearing and distance. *REN #1 & 37*

Set a 1 inch iron pipe with brass cap makt. County Surveyor's Office,

T26S, R6W 25/36 IS 1954

FO O.K. July 1964

COR. APPROX. 150' W. OF FENCE

Blazed and Scribed:

6 inch W. O., N. 34 1/2° E., 63.4 feet dist., mkt. 1/4 S 36 CS BT.

4 inch W. O., S. 80° E., 31.5 feet dist., mkt. 1/4 S 36 CS BT.

#175

51

J. W. Byron  
Dep. Co. Sur.  
R. Irving - J. Fee  
May 24, 1954  
Done for Darley  
Ware.  
File 46/6.