

Douglas County Surveyor's Record of  
Government Corners Renewed

26

T. S.

6

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

J. W. Byron, Deputy County Surveyor.  
R. Irving - John Fee. May 24, 1954  
Work done for Darley Ware.  
Filed in 46/6. C.S. # 8-12

Witness Corner to N. W. corner of John Akin D.L.C. No. 53.  
Set 1 inch iron pipe with brass cap mkd. County Surveyor's Office, 1954  
NW cor. D.L.C. 53 T26 R6 W.C. *FD. O.K. July 1964. C.S. 52/87*  
Chiseled X in top of R.R. pier mkd. "B.O", N.45°06'E., 78.55 feet.  
Blazed and Scribed:  
22 inch Walnut tree, S.1°17'W., 95.0 feet, mkd. W.C. C53 CS BT.

52

*FD. OK 5/86  
C.S. # 18  
C.S. 63/19*

1/4 sec. corner of sec. 25, T26S, R6W., and sec. 30 T26S, R5W.  
Found: - *SEE REN. NO. 18, T.26S. R.5W.*  
4 inch by 4 inch by 5 foot Cedar post. Also a 6 inch by 6 inch square  
sandstone rock 6 inches under surface mkd 1/4 S. Also found 5/8 inch rod.  
Blazed and scribed:  
10 inch W. O., S.60°E., 483.5 feet dist., mkd. 1/4 S 30 CS BT.

# 182 53

1/4 sec. corner to sec. 13, T26S, R6W., and sec. 18, T26S, R5W.  
Set 1 1/2 inch iron pipe with brass cap mkd County Surveyor's Office  
1/4 S 13/18 T26S R6W R5W 1954. Set at wire fence corner.  
Corner (NW Cor) of Farmers Livestock concrete block building  
bears S.56°E., 281.8 feet dist.  
William beaton bears N.37°23'E.

# 200 54  
*CORNER DESTROYED  
BY CONSTRUCTION  
SEE M 106-18  
G. BAUGHMAN  
5/88*

Ben B. Irving  
Ray Irving  
John Fee  
(County Surveyor's  
Office)  
Dec. 20, 1954  
C. S. File 46/67.

Northeast corner of the Henry Evans Donation Land Claim No. 43.  
Found a 1 inch X 36 inch iron pipe set by Floyd Frear in December 10, 1937.  
Found stumps of two 36 inch Maple tree B. T.s with scribing. *REN. #28*  
Set 1 inch iron pipe with brass cap marked NE cor D.L.C. # 43 1954 T 26 S,  
R 6 W.  
From which:  
10 9 inch Apple bears N.31°W., 22.0 feet.  
No other trees available.

55

**RE-RENEWED, SEE CORNER NO. #93**

1/4 sec. corner to secs. 28 and 29.  
Found 3/4 inch iron pipe set by Cole for 1/4 cor. Also found S.W. BT, *REN. #18*  
now a 24 inch B. O. and checks bearing and distance to pipe. I  
open original BT & find old face and scribe marks "BT". The  
N. E. BT is down.  
Set and iron pipe with Brass Cap marked 1/4 cor 29/28 T26S R6W County  
Surveyors Office 1956, and set alongside Cole's pipe. - *REN. No. 18*  
from which:  
16 inch W. O. bears S.62°W., 24.0 feet scribed 1/4 S 29 CS BT.  
12 inch W. O. bears S.57°E., 34.1 feet scribed 1/4 S 28 CS BT.  
*Found OK - JUNE 1964 M.E.G. - C.S. FILE 52/87*

56

James W. Byron, Deputy County Surveyor  
March 2 - 16, 1956.  
C. S. File No. 47/67.

West S. W. corner of D. L. C. No 42. (George Hannon DLC).  
Found 30 inch B. O. (now dead) N.54°20'E., 120 feet, scribing visible.  
This tree marked by Cole in 1921. Coles SW BT gone. *REN. #20*  
Also found original B. T., 20 inch W. O., N.59°30'E., 36.8 feet. This  
tree down, face rotted. Also found 1 1/2 inch iron pipe laying on  
ground and rust marks 3 inches under surface and checks above  
BTs for bearing and distance.  
Set and iron pipe with Brass Cap marked W S W cor CL 42 T26S R6W  
Douglas County Surveyor's Office 1956. Reset Cole's 1 1/2 inch - *REN. No. 20*  
iron pipe at side of Brass Cap.  
Blaze and Scribe:  
12 inch W. O., North 2.0 feet, marked WSW CL 42, CS BT.  
16 inch B. O., S.12°W., 19.0 feet, marked W S W CL 42, CS BT.  
*Found OK - JUNE 1964 M.E.G. - C.S. FILE 52/87*

57

Section corner to secs. 20, 21, 28 and 29.  
Found a 1 inch iron pipe at corner. The original BT standing, *REN. No. 5*  
center rotted, shows old blaze and checks for bearing and distance.  
The NW and SE original BTs are now stump holes only - check for  
bearing and distance.  
Marked new BTs:  
14 inch W. O., N.5°E., 29.8 feet, scribed T26S., R 6 W., S 21 CS BT.  
24 inch W. O., S.43°E., 24.8 feet, scribed T26S., R6W., S 28 CS BT.  
12 inch W. O. (forked), S.61°W., 75.7 feet, scribed S 29 CS BT.  
10 inch Madrone, N.24°W., 8.0 feet, scribed S 20 CS BT.  
*Found OK - JUNE 1964 - M.E.G. - C.S. FILE 52/87 - 7/70 P. GEE  
M 96-77*

58