

Douglas County Surveyor's Record of  
Government Corners Renewed

26 T. S. 6 R. W. W. M.

ROKE-CHAPMAN CO. EUGENE, ORE. 21881

(continued from . . .

10" W. Oak bears N.49°W. 44.5 ft. scribed S 1 T26S R7W CS BT.  
30" W. Oak bears S. 8°W. 97.0 ft. scribed S12 T26S R7W CS BT.

Section Corner to Sections 5, 6, 7, and 8, 75  
Found - Orig. 36", now 60" B. O. N.41 $\frac{1}{2}$ °W. 252.1 ft., no scar shown,  
but checks bearing & distance.  
Orig. 14", now 30" W. Oak N.60 $\frac{1}{2}$ °E. 392ft. I open & find good  
scribing "T".  
Orig. 36", now 60" B. Oak, down, (record S.73 $\frac{1}{2}$ °W. 382.8 ft)  
I find should be S.73 $\frac{1}{2}$ °W. 142.0 ft. I open & find good  
scribing "T26S".  
Orig. S.E. BT. not found.  
Set Brass Cap at Corner Mkd. County Surveyor's Office, 1959

S 6	S 5	T26S R6W
S 7	S 8	

New BT's: 11" B.Oak bears S.15 $\frac{1}{2}$ °W. 23.0 ft. scribed S 7 T26S R6W CS BT.  
21" Laurel bears S.21 $\frac{1}{2}$ °E. 33.0' . scribed S 8 T26S R6W CS BT.  
6" B.Oak bears N.32°E. 13.2 ft. scribed S 5 T26S R6W CS BT.  
12" W. Oak " N.32°W. 50.0 ft. scribed S 8 T26S R6W CSBT.  
Note - I find  $\frac{1}{2}$ " Iron Rod bears East 35.0 ft. May have been set for  
Section Corner by State.

$\frac{1}{2}$  Section Corner to Sections 6 & 7. 76  
Found - Orig. 20", now 36" W. Oak N.60°W. 103.0 ft. I open &  
find good scribing "S".  
No trace of Orig. S.E. BT. found.  
Set Brass Cap at Corner Mkd: County Surveyor's  $\frac{1}{4}$  S 6 T26S R6W  
Office, 1959 S 7  
New BT's: 36" W. Oak N.60°W. 103.0 ft., "Orig. BT" rescribed  $\frac{1}{4}$  S6 CS BT.  
10" W. Oak bears S.23 $\frac{1}{2}$ °W. 33.2 ft. scribed  $\frac{1}{4}$  S 7 CS BT.  
E. W. Fence 15 ft. South of Corner.

M. C. Lt. Bank S 6/S 5. - Meander Corner. 77  
Set Brass Cap at MC Mkd: MC T26S R6W CS BT. County Surveyor's  
S 6/S 5 Office, 1959  
New BT's: 18" B.Oak bears S.28°E. 52.8 ft. scribed MC S5 CS BT.  
23" B.Oak bears N.29°W. 49.6 ft. scribed MC S6 CS BT.  
*see Ren #73*

Meander Corner Right Bank S 6/S 5. 78  
Set Brass Cap 85 ft. South of M.C. Mkd: County Surveyor's Office, 1959  
W.C. 85' North to MC S6/S5  
T26S R6W  
New BT's: 9" Maple bears N.68°W. 33.0 ft. scribed W.C. MC. S6 CS BT.  
9" Maple bears S.20°E.67.5 ft. scribed W.C. MC. S5 CS BT.

Sec. Cor. Secs. 5 & 6, T26S R6W, & Secs. 31 & 32, T25S R6W. 79  
Found - Stone as recorded CS chisled on North face.  
 $\frac{3}{4}$ " Iron Rod alongside Stone.  
New BT's: 4" W. Oak bears S.72°E. 11.1 ft. scribed S5 CS BT. #179  
10" W. Oak bears N.7°E. 61.1 ft. scribed S32 T25S R6W CS BT.  
18" Laurel W. S.79°W. 46.8 ft. scribed S 6 T26S R6W CS BT.  
6" Laurel bears N.36°W. 38.8 ft. scribed S31 CS BT.

$\frac{1}{4}$  Corner North Line Section 5, T26-6W & Sec. 32, T25-6W. 80  
Set 1" Iron Pipe with Brass Cap  
Mkd: Sec. 32, T25S R6W; Sec. 5, T26S R6W.  
24" Fir N. 3° East 25.6 ft.  $\frac{1}{4}$  Sec. 32 CS BT.  
24" Fir S.35° West 24.0 ft.  $\frac{1}{4}$  Sec. 5 CS BT.

Refer to  
Renewed Corner  
Book No. 1  
T25S R6W  
Corn.# 59

James W. Eyrton, Deputy County Surveyor  
Milo Godfrey  
Clete Putnam  
Dec. 8, 1959  
C. S. File No. 52/5  
Map File M 16 - 59

RE-NEWED CORNER NO. #179