

Douglas County Surveyor's Record of
Government Corners Renewed

T. 26 S. T. S. R. 6 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

38

Section Corner to Secs. 1 & 2, T26-6W. & Secs. 35 & 36, T25-6W.
Found - 16" Oak, Standing but dead, S. 81°W. 229.0 ft. Cut open &
found good reverse scribing "R6W T26S". Orig. face rotted,
overgrowth dead.

Portion of Oak Stump S. 74°E. 54.8 ft., found overgrowth of
old face, badly rotted. No scribing visible.

No trace of N.W. or N.E. bearing trees.

Set - Brass Cap at Cor. Mkd: County Surveyor's T25S R6W S35 | S36
Office, 1963 T26S S 2 | S 1

New BT's: 13" D. Fir N. 45°W. 26.2 ft. Mkd: T25S R6W S35 CS BT.

8" D. Fir S. 52°W. 43.8 ft. Mkd: T26S R6W S2 CS BT.

10" D. Fir S. 73°E. 52.4 ft. Mkd: T26S R6W S1 CS BT.

16" D. Fir N. 13°E. 68.3 ft. Mkd: T25S R6W S36 CS BT.

A 1/2" Pipe & Cedar Stake in E. & W. Fence Line bears S. 29°E. 49.8 feet.

39

1/4 Section Corner to Sec. 36, T25-6W. & Sec. 1, T26-6W.

Found - Stump Hole & rotten remains of Oak Log N. 36 1/2°W. 52.8 ft.

In rotten wood found old flattened areas appearing to be
portions of old face, no scribing found.

Stump Hole S. 27 1/2°E. 34.3 ft. No portion of tree remaining.

This location also fits call in gov't field noted for ridge top.
Corner position lies in E. & W. fence line 3 ft. west of fence

corner (fences East, West and North).

Set - Brass Cap at Cor. Mkd: County Surveyor's T25S R6W 1/4 S36
Office, 1963 T26S S 1

New BT's: 6" D. Fir N. 9°E. 18.2 ft. Mkd: 1/4 S36 CS BT.

5" W. Oak S. 5°E. 19.0 ft. Mkd: 1/4 S 1 CS BT.

100

1/4 Corner to Sec. 24, T26-6W. & Sec. 19, T26-5W.

Found - 22" White Oak S. 24 1/2°E. 159.1 ft., cut open & fd. good
scribing "S". Other BT, not found.

Set - Brass Cap at Cor. Mkd: County Surveyor's office, 1964
T26S R6W 1/4 S 24/S 19 R5W.

New BT's: 15" W. Oak S. 13 1/2°E. 97.5 ft. Mkd: 1/4 S19 CS BT.

8" W. Oak S. 4 1/2°E. 91.0 ft. Mkd: 1/4 S19 CS BT.
No trees near west of line.

March 9, 1964

C. S. File No. 49/125

101

1/4 Corner to Sec. 36, T26-6W. & Sec. 31, T26-5W.

Found - 34" Bl. Oak S. 61°W. 99.7 ft., opened & fd. good scribing "BT".
Burned-out Oak Stump N. 65°E. 20.5 ft.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T26S R6W 1/4 S36/S31 R5W.

New BT's: 11" White Oak S. 48 1/2°E. 29.6 ft. Mkd: 1/4 S31 CS BT.

10" White Oak N. 15°W. 25.9 ft. Mkd: 1/4 S36 CS BT.

Note - Corner is approx. 150 ft. East & 100 ft. South of E. end
of Currier Avenue in "Fairacres".

April 17, 1964

C. S. File No. 49/125

102

S. W. Corner-D.L.C. # 47

Found- Bolt with square head (Set by Eppstein) at Corner. (Ren. # 27)
Found- Douglas Fir (Now 20" Diam.) N. 88 1/2° E. 42.2 ft. - Shows plain
axe scar, - did not open.

Found- Rotten remains of Black Oak S. 50°W 2.5 feet. - This probably was
tree mkd. by Roberts in 1905. For corner-see Vol. 2, page 136.

Found- 21" Doug. Fir S 79°E 49.0 ft., with very plain axe blaze
facing corner - (Did not find any record of this tree.)

New BT: 14" Madrone S 33° E 23.0 ft., Mkd: SW DLC 47 CS BT.

June 17, 1964

C.S. File No. 52/87

Milo E. Godfrey, Deputy County Surveyor
Vernon Tracy and Mike Stone
June and July 1963
C. S. File No. 49/123

Milo E. Godfrey, Deputy
Mike Stone
June, 1964
C. S. File No. 52/87