

Douglas County Surveyor's Record of
Government Corners Renewed

26 T.S. 6 R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

103

Section Corner to 26, 27, 34 & 35.
Found - 1" iron pipe (instead of 2" as called for) corner pipe extends approx. 18" above ground surface. (Ren. # 26)
Old White Oak (now 26" Diam) N 43 $\frac{1}{2}$ ° W 180.8 ft.-scar healed where it was previously opened.
12" white oak S 46° E 70.7 ft.-shows very plain scar.
10" white oak N. 60 3/4° E. 261.3 ft.-upper scar visible-scribing "BT" visible below on rotting face.
Did not find Eppstein's new BT. to N.W.
New BT: 10" white oak S 14° W 333.8 ft., Mkd: T 26 SR 6 W/S 34 CS. BT.
June 17, 1964
C.S. File No. 52/87

104

Meander Corner to Sections 33 & 34, Right Bank
Found - White Oak (Now 15" Diam.) N 43 $\frac{1}{2}$ ° E 29.0 ft.-shows very plain axe scars. (Ren. # 29) Tree in Good condition.
No trace of Original BT found.
Set - Iron pipe with brass cap Mkd. "County Surveyor's Office 1964 T 26 SR 6 W. H.C. S33/334. 28/27 S.S. 2/65
The Brass Cap at the corner of Secs. 27/26 bears N. 97.0 ft.
No suitable trees near in Sec. 33. 33/34

#187

105

1/4 Corner to Sections 21 & 28
Found - 3/4" iron pipe (bent over). Ren. # 65
20" white oak N. 40 $\frac{1}{2}$ ° W 22.8 ft.-some scribing visible in not completely healed scar.
30" white oak (Cole's tree) S, 68.5 ft.-scribing visible in opened scar.
All traces of laurel to the S.E. have completely vanished.
New BT. 18" white oak S 51° E 28.5 ft. Mkd: 1/4 S 28 CS BT.

#183

106

S.E. corner D.L.C. # 61
Found - 1" iron pipe in fence corner. (Fences West, North & approx. S.E.) (Ren. # 11)
Rotten remnants of old oak stump N 70° W 31.7 ft.- too far gone to find scribing or other mks.
13" white oak N 35° W 28.8 ft., with upper & lower axe scars facing corner.-marked by Boyer, according to Voytilla, but not recorded.
New BTS: 13" white oak N 35° W 28.8 ft. MKD: S.E. D.L.C. 61 CS BT.
24" white oak S 87° W 102.7 ft. MKD: S.E. D.L.C. 61 CS BT.

107

S. W. Corner D. L. C. # 48
Found - Old, rotted fir stump.- opened & found good scribing "C 48 T 26 SR 6 W" - stump is corner.
No trace found of white fir to S. E.
Set - Witness corner 4 ft. South of D.L.C. corner.
Brass Cap Mkd: "County Surveyor's Office 1964 T 26 SR 6 W W C 4 ft N. to S.W. DLC 48 L"
New BTS: 17" white fir N 60° W 17.0 ft. Mkd: WC SW DLC 48 CS BT.
16" Doug. fir S 53° E 27.7 ft. Mkd: WC SW DLC 48 CS BT.
Old N & S fence line is 7.0 ft. East of corner.

108

N. E. Corner D. L. C. # 49
Found - Black Oak (now 48" Diam.) N 25° W (not N 38° W-see affidavit of Mrs. Sands on reverse side of this sheet) 207.9 ft.-chopped open & found good scribing "6W"
Corner is in N & S fence line at corner of old fence running short distance west.
Set - Brass Cap - Mkd: "County Surveyor's office 1964 T 26 SR 6 W N.E. DLC 49 7"

(Cont next page)

Wilo E. Godfrey, Deputy
Mike Stone
June 17, 1964
C. S. File No. 52/87