

Douglas County Surveyor's Record of  
Government Corners Renewed

26 T. S. 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Section Corner to Sections 1, 2, 11, 12

114

Found - White Oak snag S 85° E 91.1 ft.-opened & found good reverse scribing-face nearly all rotted.  
Badly rotted remnants of uprooted oak S 13° W 70.6 ft.-too far gone to find markings.  
No trace found of N.E. or N.W. trees.  
Set - Brass Cap Mkd: "County Surveyor's Office 1964 T 26 SR 6 W  
S 2 1/4 S 1"  
S11 | S12  
New BTs: 8" Doug. Fir N 31° E 14.9 ft. Mkd: "T 26 SR 6 W S 1 CS BT."  
8" Doug. Fir S 36° E 18.6 ft. Mkd: " T 26 SR 6W S 12 CS BT."  
12" Doug. Fir S 20° W 23.4 ft. Mkd: "T 26 SR 6 W S 11 CS BT."  
7" Doug. Fir N 82° W 22.2 ft. Mkd: "S 2 CS BT."  
A 3-way fence corner-fences East, West & South-Bears S 62°W  
5.5 ft.

1/4 Corner to Sections 9 & 10

115

Found - White Oak (now 26" diam) N 47° W 15.8 ft.-opened and found scribing "1/4" on badly rotted face.  
No trace of N.E. tree found.  
Set - Brass Cap Mkd: County Surveyor's Office 1964 T 26 SR 6 W  
1/4 S / S "  
9 / 10  
New BTs: 14" Doug. Fir N 82° W 24.4 ft. Mkd: "1/4 S 9 CS BT"  
White Oak S 33° E 53.3 ft. Mkd:"1/4 S 10 CS BT."  
Corner lies in N & S fence line approx. 23 ft. South of fence corner - fences South & West.

Section Corner to Sections 2, 3, 10, 11

116

Found - 3/4" iron reinforcing rod (No record found)  
Madrone(now 24" diam.) N 37° W 78.5 ft.-opened and found scribe MK. (Part of "T") on edge of old, badly rotted face.-Tree appears to be dying.  
Madrone (now 24" diam.) N 43 1/2° E 21.1 ft.-upper scar previously opened-face rotted. Tree nearly dead.  
No trace found of original SE or SW trees.  
New BTs: 7" Incense cedar N 49° E 23.5 ft. Mkd:"S 2 CS BT."  
14" Doug. Fir S 45° E 51.2 ft. Mkd: " T 26 SR 6 W S 11 CS BT."  
16" Doug. Fir N 59° W 147.1 ft. Mkd: " T 26 SR 6 W S 3 CS BT."  
No trees near to S.W.  
A fence corner-fences South & East-bears S 55° E 14.5 ft.

1/4 Corner to Section 3 & 4

117

Found - White Oak (now 13" diam.) N 22° E 66 ft. Opened and found good scribing "1/4". (Ren. # 38)  
White Oak (now 18" diam.) N 54° W 59 ft. Shows good scar-did not open.  
Did not find iron rod set by Evans, nor Oak stake set by #171 Eppstein.  
Position for corner falls in center of creek, as measured from BTs.  
Set - Witness corner 25 ft. North  
Brass Cap Mkd: "County Surveyors Office 1964 T 26 SR 6 W W.C.  
25 ft. South to 1/4 s/s"  
4/3  
New BTs: 15" Doug. Fir N 5° W 25.6 ft. Mkd:"WC 1/4 S 4 CS BT".  
12" Doug. Fir N 11° E 50.0 ft. Mkd: "WC 1/4 S 3 CS BT".

Milo Godfrey, Deputy  
Wm. Stoffel, Mike Darby, Mike Stone  
May, 1964  
C. S. File No. 52/87